



HOSHIZAKI

PRODUCT GUIDE

ICE MACHINES | REACH-INS

HOSHIZAKI BEYOND STRONG.

OUR PRODUCTS. OUR PEOPLE.
OUR COMMITMENT TO YOU.



HOSHIZAKI is the world leader in the design and manufacture of ice and refrigeration products for the food service industry. With corporate headquarters in Peachtree City, Georgia, **HOSHIZAKI AMERICA, INC.'S** continuous innovation and commitment to the highest standards ensures that our customers have exceptional quality products.



CORPORATE MISSION

HOSHIZAKI AMERICA'S mission is to ensure optimal customer satisfaction by consistently delivering high-quality products and services throughout the Americas. The company aims to maintain a healthy organization and uphold its reputation as an innovative leader in the commercial kitchen equipment industry.



HOSHIZAKI AMERICA is proud to have been certified by the Georgia Department of Economic Development as **Georgia Made** for products manufactured in our production facilities in Peachtree City and Griffin Georgia.



CONTRIBUTING TO A SUSTAINABLE FUTURE

HOSHIZAKI AMERICA IS COMMITTED TO SOCIAL, ENVIRONMENTAL AND ECONOMIC SUSTAINABILITY.

We operate our facilities responsibly, as shown by our ISO 14001 certification. We recycle 90% of Stainless Steel, 87% of Galvanized Steel, 90% of Copper, 25% of Aluminum, and 90% of other scrap metal. Our ISO-9001 certification reflects our commitment to quality and regulatory standards.

We consistently use natural refrigerants and comply with US regulations, including lead content verification and energy standards, as well as Canadian NRCan. Our logistics partners participate in the SmartWay Partnership Program to reduce air pollution.

Our sustainability efforts are recognized by our 125+ Energy Star qualified units, multiple Energy Star Partner of the Year awards, and our products' classification as USBG LEED® credit qualifying.



NATURAL
REFRIGERANT



HOSHIZAKI products can contribute to satisfying EAc1, MRc2, MRc4, WEc3, IDc1, Pc18 credits under LEED®



ICE MACHINES

TYPES OF ICE	8
CUBER SERIES	10
Undercounter Cubers with Built-In Bins	12
KMEdge™ Crescent® Cubers	14
KMEdge™ Crescent® Cubers for Dispensers	18
KMEdge™ Crescent® Cubers - Serenity Series	19
IM Square Cubers Specialty Ice	26
CUBELET SERIES/FLAKERS	20
Undercounter Cubelet with Built-In Bins	22
Cubelet Ice Machines	23
Cubelet Beverage Dispensers	24
Cubelets - Serenity Series	25
Flakers	28
DISPENSER SERIES	30
DCM Ice & Water Dispensers	32
DM/DWM Dispensers	34
DB Hotel/Motel Dispensers	35
DISPENSER STANDS	36
TOP KIT MATRIX	37
ICE STORAGE BINS	38
REMOTE CONDENSERS & MATRIX	40
WATER FILTRATION	42
REMOTE MONITORING	43
ICE ACCESSORIES	106
ICE MACHINE MODEL CODE & USAGE GUIDE	112



Scan to
see our
Digital
Catalog



Scan to
see our
current
Price list

REACH-INS

REACH-INS	44
STEELHEART® SERIES	44
Upright Refrigerators & Freezers	46
Dual Temps	49
Pass-Thrus	50
Roll-Ins/Roll-Thrus	51
Heated Cabinets	52
Undercounter Refrigerators & Freezers	54
Undercounter Refrigerators Drawer / Door Combination	56
Undercounter Refrigerators with Drawers	57
Undercounter Freezers	58
Undercounter Sidemount Refrigerators	60
Undercounter Sidemount Refrigerators Drawer/Door Combination	62
Undercounter Sidemount Refrigerators with Drawers	63
Undercounter Sidemount Refrigerators Low-Profile	64
Worktop Refrigerators	68
Worktop Freezers	72
Worktop Sidemount Refrigerators & Freezers	74
Prep Tables Sandwich Top Refrigerators	76
Prep Tables - Mega Top Refrigerators	80
Prep Tables - Flat Lid Refrigerators	84
Prep Tables - Pizza Refrigerators	86
Chef Base Refrigerators	90
VALIANCE™	92
GLASS DOOR MERCHANDISERS	96
COMPACT UNDERCOUNTER REFRIGERATOR	98
SUSHI CASES	99
BACK BAR REFRIGERATION	100
REFRIGERATION ACCESSORIES	108

Ice

Hoshizaki Ice Machines maximize efficiency without compromising the quality. We offer clear, hard, and clean ice from machines guaranteed to last for years. Choose between **8 different types** of ice from air-cooled, water-cooled and remote air-cooled models. Versatile for any operation, our ice machines are perfect for restaurants and bars, convenience stores, hospitality industries, supermarkets, schools and universities, healthcare centers and more.






8 Types of Ice

with a variety of production & storage options

Crescent®

KMEdge™, hard, clear crescent® shape



Cubelet

Chewable, small pellet shape




Soft Cubelet

SOFT - Chewable, small pellet shape



Flaked

Soft, light, chewable moldable ice



Restaurants



University/School



Hotels



Business



Bars & Cocktail Lounges



Healthcare



C-Store



Grocery

Specialty Ice

Top Hat

Individual, hard, clear round shape



Sphere

Individual 1.8" in diameter, clear and solid



1by1 Cube

Individual, hard, clear square shape



2by2 Cube

Individual, hard, clear square shape



Specialty Ice - See page 26



CRESCENT® CUBERS

CLEAN, CLEAR, CRESCENT® CUBES

Clean, clear, individual crescent shaped cubes.
Longer-lasting equipment and the most efficient,
money-saving ice maker ever.



SCAN QR CODE
TO WATCH VIDEO



Energy Efficient

- Our CycleSaver design produces the same amount of ice in half the number of cycles
- Resulting in a longer total product life

Dual-sided Evaporator

- Makes ice on both sides of the evaporator
- Reduces energy costs by creating the most efficient heat exchange

Sanitary Components

- Removable air filters allow for easy and affordable maintenance
- Sealed compartments protect the evaporator, reducing bacteria growth and cleaning frequency

KM||EDGE™



Undercounter KM Crescent® Cubers - with Built-In Bins



KM-81BAJ★

17 3/4"W X 24"D X 39"H



Filter

Electrical

115V/60/1

Lbs. per 24 hours
90°A / 70°W | 70°A / 50°W
52 86

kWh per
100 Lbs.
8.5

Shipping
Weight
125 Lbs.

Self-Contained Bin Storage Capacity Up to 38 Lbs.



KM-116BAJ★

23 3/4"W X 24"D X 39"H



Filter

Electrical

115V/60/1

Lbs. per 24 hours
90°A / 70°W | 70°A / 50°W
100 125

kWh per
100 Lbs.
8.1

Shipping
Weight
146 Lbs.

Self-Contained Bin Storage Capacity Up to 53 Lbs.



KM-161B_J

23 3/4"W X 28"D X 39"H

Model

Electrical

Lbs. per 24 hours
90°A / 70°W | 70°A / 50°W

kWh per
100 Lbs.

Shipping
Weight

KM-161BAJ

115V/60/1

123

163

8.6

161 Lbs.

KM-161BWJ

115V/60/1

135

157

6.5

161 Lbs.



Filter

Self-Contained Bin Storage Capacity Up to 78 Lbs.

KM-231BAJ

24"W X 28"D X 39"H



Filter

Electrical

115V/60/1

Lbs. per 24 hours
90°A / 70°W | 70°A / 50°W
147 213

kWh per
100 Lbs.
8.4

Shipping
Weight
165 Lbs.

Self-Contained Bin Storage Capacity Up to 80 Lbs.

KM-301B_J

30"W X 28"D X 39"H

Model

Electrical

Lbs. per 24 hours
90°A / 70°W | 70°A / 50°W

kWh per
100 Lbs.

Shipping
Weight

KM-301BAJ

115V/60/1

212

290

7.1

206 Lbs.

KM-301BWJ

115V/60/1

237

265

4.9

189 Lbs.



Filter

Self-Contained Bin Storage Capacity Up to 100 Lbs.





KM-350M_J

22"W X 27 3/8"D X 28"H

Model	Electrical	Lbs. of Ice per 24 hours 90°A / 70°W 70°A / 50°W		kWh per 100 Lbs.	Shipping Weight
KM-350MAJ*	115V/60/1	393	489	5.4	175 Lbs.
KM-350MWJ	115V/60/1	383	414	4.9	175 Lbs.



Use URC-5FZ Condenser for Remote Air-Cooled Unit

KM-520M_J(Z)

22"W X 27 3/8"D X 28"H

Model	Electrical	Lbs. of Ice per 24 hours 90°A / 70°W 70°A / 50°W		kWh per 100 Lbs.	Shipping Weight
KM-520MAJ*	115V/60/1	480	556	4.7	175 Lbs.
KM-520MWJ	115V/60/1	444	474	4.7	175 Lbs.
KM-520MRJZ*	115V/60/1	495	547	4.8	175 Lbs.



Use URC-5FZ Condenser for Remote Air-Cooled Unit

KM-660M_J(Z)

22"W X 27 3/8"D X 28"H

Model	Electrical	Lbs. of Ice per 24 hours 90°A / 70°W 70°A / 50°W		kWh per 100 Lbs.	Shipping Weight
KM-660MAJ	115V/60/1	560	650	5.3	180 Lbs.
KM-660MWJ	115V/60/1	668	669	4.3	180 Lbs.
KM-660MRJZ*	115V/60/1	570	642	5.3	180 Lbs..



Use URC-5FZ Condenser for Remote Air-Cooled Unit



22 x 32 1/2 x 74 30 x 32 1/2 x 74 44 x 32 1/2 x 74 48 x 32 1/2 x 74 52 x 32 1/2 x 74

Dimensions shown in W x D x H include Bins. See TOP KIT MATRIX (pg 37) for top kit options based on bin size.

Bin graphic applies to all models on this page

CRESCENT® CUBERS | MODULAR



KM-901M_J(Z)(3) 30"W X 27 3/8"D X 32 1/2"H

Model	Electrical	Lbs. of Ice per 24 hours 90°A/70°W 70°A/50°W		kWh per 100 Lbs.	Shipping Weight
KM-901MAJ	208-230V/60/1	753	905	5.0	260
KM-901MWJ	208-230V/60/1	870	950	3.6	250
KM-901MRJZ*	208-230V/60/1	780	900	4.8	255
KM-901MRJZ3*	208-230V/60/3	830	927	4.0	250



Filter

Use URC-14FZ Condenser for Remote Air-Cooled Unit

KM-1100M_J(Z) 30"W X 27 3/8"D X 32 1/2"H

Model	Electrical	Lbs. of Ice per 24 hours 90°A/70°W 70°A/50°W		kWh per 100 Lbs.	Shipping Weight
KM-1100MAJ	208-230V/60/1	935	1087	4.9	290 Lbs.
KM-1100MWJ	208-230V/60/1	1006	1073	4.0	280 Lbs.
KM-1100MRJZ	208-230V/60/1	1030	1156	4.5	272 Lbs.

Model

Electrical

Kgs. of Ice per 24 hours
21°/10°C | 32°/21°C

kWh per
45 kgs.

Shipping
Weight

KM-1100MAJ50	220-240V/50/1	356	464	5.7	136 kg.
--------------	---------------	-----	-----	-----	---------



Filter

Use URC-14FZ Condenser for Remote Air-Cooled Unit




30 x 32 1/2 x 78 1/2



44 x 32 1/2 x 78 1/2



48 x 32 1/2 x 78 1/2



52 x 32 1/2 x 78 1/2

Dimensions shown in W x D x H include Bins. See TOP KIT MATRIX (pg 37) for top kit options based on bin size.



CRESCENT® CUBERS | MODULAR



Stackable | KMIEDGE

Hoshizaki's units are stackable for high volume production.




KM-1301S_J(Z)(3) 48"W X 27 3/8"D X 27 3/8"H

Model	Electrical	Lbs. of Ice per 24 hours		kWh per 100 Lbs.	Shipping Weight
		90°A / 70°W	70°A / 50°W		
KM-1301SAJ	208-230V/60/1	1301	1365	4.3	338 Lbs.
KM-1301SWJ	208-230V/60/1	1230	1247	3.8	335 Lbs.
KM-1301SRJZ	208-230V/60/1	1260	1400	4.3	335 Lbs.
KM-1301SAJ3*	208-230V/60/3	1350	1427	4.0	335 Lbs.
KM-1301SWJ3	208-230V/60/3	1355	1360	3.3	338 Lbs.
KM-1301SRJZ3*	208-230V/60/3	1330	1433	3.8	335 Lbs.



Use URC-14FZ Condenser for Remote Air-Cooled Unit



Dimensions shown in W x D x H include Bins. See TOP KIT MATRIX (pg 37) for top kit options based on bin size.




KM-1340M_J(Z)(3) 30"W X 27 3/8"D X 41 1/2" H

Model	Electrical	Lbs. of Ice per 24 hours		kWh per 100 Lbs.	Shipping Weight
		90°A / 70°W	70°A / 50°W		
KM-1340MAJ*	208-230V/60/1	1089	1275	4.8	315 Lbs.
KM-1340MWJ	208-230V/60/1	1280	1323	3.6	315 Lbs.
KM-1340MRJZ	208-230V/60/1	1177	1371	4.5	289 Lbs.
KM-1340MRJZ3*	208-230V/60/3	1266	1428	4.1	289 Lbs.



Use URC-14FZ Condenser for Remote Air-Cooled Unit



Dimensions shown in W x D x H include Bins. See TOP KIT MATRIX (pg 37) for top kit options based on bin size.



CRESCENT® CUBERS | MODULAR



Stackable | KMIEDGE

Hoshizaki's units are stackable for high volume production.



KM-1601MRJZ(3)


30"W X 27 3/8"D X 41 5/8"H

Model	Electrical	Lbs. of Ice per 24 hours 90°A / 70°W 70°A / 50°W		kWh per 100 Lbs.	Shipping Weight
KM-1601MRJZ	208-230V/60/1	1550	1594	4.4	316 Lbs.
KM-1601MRJZ3	208-230V/60/3	1550	1653	4.1	316 Lbs.



Filter

Use URC-22FZ Condenser for Remote Air-Cooled Unit



30 x 32 1/2 x 87 1/2 44 x 32 1/2 x 87 1/2 48 x 32 1/2 x 87 1/2 52 x 32 1/2 x 87 1/2

Dimensions shown in W x D x H include Bins. See TOP KIT MATRIX (pg 37) for top kit options based on bin size.



KM-1601S_J(Z)(3)


48"W X 27 3/8"D X 27 3/8"H

Model	Electrical	Lbs. of Ice per 24 hours 90°A / 70°W 70°A / 50°W		kWh per 100 Lbs.	Shipping Weight
KM-1601SAJ	208-230V/60/1	1433	1513	4.2	345 Lbs.
KM-1601SWJ	208-230V/60/1	1650	1660	3.3	335 Lbs.
KM-1601SRJZ*	208-230V/60/1	1600	1640	4.0	315 Lbs.
KM-1601SAJ3	208-230V/60/3	1414	1513	4.4	350 Lbs.
KM-1601SWJ3	208-230V/60/3	1660	1671	3.3	345 Lbs.
KM-1601SRJZ3	208-230V/60/3	1600	1635	4.1	355 Lbs.



Filter

Use URC-22FZ Condenser for Remote Air-Cooled Unit



48 x 32 1/2 x 73 3/8 48 x 32 1/2 x 101 3/4 52 x 32 1/2 x 73 3/8 52 x 32 1/2 x 101 3/4

Dimensions shown in W x D x H include Bins. See TOP KIT MATRIX (pg 37) for top kit options based on bin size



CRESCENT® CUBERS | MODULAR



Stackable | KMEDGE

Hoshizaki's units are stackable for high volume production.



KM-1900S_J(Z)(3)

48"W X 27 3/8"D X 36 7/16"H

Model	Electrical	Lbs. per 24 hours		kWh per 100 Lbs.	Shipping Weight
		90°A / 70°W	70°A / 50°W		
KM-1900SAJ*	208-230V/60/1	1675	1875	3.9	415 Lbs.
KM-1900SWJ	208-230V/60/1	1875	1880	3.2	415 Lbs.
KM-1900SRJZ*	208-230V/60/1	1700	1933	3.9	415 Lbs.
KM-1900SAJ3*	208-230V/60/3	1675	1865	3.9	415 Lbs.
KM-1900SWJ3	208-230V/60/3	1875	1880	3.2	415 Lbs.
KM-1900SRJZ3*	208-230V/60/3	1700	1933	3.9	415 Lbs.



Use URC-22FZ Condenser for Remote Air-Cooled Unit



Dimensions shown in W x D x H include Bins. See TOP KIT MATRIX (pg 37) for top kit options based on bin size.




KM-2200S_J(Z)(3)

48"W X 27 3/8"D X 36 7/16"H

Model	Electrical	Lbs. per 24 hours		kWh per 100 Lbs.	Shipping Weight
		90°A / 70°W	70°A / 50°W		
KM-2200SWJ3	208-230V/60/3	2200	2221	3.1	400 Lbs.
KM-2200SRJZ3*	208-230V/60/3	2075	2206	3.8	400 Lbs.



Use URC-22FZ Condenser for Remote Air-Cooled Unit



Dimensions shown in W x D x H include Bins. See TOP KIT MATRIX (pg 37) for top kit options based on bin size.



CRESCENT® CUBERS | MODULAR



Stackable | KMIEDGE

Hoshizaki's units are stackable for high volume production.



KM-2600S_JZ(3)


48"W X 27 3/8"D X 36 7/16"H

Model	Electrical	Lbs. of Ice per 24 hours 90°A / 70°W 70°A / 50°W		kWh per 100 Lbs.	Shipping Weight
KM-2600SWJ3	208-230V/60/3	2480	2482	3.6	440 Lbs.
KM-2600SRJZ3★	208-230V/60/3	2580	2617	3.6	440 Lbs.




Filter

Use URC-26JZ Condenser for Remote Air-Cooled Unit



48 x 32 1/2 x 73 3/8



52 x 32 1/2 x 87 1/2

Dimensions shown in W x D x H include Bins. See TOP KIT MATRIX (pg 37) for top kit options based on bin size.
See Top Kit Matrix on page 37 for additional bin options.



KMH-2100S_J(Z)(3)

36"W X 40"D X 36 7/16"H

Model	Electrical	Lbs. of Ice per 24 hours 90°A / 70°W 70°A / 50°W		kWh per 100 Lbs.	Shipping Weight
KMH-2100SWJ3	208-230V/60/3	2000	2060	2.9	415 Lbs.
KMH-2100SRJZ★	208-230V/60/1	1850	2034	3.8	415 Lbs.
KMH-2100SRJZ3★	208-230V/60/3	1925	2026	3.7	415 Lbs.



Filter

Use URC-22FZ Condenser for Remote Air-Cooled Unit

See Top Kit Matrix on page 37 for additional bin options.



CRESCENT® CUBERS | FOR DISPENSERS



KMD-355M_J

30"W X 24"D X 22"H

Model	Electrical	Lbs. of Ice per 24 hours 90°A / 70°W 70°A / 50°W		kWh per 100 Lbs.	Shipping Weight
KMD-355MAJ	115V/60/1	352	395	5.8	179 Lbs.
KMD-355MWJ	115V/60/1	385	395	4.4	179 Lbs.

KMD-505M_J

KMD-505MAJ	115V/60/1	415	500	5.6	176 Lbs.
KMD-505MWJ	115V/60/1	555	592	4.2	176 Lbs.
KMD-505MRJZ	115V/60/1	490	560	5.7	176 Lbs.



Filter

Use URC-5FZ Condenser for Remote Air-Cooled Unit
See Top Kit Matrix on page 45 for additional bin options.



KMD-705M_J

30"W X 24"D X 26"H

Model	Electrical	Lbs. per 24 hours 90°A / 70°W 70°A / 50°W		kWh per 100 Lbs.	Shipping Weight
KMD-705MAJ	115V/60/1	620	721	4.8	200 Lbs.
KMD-705MWJ	115V/60/1	720	773	3.8	200 Lbs.
KMD-705MRJZ	115V/60/1	670	727	4.4	200 Lbs.



Filter

Use URC-9FZ Condenser for Remote Air-Cooled Unit
See Top Kit Matrix on page 45 for additional bin options.



KMD-860M_J(Z)

30"W X 24 5/8"D X 28"H

Model	Electrical	Lbs. of Ice per 24 hours 90°A / 70°W 70°A / 50°W		kWh per 100 Lbs.	Shipping Weight
KMD-860MAJ	208-230V/60/1	665	855	5.2	248 Lbs.
KMD-860MWJ	208-230V/60/1	862	940	3.9	258 Lbs.
KMD-860MRJZ	208-230V/60/1	850	967	5.1	256 Lbs.



Filter

Use URC-9FZ Condenser for Remote Air-Cooled Unit

LANCER
A HOSHIZAKI Company




For Dispensers visit
our friends at Lancer
Worldwide



30 x 30 1/2 x 39 5/8



30 x 32 1/2 x 68 1/8



48 x 32 1/2 x 74

Dimensions shown in W x D x H include Bins. See TOP KIT MATRIX (pg 37) for top kit options based on bin size.



CRESCENT® CUBERS | FOR DISPENSERS



SERENITY SERIES

Serenity Series machines utilize a remote condenser and compressor, enabling high-volume units to be placed in compact spaces while minimizing noise. See page 41 for **Remote Condensers (Required)**.



KMS-822MLJ

22"W X 24 5/8"D X 28"H

Model	Electrical	Lbs. of Ice per 24 hours 90°A / 70°W 70°A / 50°W		kWh per 100 Lbs.	Shipping Weight
KMS-822MLJ using 1 Phase Remote Condenser	208-230V/60/1 *	770	851	5.3	150 Lbs.



Filter

Use SRK-10J Condenser for Remote Air-Cooled Unit (sold separately)
*115V supply for the KMS Ice maker is supplied from the SRK remote condenser



KMS-1122MLJ

22"W X 18 1/8"D X 31 1/4"H

Model	Electrical	Lbs. of Ice per 24 hours 90°A / 70°W 70°A / 50°W		kWh per 100 Lbs.	Shipping Weight
KMS-1122MLJ using 1 Phase Remote Condenser	208-230V/60/1 *	1075	1151	4.2	152 Lbs.
KMS-1122MLJ* using 3 Phase Remote Condense	208-230V/60/3 *	1100	1151	4.0	152 Lbs.



Filter

Use SRK-12J or SRK-12J3 Condenser for Remote Air-Cooled Unit (sold separately)
*115V supply for the KMS Ice maker is supplied from the SRK remote condenser



KMS-1402MLJ

30"W X 24"D X 28"H

Model	Electrical	Lbs. of Ice per 24 hours 90°A / 70°W 70°A / 50°W		kWh per 100 Lbs.	Shipping Weight
KMS-1402MLJ using 1 Phase Remote Condenser	208-230V/60/1 *	1400	1501	4.3	178 Lbs.
KMS-1402MLJ using 3 Phase Remote Condense	208-230V/60/3 *	1325	1474	4.6	178 Lbs.



Filter

Use SRK-15/15J3 Condenser for Remote Air-Cooled Unit (sold separately)
*115V supply for the KMS Ice maker is supplied from the SRK remote condenser

KMS-2000MLJ

30"W X 24"D X 32 7/8"H

Model	Electrical	Lbs. of Ice per 24 hours 90°A / 70°W 70°A / 50°W		kWh per 100 Lbs.	Shipping Weight
KMS-2000MLJ using 1 Phase Remote Condenser	208-230V/60/1 *	1850	1926	4.5	206 Lbs.
KMS-2000MLJ using 3 Phase Remote Condense	208-230V/60/3 *	1900	1938	4.3	206 Lbs.



Filter

Use SRK-20J or SRK-20J3 Condenser for Remote Air-Cooled Unit (sold separately)
*115V supply for the KMS Ice maker is supplied from the SRK remote condenser



CUBELET



CHEWABLE, SOFT, SMALL NUGGET-SHAPED


Hoshizaki's chewable nugget-shaped ice is designed to enhance beverages with the perfect balance of texture and flavor absorption. Available in two options—Cubelet Ice and Soft Cubelet Ice—each type offers ideal consistency for easy dispensing and long-lasting enjoyment **perfect for hospitality, healthcare, offices, and food service.**

ADVANCED
CleanCycle²



Cubelet

- Chewable, soft, small nugget-shaped
- Available in 3 sizes






What is Soft Cubelet Ice?

A smaller, softer version of cubelet ice, engineered to be truly chewable—easy on teeth and great for sipping and crunching. The porous nature absorbs flavor, making beverages taste more integrated, even toward the end of the drink.

Soft Cubelet

- Smaller, softer nugget-shaped ice
- Scoop from bin only. Not intended to be dispensed.



CUBELET | SELF-CONTAINED



Undercounter Cubelets with Built-In Bin



-DS shown with Custom Cabinetry

C-80BAK Mini Cubelet

14 7/8"W X 22 5/8"D X 33 1/2"H

The ADA compliant machine dimensions are 14 7/8"W x 22 5/8"D x 31 1/2"H

Model	Electrical	Lbs. per 24 hours		kWh per 100 Lbs.	Shipping Weight
		90°A / 70°W	70°A / 50°W		
C-80BAK	115V/60/1	65	92	8.5	134 Lbs.
C-80BAK-DS	115V/60/1	65	92	8.5	134 Lbs.
C-80BAK-AD	115V/60/1	65	92	8.5	134 Lbs.
C-80BAK-ADDS	115V/60/1	65	92	8.5	134 Lbs.



Filter

Self-Contained Bin Storage Capacity Up to 22 Lbs.
UL approved for outdoor use ADA compliant

†-DS Models - Wood Door System
(Designed to accommodate custom cabinetry)



F-330BAJ-C Mini Cubelet

24"W X 26"D X 39"H (6" Legs Included)



Filter

Electrical	Lbs. per 24 hours		kWh per 100 Lbs.	Shipping Weight
	90°A / 70°W	70°A / 50°W		
115V/60/1	214	288	7.3	178 Lbs.

Self-Contained Bin Storage Capacity Up to 80 Lbs.



F-450MAJ-C Mini Cubelet


22"W X 27 3/8"D X 22"H



Filter

Electrical	Lbs. per 24 hours		kWh per 100 Lbs.	Shipping Weight
	90°A / 70°W	70°A / 50°W		
115V/60/1	316	412	6.1	170 Lbs.

*Not recommended for dispensing applications.



30 x 32 1/2 x 55 3/8 22 x 32 1/2 x 68 30 x 32 1/2 x 68 44 x 32 1/2 x 68 48 x 32 1/2 x 68 52 x 32 1/2 x 68

Dimensions shown in W x D x H include Bins. See TOP KIT MATRIX (pg 37) for top kit options based on bin size.



CUBELET | SELF-CONTAINED




F-801M_J-C Small Cubelet

22"W X 27 3/8"D X 26"H

Model	Electrical	Lbs. per 24 hours 90°A / 70°W 70°A / 50°W		kWh per 100 Lbs.	Shipping Weight
F-801MAJ-C*	115V/60/1	532	690	5.00	205 Lbs.
F-801MWJ-C	115V/60/1	580	632	4.13	205 Lbs.



Filter



30 x 32 1/2 x 59 3/8 22 x 32 1/2 x 72 30 x 32 1/2 x 72 44 x 32 1/2 x 72 48 x 32 1/2 x 72 52 x 32 1/2 x 72

Dimensions shown in W x D x H include Bins. See TOP KIT MATRIX (pg 37) for top kit options based on bin size.

F-1002M_J(Z)-C Small Cubelet


22"W X 27 3/8"D X 26"H

Model	Electrical	Lbs. per 24 hours 90°A / 70°W 70°A / 50°W		kWh per 100 Lbs.	Shipping Weight
F-1002MAJ-C	115V/60/1	726	890	4.57	210 Lbs.
F-1002MWJ-C	115V/60/1	770	878	3.95	205 Lbs.
F-1002MRJZ-C	115V/60/1	680	821	4.94	210 Lbs.



Filter

Use URC-5FZ Condenser for Remote Air-Cooled Unit



22 x 32 1/2 x 72 30 x 32 1/2 x 72 44 x 32 1/2 x 72 48 x 32 1/2 x 72 52 x 32 1/2 x 72

Dimensions shown in W x D x H include Bins. See TOP KIT MATRIX (pg 37) for top kit options based on bin size.



F-1501M_J(Z)-C Medium Cubelet

30"W X 27 3/8"D X 34 7/16"H

Model	Electrical	Lbs. per 24 hours 90°A / 70°W 70°A / 50°W		kWh per 100 Lbs.	Shipping Weight
F-1501MAJ-C	208-230V/60/1	1020	1327	4.61	325 Lbs.
F-1501MWJ-C	208-230V/60/1	1218	1376	3.76	330 Lbs.
F-1501MRJZ-C	208-230V/60/1	1054	1353	4.50	325 Lbs.



Filter

Electrical	Lbs. per 24 hours 90°A / 70°W 70°A / 50°W		kWh per 100 Lbs.	Shipping Weight
208-230V/60/1	1500	1832	4.35	345 Lbs.

Use URC-14FZ Condenser for Remote Air-Cooled Unit

Use URC-22FZ Condenser for Remote Air-Cooled Unit



30 x 32 1/2 x 79 1/4 44 x 32 1/2 x 79 1/4 48 x 32 1/2 x 79 1/4 52 x 32 1/2 x 79 1/4

Dimensions shown in W x D x H include Bins. See TOP KIT MATRIX (pg 37) for top kit options based on bin size.



CUBELET | BEVERAGE DISPENSER



FD-650M_J(Z)-C Small Cubelet

22"W X 24"D X 26"H

Model	Electrical	Lbs. per 24 hours		kWh per 100 Lbs.	Shipping Weight
		90°A / 70°W	70°A / 50°W		
FD-650MAJ-C	115V/60/1	495	634	5.5	185 Lbs.
FD-650MWJ-C	115V/60/1	520	622	4.0	185 Lbs.
FD-650MRJZ-C★	115V/60/1	470	588	5.0	185 Lbs.



Filter

Use URC-5FZ Condenser for Remote Air-Cooled Unit

See TOP KIT MATRIX (pg 37) for top kit options based on bin size.

FD-1002M_J(Z)-C Small Cubelet

22"W X 24"D X 26"H

Model	Electrical	Lbs. per 24 hours		kWh per 100 Lbs.	Shipping Weight
		90°A / 70°W	70°A / 50°W		
FD-1002MAJ-C	115V/60/1	726	890	4.6	210 Lbs.
FD-1002MRJZ-C	115V/60/1	680	821	4.9	210 Lbs..



Filter

Use URC-5FZ Condenser for Remote Air-Cooled Unit

See TOP KIT MATRIX (pg 37) for top kit options based on bin size.

Available in all stainless steel (-C) or gloss black vinyl clad front cover with stainless steel top and sides (-CB).

FD-1002M_J(Z)-CB Small Cubelet

22"W X 24"D X 26"H

Model	Electrical	Lbs. per 24 hours		kWh per 100 Lbs.	Shipping Weight
		90°A / 70°W	70°A / 50°W		
FD-1002MAJ-CB	115V/60/1	726	890	4.6	210 Lbs.
FD-1002MRJZ-CB	115V/60/1	680	821	4.9	210 Lbs..



Filter

Use URC-5FZ Condenser for Remote Air-Cooled Unit

See TOP KIT MATRIX (pg 37) for top kit options based on bin size.



CUBELET | BEVERAGE DISPENSER



SERENITY SERIES

Serenity Series machines utilize a remote condenser and compressor, enabling high-volume units to be placed in compact spaces while minimizing noise. See page 41 for **Remote Condensers (Required)**.




FS-1001MLJ-C Small Cubelet

30"W X 11"D X 26"H

Filter	Electrical	Lbs. per 24 hours 90°A / 70°W 70°A / 50°W		kWh per 100 Lbs.	Shipping Weight	Shipping Weight
	115V/60/1	720	851	5.1	166 Lbs.	166 Lbs.

Use SRC-10J Condenser for Remote Air-Cooled Unit




FS-1022MLJ-C Small Cubelet

22"W X 16 1/2"D X 26"H

Filter	Electrical	Lbs. per 24 hours 90°A / 70°W 70°A / 50°W		kWh per 100 Lbs.	Shipping Weight	Shipping Weight
	115V/60/1	730	889	5.1	150 Lbs.	150 Lbs.

Designed for use on beverage dispensers.

Use SRC-10J Condenser for Remote Air-Cooled Unit




FS-1501MLJ-C Medium Cubelet

30"W X 16 1/2"D X 34 1/4"H

Filter	Electrical	Lbs. per 24 hours 90°A / 70°W 70°A / 50°W		kWh per 100 Lbs.	Shipping Weight	Shipping Weight
	115V/60/1	1125	1386	4.75	229 Lbs.	229 Lbs.

Designed for use on beverage dispensers.

Use SRC-14J Condenser for Remote Air-Cooled Unit



Creative Cocktails

HOSHIZAKI SPECIALTY ICE

ELEVATE YOUR COCKTAIL PROGRAM



- ◆ Create upscale signature cocktails
- ◆ Increase revenue per cocktail
- ◆ Perfect amount of chilling with minimal dilution
- ◆ Perfect for preparation & presentation



-DS shown with Custom Cabinetry



AM Cubers with Built-In Bins

AM-50BAK

14 7/8"W X 22 5/8"D X 33 1/2"H

The ADA compliant machine dimensions are 147/8"W x 225/8"D x 311/2"H



Model	Electrical	Lbs. per 24 hours		kWh per 100 Lbs.	Shipping Weight
		90°A / 70°W	70°A / 50°W		
AM-50BAK	115V/60/1	35	51	17	113 Lbs.
AM-50BAK-DS	115V/60/1	35	51	17	113 Lbs.
AM-50BAK-AD	115V/60/1	34	55	16.8	112 Lbs.
AM-50BAK-ADDS	115V/60/1	34	55	16.8	112 Lbs.



Filter

Self-Contained Bin Storage Capacity Up to 22 Lbs.

†-DS Models - Wood Door System
(Designed to accommodate custom cabinetry)

Scan to view
Specialty Ice
Machines



SPECIALTY ICE



1by1 Cube with Built-In Bin

IM-200BAC

39 1/2"W X 23 5/8"D X 33 1/2"H (6" Legs Included)



Filter

Electrical

115V/60/1

Lbs. per 24 hours
90°A / 70°W | 70°A / 50°W

150 188


kWh per
100 Lbs.

8.4

Shipping
Weight

212 Lbs.

Self-Contained Bin Storage Capacity Up to 75 Lbs.



1by1 Cube Stackable Cuber

IM-500SAB

44" W x 27-5/8" D x 21-3/4" H



Filter

Electrical

115V/60/1

Lbs. per 24 hours
90°A / 70°W | 70°A / 50°W


414 489

kWh per
100 Lbs.

5.8

Shipping
Weight

234 Lbs.



Dimensions shown in W x D x H include Bins. See TOP KIT MATRIX (pg 37) for top kit options based on bin size.

See TOP KIT MATRIX (pg 37) for top kit options based on bin size.



Sphere Ice Machine with Built-In Bin

IM-50BAA-Q

24 3/4" W X 20 3/4"D X 39 1/2"H (6" Legs Included)



Electrical

115V/60/1

Lbs. per 24 hours
90°A / 70°W | 70°A / 50°W

45 50

kWh per
100 Lbs.

15.7

Cubes produced
in 24 hour period

~ 475

Shipping
Weight

168 Lbs.



Filter

Self-Contained Bin Storage Capacity Up to 36 Lbs.



2by2 Cube with Built-In Bin

IM-50BAA-LM

19 3/4" W X 17 3/4"D X 39 1/2"H (6" Legs Included)



Electrical

115V/60/1

Lbs. per 24 hours
90°A / 70°W | 70°A / 50°W

45 50

kWh per
100 Lbs.

15.7

Cubes produced in
24 hour period

~ 172


Shipping
Weight

137 Lbs.



Filter

Self-Contained Bin Storage Capacity Up to 22 Lbs.



Flaker



SOFT, LIGHT, MOLDABLE, VARIOUS SHAPES

Flaked ice is relatively dry and cools more quickly than other forms of ice. A 2-second flush of the evaporator occurs every hour to reduce impurity and mineral build up, improving sanitation and reliability.



Undercounter FLAKER with Built-In Bin

F-330BAJ

24"W X 26"D X 39"H (6" Legs Included)



Filter

Electrical

Lbs. per 24 hours
90°A / 70°W | 70°A / 50°W

kWh per
100 Lbs.

Shipping
Weight

115V/60/1

243

332

6.0

178 Lbs.

Self-Contained Bin Storage Capacity Up to 80 Lbs.

F-450MAJ

22"W X 27 3/8"D X 22"H



Filter

Electrical

Lbs. per 24 hours
90°A / 70°W | 70°A / 50°W

kWh per
100 Lbs.

Shipping
Weight

115V/60/1

395

492

4.9

170 Lbs.

F-801M_J

22"W X 27 3/8"D X 26"H

Model

Electrical

Lbs. per 24 hours
90°A / 70°W | 70°A / 50°W

kWh per
100 Lbs.

Shipping
Weight

F-801MAJ★

115V/60/1

566

751

4.5

205 Lbs.

F-801MWJ

115V/60/1

605

680

3.9

205 Lbs.



Filter



30 x 32 1/2 x 55 3/8



22 x 32 1/2 x 68



30 x 32 1/2 x 68



44 x 32 1/2 x 68



48 x 32 1/2 x 68



52 x 32 1/2 x 68

Dimensions shown in W x D x H include Bins. See TOP KIT MATRIX (pg 37) for top kit options based on bin size.

FLAKER | SELF-CONTAINED



F-1002M_J(Z)


22"W X 27 3/8"D X 26"H

Model	Electrical	Lbs. per 24 hours		kWh per 100 Lbs.	Shipping Weight
		90°A / 70°W	70°A / 50°W		
F-1002MAJ	115V/60/1	758	980	4.4	210 Lbs.
F-1002MWJ	115V/60/1	833	955	3.6	205 Lbs.
F-1002MRJZ	115V/60/1	722	907	4.5	210 Lbs.
F-1002MLJ	115V/60/1	797	1028	1.5	150 Lbs.



Filter

Use URC-5F Condenser for Remote Air-Cooled Unit



Dimensions shown in W x D x H include Bins. See TOP KIT MATRIX (pg 37) for top kit options based on bin size.



F-2001M_J(Z)(3)

30"W X 27 1/2"D X 34 5/8"H

Model	Electrical	Lbs. per 24 hours		kWh per 100 Lbs.	Shipping Weight
		90°A / 70°W	70°A / 50°W		
F-2001MWJ	208-230V/60/1	1840	2043	3.2	342 Lbs.
F-2001MRJZ	208-230V/60/1	1660	2073	3.8	360 Lbs.
F-2001MRJZ3	208-230V/60/3	1675	2098	3.9	360 Lbs.
F-2001MLJ	115V/60/1	1733	2280	0.6	250 Lbs.


F-1501M_J(Z)

30" W x 27-3/8" D x 34-5/8" H

Model	Electrical	Lbs. per 24 hours		kWh per 100 Lbs.	Shipping Weight
		90°A / 70°W	70°A / 50°W		
F-1501MAJ	208-230V/60/1	1154	1543	4.0	325 Lbs.
F-1501MWJ	208-230V/60/1	1410	1624	3.2	350 Lbs.
F-1501MRJZ	208-230V/60/1	1181	1532	4.0	325 Lbs.



Filter



Dimensions shown in W x D x H include Bins. See TOP KIT MATRIX (pg 37) for top kit options based on bin size.



DISPENSERS

CRESCENT® AND CUBELET ICE FOR DISPENSERS

Hydration Made Easy! Hoshizaki offers a complete range of ice and water dispensers, including options for Crescent® or Cubelet ice, as well as both countertop and freestanding units. Each dispenser is designed to produce and store varying amounts of ice, ensuring that you can find the perfect fit for your needs, whether for a cozy office break room or a bustling hotel. Enjoy having ice-cold drinks and refreshing water readily available! - be it a small office breakroom or a busy high-rise hotel.

Features & Benefits

- Attractive stainless steel exterior provides long life and easy maintenance
- Three dimensional agitation prevents clumping and assists in delivering ice conveniently
- DB Series accommodates KMEdge™ Series Cubers
- DCM Series dispenses easy to chew cubelet ice and water
- All dispensers feature built-in ice storage capacity





OptiServe TOUCHLESS ICE & WATER

- Hands free dispensing that helps eliminate cross contamination
- For sanitary use in breakroom areas, lobbies, nursing stations, cafeterias and more -
- Hoshizaki's DCM dispensers can sit on top of a counter or stand for additional storage



IDEAL FOR HEALTHCARE OPERATIONS

DISPENSERS | SELF-CONTAINED



DCM-271BAH Mini Cubelet

16 5/8" W X 24 1/4"D X 31 3/4"H (4" Legs Included)

Electrical	Lbs. per 24 hours 90°A / 70°W 70°A / 50°W		kWh per 100 Lbs.	Shipping Weight
115V/60/1	196	257	6.9	154 Lbs.

Self-Contained Bin Storage Capacity Up to 10 Lbs.



On a counter without legs
or on a stand



**Floor Model
with Optional Stand**
16 9/16 x 24 1/8 x 66 7/8
W x D x H



**Counter-Top
with 4" Legs**
16 9/16 x 24 1/8 x 31 11/16
W x D x H



DCM-300BAH Mini Cubelet

26"W X 22 1/2"D X 40"H (Unit supplied without legs)

Condenser	Lbs. per 24 hours 90°A / 70°W 70°A / 50°W		kWh per 100 Lbs.	Shipping Weight
115V/60/1	232	321	6.8	220 Lbs.

Self-Contained Bin Storage Capacity Up to 40 Lbs.

DCM-500B_H Small Cubelet

26"W X 22 1/2"D X 40"H (Unit supplied without legs)

Model	Condenser	Lbs. per 24 hours 90°A / 70°W 70°A / 50°W		kWh per 100 Lbs.	Shipping Weight
DCM-500BAH	115V/60/1	450	618	5.6	255 Lbs.
DCM-500BWH	115V/60/1	512	590	4.5	255 Lbs.

Self-Contained Bin Storage Capacity Up to 40 Lbs.



DCM-75_B_H Medium Cubelet

34 1/16"W X 28 1/2"D X 48 1/16"H
(Unit supplied without legs)

Model	Condenser	Lbs. per 24 hours 90°A / 70°W 70°A / 50°W		kWh per 100 Lbs.	Shipping Weight
DCM-752BAH	115V/60/1	576	708	5.1	345 Lbs.
DCM-751BWH	115V/60/1	678	782	4.8	345 Lbs.

Self-Contained Bin Storage Capacity Up to 95 Lbs.

FOR: DCM 300BAH/500BAH/75_BAH



**Counter-Top
with Optional 6" Legs**
26 x 22 1/2 x 40
W x D x H



**Counter-Top
with Optional 6" Legs**
26 x 22 1/2 x 46
W x D x H



**Floor Model
with Optional Stand**
26 x 22 1/2 x 72 1/2
W x D x H



DISPENSERS | SELF-CONTAINED



Hands-free sensor designed for use with opaque containers. Not intended for outdoor use - avoid placement in direct sunlight.



DCM-271BAH-OS Mini Cubelet

16 5/8" W X 24 1/4" D X 31 3/4" H (4" Legs Included)

Condenser	Lbs. per 24 hours 90°A / 70°W 70°A / 50°W		kWh per 100 Lbs.	Shipping Weight
115V/60/1	196	257	6.9	154 Lbs.

Self-Contained Bin Storage Capacity Up to 10 Lbs.



On a counter without legs
or on a stand



**Floor Model
with Optional Stand**
16 5/8 x 24 1/4 x 66 7/8
W x D x H



**Counter-Top
with 4" Legs**
16 5/8 x 24 1/4 x 31 3/4
W x D x H



DCM-300BAH-OS Mini Cubelet

26"W X 22 1/2"D X 40"H (Unit supplied without legs)

Condenser	Lbs. per 24 hours 90°A / 70°W 70°A / 50°W		kWh per 100 Lbs.	Shipping Weight
115V/60/1	232	321	6.8	240 Lbs.

Self-Contained Bin Storage Capacity Up to 40 Lbs.

DCM-500B_H-OS Small Cubelet

26"W X 22 1/2"D X 40"H (Unit supplied without legs)

Model	Condenser	Lbs. per 24 hours 90°A / 70°W 70°A / 50°W		kWh per 100 Lbs.	Shipping Weight
DCM-500BAH-OS	115V/60/1	450	618	5.6	276 Lbs.
DCM-500BWH-OS	115V/60/1	512	590	4.5	269 Lbs.

Self-Contained Bin Storage Capacity Up to 40 Lbs.



DCM-75_B_H-OS Medium Cubelet

34 1/16"W X 28 1/2"D X 48 1/16"H
(Unit supplied without legs)

Model	Condenser	Lbs. per 24 hours 90°A / 70°W 70°A / 50°W		kWh per 100 Lbs.	Shipping Weight
DCM-752BAH-OS	115V/60/1	576	708	5.1	345 Lbs.
DCM-751BWH-OS	115V/60/1	678	782	4.8	345 Lbs.

Self-Contained Bin Storage Capacity Up to 95 Lbs.

Units supplied without legs

FOR: DCM 300BAH/500B_H/75_B_H



Counter-Top
26 x 22 1/2 x 40
W x D x H



**Counter-Top
with Optional 6" Legs**
26 x 22 1/2 x 46
W x D x H



**Floor Model
with Optional Stand**
26 x 22 1/2 x 72 1/2
W x D x H



DISPENSERS



KM|EDGE Crescent®




DM-200B

30"W X 28"D X 36 3/8"H


Electrical	Application Ice Storage Capacity	Dispensing Rate	Icemaker Production per 24 hrs.	Icemaker kWh per 100 lbs.	Shipping Weight
115V/60/1	200 Lbs.	7.5 lbs. / min.	N/A	N/A	210 Lbs.



Unit supplied without legs / Only dispenses Crescent® ice



Counter-Top
30 x 28 x 36 3/8
W x D x H



Counter-Top
with optional 4" legs
30 x 28 x 40 3/8
W x D x H



Cubelet



DM-4420N

22"W X 30 1/2"D X 40"H

Electrical	Application Ice Storage Capacity	Dispensing Rate	Icemaker Production per 24 hrs.	Icemaker kWh per 100 lbs.	Shipping Weight
115V/60/1	200 Lbs.	N/A	N/A	N/A	185 Lbs.



Canadian Energy Performance Verified Rendement
Energetique Verified



Hoshizaki's Stands are specifically designed to support ice machines and dispensers, making them more accessible while also providing storage for accessories and tools.

SEE PAGE 36 FOR DISPENSER STANDS

HOTEL DISPENSERS



KMEDGE Crescent® DB Dispensers

DB-130H

22"W X 30"D X 53"H (6" Legs Included)

Electrical	Application Ice Storage Capacity	Dispensing Rate	Icemaker kWh per 100 lbs.	Shipping Weight
115V/60/1	130 Lbs.	20 lbs. / min.	N/A	220 Lbs.



22 x 30 x 53
W x D x H



KM-350/520/660M
Cuber sold separately
22 x 30 x 81
W x D x H



DB-200H

30"W X 30"D X 53"H (6" Legs Included)

Electrical	Application Ice Storage Capacity	Dispensing Rate	Icemaker kWh per 100 lbs.	Shipping Weight
115V/60/1	200 Lbs.	13 lbs. / min.	N/A	220 Lbs.



30 x 30 x 53
W x D x H



KML-325/500
Cuber sold separately
30 x 30 x 75
W x D x H



KML-700
Cuber sold separately
30 x 30 x 79
W x D x H



On a counter without legs
or on a stand

DB Water Dispenser CONVERSION KIT



Convert existing DB-130H or DB-200H ice only
dispensers to an ice and water dispenser with
HS-5749. (shown with KMD-705MAJ)



On a counter without legs
or on a stand

DISPENSER | STANDS / BAGGERS



Hoshizaki's Stands are specifically designed to support ice machines and dispensers, making them more accessible while also providing storage for accessories and supplies.

Model Number	Use with Ice Machine / Dispenser Model	Dimensions W x D x H (Height includes 6" legs)	Shipping Weight
SD-200	DM-200B	30" x 28" x 32 ^{13/16} "	105 lbs.
SD-271	DCM-271 (-OS)	16 ^{1/2} " x 24" x 35 ^{3/16} "	85 lbs.
SD-500	DCM-300 (-OS) / DCM-500 (-OS)	25 ^{7/8} " x 22" x 32 ^{3/4} "	90 lbs.
SD-750	DCM-751 (-OS) / DCM-752 (-OS)	34" x 28" x 32 ^{3/4} "	110 lbs.



- Heavy duty stands for floor model ice machines/dispensers
- Easy cleaning and maintenance
- Attractive stainless steel exterior
- Locking doors standard

HCD ICE BAGGING SYSTEM SERIES	Model Number	Exterior Finish	Application Ice Storage Capacity	Dimensions W x D x H	Shipping Weight
	HCD-500B	Stainless Steel	647 Lbs.	30" x 36" x 71"	510 Lbs.
	HCD-1000B	Stainless Steel	1078 Lbs.	48" x 36" x 71"	590 Lbs.

48" heavy duty ice paddle included





Use this chart to determine if your Ice Maker will require a “Top Kit” adapter to fit on your preferred bin.

	22" Width KM-350M KM-520M KM-660M F-450M F-801M F-1002M	22" Width KMD-410M† KMS-822M FD-650M-C† FD-1002M-C	30" Width KM-901M KM-1100M KM-1340M KM-1601M KML Series F-1501M F-2001	30" Width KMD-355M KMD-505M KMD-705M KMD-460M‡ KMD-530M‡ KMD-860M‡ KMS-1402M* KMS-2000M*	44" Width 2 KM-350M 2 KM-520M 2 KM-660M IM-500S 2 F-450M 2 F-801M 2 F-1002M	44" Width 2 KMD-410M 2 FD-650M-C 2 FD-1002M-C	48" Width KM-1301S KM-1400S KM-1601S KM-1900S KM-2200S KM-2600S	60" Width 2 KM-901M 2 KM-1100M 2 KM-1340M 2 KM-1601M 2 KML Series 2 F-1501/2001M 2 KMD Series*‡
22" Width B-300SF DB-130H	—	HS-2153 (KMD-410 on B-300 only) (KMD-410 not compatible with DB-130H)	N/A	N/A	N/A	N/A	N/A	N/A
BD-300SF†	N/A	—	N/A	N/A	N/A	N/A	N/A	N/A
30" Width B-250SF B-500SF	HS-2033	HS-2033 & HS-2129	—	HS-2129	N/A	N/A	N/A	N/A
BD-500SF†	N/A	N/A	N/A	— (Only fits KMD Units)	N/A	N/A	N/A	N/A
44" Width B-700SF	HS-2035	HS-2035 & HS-2130	HS-2034	HS-2130 & HS-2034	—	HS-2130 (KMD-410M doesn't apply.)	N/A	N/A
48" Width B-800SF	HS-2035 & HS-2032	HS-2035, HS-2032 & HS-2131	HS-2034 & HS-2032	HS-2131, HS-2034 & HS-2032	HS-2032	HS-2032 & HS-2131	—	N/A
48" Width B-1150SS B-1300SS	UNIVERSAL TOP KIT INCLUDED	N/A	UNIVERSAL TOP KIT INCLUDED	UNIVERSAL TOP KIT INCLUDED & HS-2147	IM & F UNITS ONLY (HS-5397 for IM-500)	N/A	UNIVERSAL TOP KIT INCLUDED	N/A
52" Width B-900SF	HS-2035 & HS-2033	HS-2035, HS-2033 & HS-2132	HS-2035	HS-2132 & HS-2035	HS-2033	HS-2033 & HS-2132	HS-2032	N/A
60" Width B-1500SS B-1650SS	N/A	N/A	UNIVERSAL TOP KIT INCLUDED & HS-2111	N/A	UNIVERSAL TOP KIT INCLUDED (HS-5397 for IM-500)	N/A	UNIVERSAL TOP KIT INCLUDED	UNIVERSAL TOP KIT INCLUDED
30" Width DB-200H DM-200B	HS-2036 (Only fits KM Units)	N/A	— (KML Series only)	NEED HS-2148 (KMD Series on DB-200H only)	N/A	N/A	N/A	N/A

— No top kit necessary | N/A Combination of ice maker and bin is not possible

*Except KMD-410M (See 22" Wide), †BD Bins Fit 24" to 24 1/2" Deep Ice makers w/o Top Kit, ‡HS-5065 Req'd for Air Cooled KMD-460/530MAJ

KMS[§], KMD, or FD on Bin Need Top Kit Extension:

Model Number	For Use With
HS-2129	B-250SF / B-500 Bins
HS-2130	B-700 Bins
HS-2131	B-800 Bins
HS-2132	B-900 Bins
HS-2147	B-1150 & 1300 Bins
HS-2153	B-300 Bins
HS-5424	KMD on DB-130
HS-2032	4" ABS Top Kit
HS-2033	8" ABS Top Kit

§Except KMS-1122MLJ

36" Width - KMH-2100S - Fit Kloppenberg Bins Only (Sold Separately)

Model Number	Description
HS-2034	14" ABS Top Kit
HS-2035	22" ABS Top Kit
HS-2036	(2) 4" ABS Top Kits for KM on DB-200H
HS-2066	Seismic Kit for SD 500 Stands
HS-2071	Anchored Leg Kit SD 500 Stands
HS-2111	11.3" x 26.2" Stainless Cover/Separator
HS-2148	30" x 3.1" Stainless Cover
HS-2153	KMD-410 on B-300 bin
HS-2160	2 KM-901M
HS-5065	Front Panel Filter Kit for KMD-460/530M
HS-5397	Bin Control Kit for IM-500 on B-1150/1300/1500/1650

ICE | STORAGE BINS

The non-corrosive bin liner guarantees safe and sanitary ice storage. The foamed-in-place polyurethane insulation in all side walls and bottom of the bin provide reliable ice storage.

B-250SF



Exterior Finish	Application Ice Storage Capacity	Dimensions W x D x H (Height includes 6" legs)	Shipping Weight
Stainless Steel	250 Lbs.	30" x 32 1/3" x 33 3/8"	110 Lbs.

Four 6" Painted Legs included
Refer to Top Kit Matrix for necessary configurations

B-300SF BD-300SF**



Model	Exterior Finish	Application Ice Storage Capacity	Dimensions W x D x H (Height includes 6" legs)	Shipping Weight
B-300SF	Stainless Steel	300 Lbs.	22" x 32 1/3" x 46"	125 Lbs.

Four 6" Painted Flanged Legs included
Refer to Top Kit Matrix for necessary configurations

Model	Exterior Finish	Application Ice Storage Capacity	Dimensions W x D x H (Height includes 6" legs)	Shipping Weight
BD-300SF	Stainless Steel	300 Lbs.	22" x 32 1/3" x 46"	130 Lbs.

Four 6" Painted Flanged Legs included
For use with **KMD-410M, KMS-822M, FD-650M-C, FD-1002M-C**
**BD Bins fit 24" to 24 1/2" deep Ice Machines without Top Kit extension

B-500SF BD-500SF**



Model	Exterior Finish	Application Ice Storage Capacity	Dimensions W x D x H (Height includes 6" legs)	Shipping Weight
B-500SF	Stainless Steel	500 Lbs.	30" x 32 1/2" x 46"	140 Lbs.

Four 6" Painted Legs included
Refer to Top Kit Matrix for necessary configurations

Model	Exterior Finish	Application Ice Storage Capacity	Dimensions W x D x H (Height includes 6" legs)	Shipping Weight
BD-500SF	Stainless Steel	500 Lbs.	30" x 32 1/2" x 46"	140 Lbs.

Four 6" Painted Flanged Legs included
For use with **KMD-460M, KMD-530M, KMD-860M**
**BD Bins fit 24" to 24 1/2" deep Ice Machines without Top Kit extension



Scan to view
most recent
Matrix

ICE | STORAGE BINS



B-700SF

Exterior Finish	Application Ice Storage Capacity	Dimensions W x D x H (Height includes 6" legs)	Shipping Weight
Stainless Steel	700 Lbs.	44" x 32 1/3" x 46"	175 Lbs.

Four 6" Painted Legs included
Refer to Top Kit Matrix for necessary configurations



B-800SF

Exterior Finish	Application Ice Storage Capacity	Dimensions W x D x H (Height includes 6" legs)	Shipping Weight
Stainless Steel	800 Lbs.	48" x 32 1/3" x 46"	185 Lbs.

Four 6" Painted Legs included
Refer to Top Kit Matrix for necessary configurations



B-900SF

Exterior Finish	Application Ice Storage Capacity	Dimensions W x D x H (Height includes 6" legs)	Shipping Weight
Stainless Steel	900 Lbs.	52" x 32 1/3" x 46"	195 Lbs.

Four 6" Painted Legs included
Refer to Top Kit Matrix for necessary configurations



B-1150SS / B-1300SS

Model	Exterior Finish	Application Ice Storage Capacity	Dimensions W x D x H (Height includes 6" legs)	Shipping Weight
B-1150SS	Stainless Steel	1148 Lbs.	48" x 41" x 60 3/16"	315 Lbs.
B-1300SS	Stainless Steel	1304 Lbs.	48" x 41" x 66 3/16"	330 Lbs.

Four 6" Stainless Steel Legs included
Baffle design increases ice accessibility by 30%
Universal top included - Check Top Kit Application Guide for detail



B-1500SS / B-1650SS

Model	Exterior Finish	Application Ice Storage Capacity	Dimensions W x D x H (Height includes 6" legs)	Shipping Weight
B-1500SS	Stainless Steel	1500 Lbs.	60" x 41" x 62 3/16"	360 Lbs.
B-1650SS	Stainless Steel	1605 Lbs.	60" x 41" x 66 3/16"	375 Lbs.


Four 6" Stainless Steel Legs included
Baffle design increases ice accessibility by 30%
Universal top included - Check Top Kit Application Guide for detail



REMOTE | CONDENSER

AIR-COOLED REMOTE CONDENSERS - URC / SRC / SRK

An Ice Machine with a **Remote Air Condenser** provides quiet operation at the icemaker location, improves efficiency, and saves energy with cooler operation. Sturdy construction and weather-resistant cabinet finish provides long life operation. Remote condensers may be installed outdoors up to 55 feet from the icemaker. For installations exceeding 55 feet, contact a Factory Technical Service Representative at 800-233-1940.



Model Number	For Use With	Electrical	Dimensions W x D x H (Height includes legs)	Shipping Weight
URC-5FZ	KMI-520MRJZ, KMD-505MRJZ, KMD-530MRJZ, KM-660MRJZ, FD-650MRJZ-C, FD-1002MRJZ-C, F-1002MRJZ-C	115V/60/1	21 ^{13/16} " x 14 ^{1/16} " x 32 ^{13/16} "	90 Lbs.
URC-9FZ	KML-700MRJZ, KMD-705MRJZ, KMD-860MRJZ	115V/60/1	35 ^{11/16} " x 14 ^{1/16} " x 36 ^{1/2} "	90 Lbs.
SRC-10J	FS-1001MLJ-C, FS-1022MLJ-C	230V/60/1	35 ^{3/4} " x 23 ^{1/2} " x 37"	230 Lbs.
SRK-10J	KMS-822MLJ	230V/60/1**	38" x 29" x 37"	230 Lbs.
SRK-12J SRK-12J3	KMS-1122MLJ KMS-1122MLJ	230V/60/1** 230V/60/3	52 ^{3/8} " x 19 ^{1/2} " x 43" 52 ^{3/8} " x 19 ^{1/2} " x 43"	275 Lbs. 275 Lbs.
SRC-14J	FS-1501MLJ-C	230V/60/1**	37 ^{3/4} " x 26 ^{5/8} " x 37"	220 Lbs.
SRK-15J SRK-15J3	KMS-1402MLJ KMS-1402MLJ	230V/60/1 230V/60/3	52 ^{3/8} " x 19 ^{1/2} " x 43" 52 ^{3/8} " x 19 ^{1/2} " x 43"	275 Lbs. 275 Lbs.

**3 wire with neutral for 115V

REMOTE | CONDENSER

For Use With Crescent®, Flaker And Cubelet Ice Makers. See Pages 11, 20, And 29.

Model Number	For Use With	Electrical	Dimensions W x D x H (Height includes legs)	Shipping Weight
URC-14FZ	KM-901MRJZ(3), KM-1100MRJZ, KM-1301SRJZ(3), KM-1340MRJZ(3), F-1501MRJZ(-C)	115V/60/1	35 ^{11/16"} x 14 ^{1/16"} x 36 ^{1/2"}	110 Lbs.

Model Number	For Use With	Electrical	Dimensions W x D x H (Height includes legs)	Shipping Weight
SRK-20J	KMS-2000MLJ	230V/60/1	62" x 21" x 45"	345 Lbs.
SRK-20J3	KMS-2000MLJ	230V/60/3	62" x 21" x 45"	345 Lbs.

Model Number	For Use With	Electrical	Dimensions W x D x H (Height includes legs)	Shipping Weight
URC-22FZ	KM-1601MRJZ(3), KM-1601SRJZ(3), KM-1900SRJZ(3), KM-2200SRJZ(3), KMH-2100SRJZ(3), F-2001MRJZ(3)(-C)	115V/60/1	46 ^{3/8"} x 14 ^{1/16"} x 40 ^{1/2"}	130 Lbs.
URC-26JZ	KM-2600SRJZ3	115V/60/1	46 ^{3/8"} x 14 ^{1/16"} x 40 ^{1/2"}	150 Lbs.

REMOTE CONDENSER MATRIX

Non-Precharged Line Sets - BRAZING REQUIRED

Remote Condenser	Ice Machines	Shipping Weight	25' Length	35' Length	55' Length
URC-5FZ	KM-520MRJZ, KM-660MRJZ, KMD-505MRJZ, FD-650MRJZ-C, F-1002MRJZ(-C), FD-1002MRJZ(-C)	90 Lbs.	HS-5587	HS-5588	N/A
URC-9FZ	KML-700MRJZ, KMD-705MRJZ, KMD-860MRJZ	90 Lbs.	HS-5604	HS-5605	HS-5606
URC-14FZ	KM-901MRJZ(3), KM-1100MRJZ, KM-1301SRJZ(3), KM-1340MRJZ(3) F-1501MRJZ(-C)	100 Lbs.	HS-5604	HS-5605	HS-5606
URC-22FZ	KM-1601MRJZ(3), KM-1601SRJZ(3), KM-1900SRJZ(3) KM-2200SRJZ(3), KMH-2100SRJZ(3), F-2001MRJZ(3)(-C)	130 Lbs.	HS-5323	HS-5324	HS-5325
URC-26JZ	KM-2600SRJZ3	150 Lbs.	HS-5323	HS-5324	HS-5325

Non-Precharged Line Sets - BRAZING REQUIRED

Remote Condenser	Ice Machines	Shipping Weight	25' Length	35' Length	55' Length
SRC-10J	FS-1001MLJ-C, FS-1022MLJ-C	230 Lbs.	HS-5299*	HS-5300*	HS-5301*
SRK-10J	KMS-822MLJ	230 Lbs.	HS-0250*	HS-0251*	HS-0252*
SRK-12J SRK-12J3	KMS-1122MLJ	275 Lbs.	HS-0250*	HS-0251*	HS-0252*
SRC-14J	FS-1501MLJ-C	220 Lbs.	HS-5323*	HS-5324*	HS-5325*
SRK-15J SRK-15J3	KMS-1402MLJ	275 Lbs.	HS-0250*	HS-0251*	HS-0252*
SRK-20J SRK-20J3	KMS-2000MLJ	345 Lbs.	HS-0243*	HS-0244*	HS-0245*

*Line sets require refrigerant

WATER | FILTRATION

HOSHIZAKI Water Filters are designed to eliminate particles as small as 1 micron, ensuring the highest quality ice and water available. Providing clean and healthy water is crucial, particularly in healthcare and educational environments.

Model Number	Description	Aprox. Ice Production	Undercounter KMs	KM Cubers	IM Cubers	Flakers / Cubelet	DCMs
H9320-51 Use E-10 10" Prefilter	Single	< 700 lbs / 24 hours	AM-50, KM-81, 116, 161 KM-231, 301	KM-350, 520, 660 , 500, 700 KMD-410, 460, 530	IM-200,500 IM-50BAA-LM	All Models	All Models
H9320-52 Use E-20 20" Prefilter	Twin	800 - 1100 lbs / 24 hours	N/A	KM-901, 1100, KMD-860 KMS-822, 1122, 1402	IM-50BAA-Q	N/A	N/A
H9320-53 Use E-20 20" Prefilter	Triple	1200 - 2600* lbs / 24 hours	N/A	KM-1301, 1340, 1601, 1900, 2200, 2600 KMH-2100 KMS-2000	N/A	N/A	N/A
H9655-11	Replacement Cartridge (1) One each	*For installations producing more than 2.6K lbs, water filters are required on each water line; water line split must occur from the water source; not as a T- or Y-connection from supply. For more information on proper installation for systems exceeding 2.6L lbs, please contact Hoshizaki Tech Services at 800-233-1940.					

Recommended water filter configurations based on average ice machine usage and regular filter replacement. If your operation has challenging water conditions or higher usage, then it may be necessary to use an additional filter or prefilter.

Water Filters	Description	Height of System (Manifold + Cartridge)
H9320-51	Single	18.4" H
H9320-52	Twin	19.11" H
H9320-53	Triple	19.15" H
H9320-54	4H-SI (medical) Single	18.1" H
H9655-11	Replacement Cartridge each	N/A
H9655-06	Replacement Cartridge (6 pk)	N/A
H9655-08	4H-SI (medical) Cartridge (1 pk)	18.1" H

Prefilters	Description	Height of System (Manifold + Cartridge)
9534-26	E-20 Replacement Cartridges (6 pk)	20"
9534-12	E-10 Replacement Cartridges (12 pk)	10"
9534-20	E-20 Replacement Cartridges (20 pk)	20"
9534-40	E-10 Replacement Cartridges (40 pk)	10"
9795-80	E-10 Prefilter	10"
9795-90	E-20 Prefilter	20"



SANITIZING AND MONITORING

Advanced ozone-treated water sanitizes the ice machine, bin, and related parts. Can be used on all Hoshizaki ice machines except ice and water dispensers.

BioSure
PROFESSIONAL

Model	Description	Overall Dimensions W x D x H
HS-5767	Bio ₃ Sure Clean Ice Ozone System. Includes Head and Standard Cartridge Assembly	4.6" x 2.9" x 5.8"
HS-5768	Bio ₃ Sure Clean Ice Ozone Standard Cartridge	6-12 months Lifetime
HS-5769	Bio ₃ Sure Clean Ice Ozone Large Cartridge	18-36 months Lifetime



Bio₃Sure Clean Ice Ozone System
HS-5767


Remote Monitoring System

For use on Hoshizaki KM Cuber ice machines

Model Number	For use with	Shipping Length	Shipping Width	Shipping Height	Shipping Weight
HS-5562	KM Cuber ice machines Not for use with KMD-410	8"	8"	3"	1 lb.
HS-5602	Flaker, Cubelet and DCM Series ice machines**	12"	12"	4"	2 lb.



- Performance dashboard for status, historical data
- Alert notification by email or text
- Remotely diagnose machines
- Control functions: ON/OFF, Reset, Lock-down



REACH-INS

REFRIGERATORS / FREEZERS / PREP TABLES
HOT HOLDING / BACK BAR



Hoshizaki Steelheart® Reach-Ins are engineered to meet the tough demands of commercial kitchens. Steelheart® reach-ins offer rugged, stainless steel construction inside and out for the highest quality, durability, performance and sanitation.



See all
Reach-In
models



BEYOND STRONG.

It's the promise of reliability... and the peace of mind that comes with it.

It's performing beyond expectations... with relentless durability and sustainability.

It's knowing that we've already thought about your future and can perform at the next level.

UPRIGHT | REFRIGERATORS

Solid Doors

Unique ducted air distribution system, maintains uniform cabinet temperatures even when full



R1A-FS(L) ★ R1A-HS(L) ★

R2A-FS

R2A-HS

R3A-FS

- Energy efficient thermostatic expansion valve for faster temperature recovery
- Self-closing stainless steel doors with spring assist hinges, stay open feature and locks.

- Stainless steel interior and exterior front, sides and top
- 4" Heavy duty stem casters standard, 2 with brakes.



Model Number	R1A-FS ★ (L) - Left hinge	R1A-HS ★ (L) - Left hinge	R2A-FS	R2A-FSN	R2A-HS	R3A-FS	R3A-HS
Interior Storage Capacity (AHAM)	23.10 ft³	23.10 ft³	50.37 ft³	47.11 ft³	50.37 ft³	79.03 ft³	79.03 ft³
Overall Dimensions (W x D x H including 4" casters)	27.5" x 33.5" x 79.5"	27.5" x 33.5" x 79.5"	55" x 33.5" x 79.5"	52" x 33.5" x 79.5"	55" x 33.5" x 79.5"	82.5" x 33.5" x 79.5"	82.5" x 33.5" x 79.5"
Depth with Doors Open at 90°	59.25"	59.25"	59.25"	57.75"	59.25"	59.25"	59.25"
Interior Door Opening Width	21.75"	21.75"	21.75"	20.25"	21.75"	21.75"	21.75"
Interior Door Opening Height	59.25"	27.75" each	59.25"	59.25"	27.75" each	59.25"	27.75" each
Adjustable Shelves	3	3	6	6	6	9	9
Center Shelves (C)	N/A	N/A	3	3	3	6	6
Shelf Dimensions (W x D)	21.25" x 26"	21.25" x 26"	21.25" x 26" (C) 6" x 17.8"	19.75" x 26"	21.25" x 26" (C) 6" x 17.8"	21.25" x 26" (C) 6" x 22.9"	21.25" x 26" (C) 6" x 22.9"
Crated Shipping Weight	345 lbs.	345 lbs.	562 lbs.	562	562 lbs.	811 lbs.	811 lbs.
Crated Shipping Dimensions (L x W x H)	37.5" x 31.5" x 81"	37.5" x 31.5" x 81"	58" x 37.5" x 81"	58" x 37.5" x 81"	58" x 37.5" x 81"	86" x 37.5" x 81"	86" x 37.5" x 81"
Voltage	115V/60/1	115V/60/1	115V/60/1	115/60/1	115V/60/1	115V/60/1	115V/60/1
Amperage (AMP)	5	5	8	8	8	9.5	9.5
HACR Breaker (AMP)	15	15	15	15	15	15	15
Energy Consumption (kWh / day) ASHRAE	1.25	1.25	3.47	2.85	3.47	4.39	4.39
Heat Rejection (BTU / hr)*	317	317	513	621	513	703	703
Voltage Range	104 - 126	104 - 126	104 - 126	104 - 126	104 - 126	104 - 126	104 - 126
Ambient Temp. Range	45° - 100°F	45° - 100°F	45° - 100°F	45° - 100°F	45° - 100°F	45° - 100°F	45° - 100°F
Control Set Point Range	31° - 52°F	31° - 52°F	31° - 52°F	31° - 52°F	31° - 52°F	31° - 52°F	31° - 52°F
Refrigerant	R290	R290	R290	R290	R290	R290	R290

*Based on 100°F ambient cycling at set point



UPRIGHT | REFRIGERATORS

Glass Doors



- Stainless steel interior and exterior front, sides and top
- Lockable doors are energy efficient multi-pane, argon filled
- Energy efficient thermostatic expansion valve/self contained refrigeration system
- All models come with energy efficient vertical LED lights
- Unique ducted air distribution system, maintains a uniform cabinet temperatures even when full
- 4" Heavy duty stem casters standard
- Center shelves for added storage capacity

Model Number	R1A-FG	R1A-HG	R2A-FG	R2A-HG	R3A-FG ★	R3A-HG ★
Interior Storage Capacity (AHAM)	23.10 ft ³	23.10 ft ³	50.37 ft ³	50.37 ft ³	79.03 ft ³	79.03 ft ³
Overall Dimensions (W x D x H including 4" casters)	27.5" x 34.5" x 79.5"	27.5" x 34.5" x 79.5"	55" x 34.5" x 79.5"	55" x 34.5" x 79.5"	82.5" x 34.5" x 79.5"	82.5" x 34.5" x 79.5"
Depth with Doors Open at 90°	57"	57"	57"	57"	57"	57"
Interior Door Opening Width	21.75"	21.75"	21.75"	21.75"	21.75"	21.75"
Interior Door Opening Height	59.25"	27.75" each	59.25"	27.75" each	59.25"	27.75" each
Adjustable Shelves	3	3	6	6	9	9
Center Shelves (C)	N/A	N/A	3	3	6	6
Shelf Dimensions (W x D)	21.25" x 26"	21.25" x 26"	21.25" x 26" (C) 6" x 17.8"	21.25" x 26" (C) 6" x 17.8"	21.25" x 26" (C) 6" x 22.9"	21.25" x 26" (C) 6" x 22.9"
Crated Shipping Weight	350 lbs.	350 lbs.	570 lbs.	570 lbs.	826 lbs.	826 lbs.
Crated Shipping Dimensions (L x W x H)	37.5" x 31.5" x 81"	37.5" x 31.5" x 81"	58" x 37.5" x 81"	58" x 37.5" x 81"	86" x 37.5" x 81"	86" x 37.5" x 81"
Voltage	115V/60/1	115V/60/1	115V/60/1	115V/60/1	115V/60/1	115V/60/1
Amperage (AMP)	5	5	8	8	9.5	9.5
HACR Breaker (AMP)	15	15	15	15	15	15
Energy Consumption (kWh / day) ASHRAE	2.47	2.47	5.05	5.05	6.5	6.5
Heat Rejection (BTU / hr)*	639	639	978	978	1255	1255
Voltage Range	104 - 126	104 - 126	104 - 126	104 - 126	104 - 126	104 - 126
Ambient Temp. Range	45° - 100°F	45° - 100°F	45° - 100°F	45° - 100°F	45° - 100°F	45° - 100°F
Control Set Point Range	31° - 52°F	31° - 52°F	31° - 52°F	31° - 52°F	31° - 52°F	31° - 52°F
Refrigerant	R290	R290	R290	R290	R290	R290

*Based on 100°F ambient cycling at set point



UPRIGHT | FREEZERS

Solid Doors



F1A-FS(L)

F1A-HS(L)

F2A-FS

F2A-FSN

F2A-HS

F3A-FS

F3A-HS

- Stainless steel interior and exterior front, sides and top
- Energy efficient thermostatic expansion valve
- 4" Heavy duty stem casters standard
- Self-closing stainless steel doors with spring assist hinges, stay open feature and locks
- Unique ducted air distribution system, maintains uniform cabinet temperatures even when full

Model Number	F1A-FS (L) - Left hinge	F1A-HS (L) - Left hinge	F2A-FS	F2A-FSN	F2A-HS	F3A-FS	F3A-HS
Interior Storage Capacity (AHAM)	23.10 ft ³	23.10 ft ³	50.37 ft ³	47.11 ft ³	50.37 ft ³	79.03 ft ³	79.03 ft ³
Overall Dimensions (W x D x H including 4" casters)	27.5" x 33.5" x 79.5"	27.5" x 33.5" x 79.5"	55" x 33.5" x 79.5"	52" x 33.5" x 79.5"	55" x 33.5" x 79.5"	82.5" x 33.5" x 79.5"	82.5" x 33.5" x 79.5"
Depth with Doors Open at 90°	59.25"	59.25"	59.25"	57.75"	59.25"	59.25"	59.25"
Interior Door Opening Width	21.75"	21.75"	21.75"	20.25"	21.75"	21.75"	21.75"
Interior Door Opening Height	59.25"	27.75" each	59.25"	59.25"	27.75" each	59.25"	27.75" each
Adjustable Shelves	3	3	6	6	6	9	9
Shelf Dimensions (W x D)	21.25" x 26"	21.25" x 26"	21.25" x 26" (C) 6" x 17.8"	19.75" x 26"	21.25" x 26" (C) 6" x 17.8"	21.25" x 26" (C) 6" x 22.9"	21.25" x 26" (C) 6" x 22.9"
Crated Shipping Weight	345 lbs.	345 lbs.	562 lbs.	562 lbs.	562 lbs.	830 lbs.	830 lbs.
Crated Shipping Dimensions (L x W x H)	37.5" x 31.5" x 81"	37.5" x 31.5" x 81"	58" x 37.5" x 81"	58" x 37.5" x 81"	58" x 37.5" x 81"	86" x 37.5" x 81"	86" x 37.5" x 81"
Voltage	115V/60/1	115V/60/1	115V/60/1	115V/60/1	115V/60/1	230V/60/1	230V/60/1
Amperage (AMP)	8.46	8.46	8.7	9.5	8.7	11	11
HACR Breaker (AMP)	15	15	15	15	15	20	20
Energy Consumption (kWh / day) ASHRAE	6.25	6.25	12.16	11.61	12.16	17.02	17.02
Heat Rejection (BTU / hr)*	1178	1178	1820	2184	1820	1643	1643
Voltage Range	104 - 126	104 - 126	104 - 126	104 - 126	104 - 126	208 - 254	208 - 254
Ambient Temp. Range	45° - 100°F	45° - 100°F	45° - 100°F	45° - 100°F	45° - 100°F	45° - 100°F	45° - 100°F
Control Set Point Range	-10° - +12°F	-10° - +12°F	-10° - +12°F	-10° - +12°F	-10° - +12°F	-10° - +12°F	-10° - +12°F
Refrigerant	R290	R290	R290	R290	R290	R290	R290

*Based on 100°F ambient cycling at set point

UPRIGHT | FREEZERS & DUAL-TEMPS

Glass Doors



- Stainless steel interior and exterior front, sides and top
- Lockable doors are energy efficient multi pane, argon filled
- Energy efficient vertical LED lights
- Unique ducted air distribution system, maintains uniform cabinet temperatures
- Dual temperature cabinets for space efficiency
- 4" Heavy duty stem casters standard

Model Number	F1A-FG	F1A-HG	F2A-FG	F2A-HG	DT1A-HS	DT2A-FS
Interior Storage Capacity (AHAM) Refrigerator Freezer	23.10 ft ³	23.10 ft ³	50.37 ft ³	50.37 ft ³	10.19 ft ³ 10.19 ft ³	23.10 ft ³ 23.10 ft ³
Overall Dimensions (W x D x H including 4" casters)	27.5" x 34.5" x 79.5"	27.5" x 34.5" x 79.5"	55" x 34.5" x 79.5"	55" x 34.5" x 79.5"	27.5" x 35" x 79.5"	55" x 33.5" x 79.5"
Depth with Doors Open at 90°	57"	57"	57"	57"	61.75"	59.25"
Interior Door Opening Width	21.75"	21.75"	21.75"	21.75"	21.75"	21.75"
Interior Door Opening Height	59.25"	27.75" each	59.25"	27.75" each	27.75" each	59.25"
Adjustable Shelves	3	3	6	6	3	3
Center Shelves (C)	N/A	N/A	3	3	N/A	N/A
Shelf Dimensions (W x D)	21.25" x 26"	21.25" x 26"	(L/R) 21.25" x 26" (C) 6" x 17.8"	(L/R) 21.25" x 26" (C) 6" x 17.8"	21.25" x 26"	21.25" x 26"
Crated Shipping Weight	365 lbs.	365 lbs.	602 lbs.	602 lbs.	415 lbs.	634 lbs.
Crated Shipping Dimensions (L x W x H)	37.5" x 31.5" x 81"	37.5" x 31.5" x 81"	58" x 37.5" x 81"	58" x 37.5" x 81"	37.5" x 31.5" x 81"	58" x 37.5" x 81"
Voltage	115V/60/1	115V/60/1	115V/60/1	115V/60/1	115V/60/1	115V/60/1
Amperage (AMP)	8.5	8.5	9.1	9.1	5.5	14
HACR Breaker (AMP)	15	15	15	15	15	20
Energy Consumption (kWh / day) ASHRAE	7.73	7.73	16.3	16.3	4.49	8.59
Heat Rejection (BTU / hr)*	806	806	1694	1694	168 439	376 1401
Voltage Range	104 - 126	104 - 126	104 - 126	104 - 126	104 - 126	104-126
Ambient Temp. Range	45° - 80°F	45° - 100°F	45° - 80°F	45° - 100°F	45° - 100°F	45° to 100°F
Control Set Point Range Refrigerator Freezer	-10° - +12°F	-10° - +12°F	-10° - +12°F	-10° - +12°F	33° to 52°F - 10° to 10°F	33° to 52°F - 10° to 10°F
Refrigerant	R290	R290	R290	R290	R290	R290

*Based on 100°F ambient cycling at set point



UPRIGHT | PASS-THRU REFRIGERATORS

Stainless and Glass Doors



PT1A-FS-FS ★
(Shown with door open)



PT1A-HS-HS ★



PT1A-FG-FG



PT2A-HS-HS



PT2A-FG-FG

- Stainless steel interior and exterior front, sides and top
- Lockable doors are energy efficient multi pane, argon filled
- Energy efficient LED lights

- Unique ducted air distribution system, maintains uniform cabinet temperatures
- 4" Heavy duty stem casters standard, two with brakes
- Glass and solid door configurations can be customized

Model Number	PT1A-FS-FS ★	PT1A-HS-HS ★	PT1A-FG-FG	PT2A-FS-FS	PT2A-HS-HS	PT2A-FG-FG
Interior Storage Capacity (AHAM)	24.20 ft³	24.20 ft³	24.20 ft³	52.50 ft³	52.50 ft³	52.50 ft³
Overall Dimensions (W x D x H including 4" casters)	27.5" x 35.75" x 79.5"	27.5" x 35.75" x 79.5"	27.5" x 37.75" x 79.5"	55" x 35.75" x 79.5"	55" x 35.75" x 79.5"	55" x 37.75" x 79.5"
Depth with Doors Open at 90°	87.25"	87.25"	82.5"	87.25"	87.25"	82.5"
Interior Door Opening Width	21.75"	21.75"	21.75"	21.75"	21.75"	21.75"
Interior Door Opening Height	59.25"	27.75" each	59.25"	59.25"	27.75" each	59.25"
Adjustable Shelves	3	3	3	6	6	6
Center Shelves (C)	N/A	N/A	N/A	3	3	3
Shelf Dimensions (W x D)	21.25" x 30.75"	21.25" x 30.75"	21.75" x 30.75"	21.25" x 26" (C) 6" x 17.8"	21.25" x 26" (C) 6" x 17.8"	21.25" x 26" (C) 6" x 17.8"
Crated Shipping Weight	357 lbs	357 lbs	367 lbs.	592 lbs	592 lbs	681 lbs.
Crated Shipping Dimensions (L x W x H)	38.5" x 31.5" x 81"	38.5" x 31.5" x 81"	41.25" x 31.5" x 81"	58" x 38.5" x 81"	58" x 38.5" x 81"	58" x 41.25" x 81"
Voltage	115/60/1	115/60/1	115V/60/1	115/60/1	115/60/1	115V/60/1
Amperage (AMP)	5	5	5	8	8	8
HACR Breaker (AMP)	15	15	15	15	15	15
Energy Consumption (kWh / day) ASHRAE	1.31	1.31	2.68	3.24	3.24	6
Heat Rejection (BTU / hr)*	348	348	653	581	581	1429
Voltage Range	104-126	104-126	104 - 126	104-126	104-126	104 - 126
Ambient Temp. Range	45° to 100°F	45° to 100°F	45° - 100°F	45° to 100°F	45° to 100°F	45° - 100°F
Control Set Point Range	31° to 52°F	31° to 52°F	31° to 52°F	31° to 52°F	31° to 52°F	31° to 52°F
Refrigerant	R290	R290	R290	R290	R290	R290

*Based on 100°F ambient cycling at set point



UPRIGHT | ROLL-THRU / ROLL-IN

Solid Doors

Hoshizaki's roll-in and roll-thru refrigerators are built for demanding commercial kitchens that rely on speed and organization. Roll-in models allow full racks to be quickly loaded from one side, while roll-thru designs provide front and back access, streamlining movement between prep and service areas.



RN1A-FS / RT1A-FS-FS



RT1A-FS-FS



RN2A-FS / RT2A-FS-FS

- Stainless steel interior and exterior front, sides and top
- Environmentally friendly R290 hydrocarbon refrigerant
- All models come with energy efficient vertical LED lights

- Unique ducted air distribution system, maintains uniform cabinet temperatures
- Reinforced stainless steel ramp and floor accommodate Roll-In racks up to 72" tall (supplied by others)
- Made to order

Model Number	RN1A-FS	RT1A-FS-FS	RN2A-FS	RT2A-FS-FS
Interior Storage Capacity (AHAM)	38.13 ft ³	38.13 ft ³	78.35 ft ³	78.35 ft ³
Overall Dimensions (W x D x H including 4" casters)	35" x 38.9" x 87.5"	35" x 45.5" x 87.5"	68" x 38.9" x 87.5"	68" x 45.5" x 87.5"
Depth with Doors Open at 90°	65.25"	98.5"	65.25"	98.5"
Interior Door Opening Width	29.25"	29.25"	29.25"	29.25"
Interior Door Opening Height	72.75"	72.75"	72.75"	72.75"
Crated Shipping Weight	429 lbs	459 lbs	676 lbs	737 lbs
Crated Shipping Dimensions (L x W x H)	40.5" x 39" x 93.5"	40.5 x 39" x 93.5"	72" x 40.5" x 93.75"	72" x 40.5" x 93.75"
Voltage	115V/60/1	115V/60/1	115V/60/1	115V/60/1
Amperage (AMP)	6.4	6.4	8.2	8.2
HACR Breaker (AMP)	15	15	15	15
Energy Consumption (kWh / day) ASHRAE	3.186	3.186	5.06	5.06
Heat Rejection (BTU / hr)*	774	774	1376	1376
Voltage Range	104-126	104-126	104-126	104-126
Ambient Temp. Range	45° to 100°	45° to 100°	45° to 100°	45° to 100°
Control Set Point Range	31° - 52°F	31° - 52°F	31° - 52°F	31° - 52°F
Refrigerant	R290	R290	R290	R290

*Based on 100°F ambient cycling at set point



UPRIGHT | HEATED CABINETS

Solid Doors



HC1A-FS ★

(Shown with top and door open)



HC1A-HS ★



HC2A-FS ★



HC2A-HS ★

- Stainless steel interior with stainless exterior front, sides, and top
- Interior top-mounted heating element with fan to circulate heat through cabinet; heat shield foamed in next to heating element
- Additional storage fits 12 (36 for 2-section) sheet pans
- Maximum interior storage capacity with smallest external footprint
- Solid state digital controller with temperature alarms and LED display (Fahrenheit or Celsius)
- 4" Heavy duty stem casters standard, two with brakes

Model Number	HC1A-FS ★	HC1A-HS ★	HC2A-FS ★	HC2A-HS ★
Interior Storage Capacity (AHAM)	22.70 ft ³	22.62 ft ³	49.70 ft ³	49.50 ft ³
"Overall Dimensions (W x D x H including 4" casters)"	27.5" x 33.5" x 79.5"	27.5" x 33.5" x 79.5"	55" x 33.5" x 79.5"	55" x 33.5" x 79.5"
Depth with Doors Open at 90°	59.25"	27.75"	59.25"	59.25"
Interior Door Opening Width	21.75"	21.75"	21.75"	21.75"
Interior Door Opening Height	59.25"	27.75" each	59.25"	27.75" each
Adjustable Shelves	3	3	6	6
Center Shelves (C)	N/A	N/A	3	3
Shelf Dimensions (W x D)	21.25" x 26"	21.25" x 26"	21.25" x 26"	21.25" x 26"
Crated Shipping Weight	340 lbs	340 lbs	578 lbs	578 lbs
Crated Shipping Dimensions (L x W x H)	37.5" x 31.5" x 81"	37.5" x 31.5" x 81"	58" x 37.5" x 81"	58" x 37.5" x 81"
Voltage	115/60/1	115/60/1	208-230/60/1	208-230/60/1
Amperage (AMP)	10	10	9 (208v) /10 (230v)	9 (208v) /10 (230v)
HACR Breaker (AMP) (W) ASTM 2140-11	15	15	20	20
Energy Consumption (w) ASTM 2140-11	N/A	N/A	N/A	N/A
Voltage Range	104-126	104-126	208-254	208-254
Ambient Temp. Range	45° to 100°F	45° to 100°F	45° to 100°F	45° to 100°F
Control Set Point Range	140° to 180°F	140° to 180°F	140° to 180°F	140° to 180°F



UPRIGHT | HEATED CABINETS & PASS-THRUS

Solid Doors



HC1A-FS-FS ★
(Shown with top and doors open)



HC1A-HS-HS ★



HC2A-FS-FS ★



HC2A-HS-HS ★

- Stainless steel interior with stainless exterior front, sides, and top
- Interior top-mounted heating element with fan to circulate heat through cabinet; heat shield foamed in next to heating element
- Additional storage fits 12 (36 for 2 section) sheet pans

- Maximum interior storage capacity with smallest external footprint
- Solid state digital controller with temperature alarms and LED display (Fahrenheit or Celsius)
- 4" Heavy duty stem casters standard, two with brakes

Model Number	HC1A-FS-FS ★	HC1A-HS-HS ★	HC2A-FS-FS ★	HC2A-HS-HS ★
Interior Storage Capacity (AHAM)	23.82 ft³	23.68 ft³	52.40 ft³	52.10 ft³
"Overall Dimensions (W x D x H including 4" casters)"	27.5" x 35.75" x 79.5"	27.5" x 35.75" x 79.5"	55" x 35.75" x 79.5"	55" x 35.75" x 79.5"
Depth with Doors Open at 90°	87.25"	87.25"	87.25"	87.25"
Interior Door Opening Width	21.75"	21.75"	21.75"	21.75"
Interior Door Opening Height	59.25"	27.75" each	59.25"	27.75" each
Adjustable Shelves	3	3	6	6
Center Shelves (C)	N/A	N/A	3	3
Shelf Dimensions (W x D)	21.25" x 30.75"	21.25" x 30.75"	21.25" x 30.75"	21.25" x 30.75"
Crated Shipping Weight	367 lbs	367 lbs	625 lbs	625 lbs
Crated Shipping Dimensions (L x W x H)	38.5" x 31.5" x 81"	38.5" x 31.5" x 81"	58" x 38.5" x 81"	58" x 38.5" x 81"
Voltage	115/60/1	115/60/1	208-230/60/1	208-230/60/1
Amperage (AMP)	10	10	9 (208v) /10 (230v)	9 (208v) /10 (230v)
HACR Breaker (AMP)	15	15	20	20
Energy Consumption (w) ASTM 2140-11	N/A	N/A	N/A	N/A
Voltage Range	104-126	104-126	208-254	208-254
Ambient Temp. Range	45° to 100°F	45° to 100°F	45° to 100°F	45° to 100°F
Control Set Point Range	140° to 180°F	140° to 180°F	140° to 180°F	140° to 180°F





STEELHEART® UNDERCOUNTER & WORKTOP REFRIGERATION

YOUR HEIGHT, YOUR CHOICE

Hoshizaki Undercounters come in three worksurface heights to meet the needs of your busy operation.



- Standard Height 36" work surfaces with 6" casters are the most commonly found units in operations, allowing the user to work on the top of the cabinet when needed.
- ADA-Complaint 34" work surfaces with 4" casters meet ADA-Compliance for work surfaces and cabinet access.
- Low Profile 32" work surfaces with 2.25" casters are made to slide right under existing ADA-compliant counters with plenty of room for air circulation to ensure optimal performance.



Scan to
View
Undercounter
Models



UNDERCOUNTER | REFRIGERATORS

Solid Doors

34" WORK HEIGHT W/ 4" CASTERS



UR27B(-01) ★

UR36B(-01) ★

UR48B(-01) ★

UR60B(-01) ★

UR72B(-01) ★

- Stainless steel interior and exterior front, sides and top
- Cabinet and doors are insulated with 2" foamed-in-place polyurethane
- Engineered to maintain NSF-7 temperatures in 100°F ambient

- Optional 2.25" casters for ADA Compliance 

- Field reversible doors
- Electronic controls

Model Number	UR27B ★ UR27B-01 ** (01 Cylinder Door Lock)	UR36B ★ UR36B-01 ** (01 Cylinder Door Lock)	UR48B ★ UR48B-01 ** (01 Cylinder Door Lock)	UR60B ★ UR60B-01 ** (01 Cylinder Door Lock)	UR72B ★ UR72B-01 ** (01 Cylinder Door Lock)
Interior Storage Capacity (AHAM)	6.21 ft³	8.64 ft³	12 ft³	15.1 ft³	18.27 ft³
Overall Dimensions (W x D x H including 4" casters)	27" x 30" x 33.75"	36" x 30" x 33.75"	48" x 30" x 33.75"	60" x 30" x 33.75"	72" x 30" x 33.75"
Depth with Doors Open at 90°	55.5"	58.5"	52.5"	58.5"	52.5"
Interior Door Opening Width	22.75"	25.5"	19.5"	25.5"	19.5"
Interior Door Opening Height	23"	23"	23"	23"	23"
Adjustable Shelves	1	1	2	2	3
Shelf Dimensions (W x D)	22" x 16"	31" x 16"	21.5" x 16"	27.25" x 16"	22" x 16"
Crated Shipping Weight	173 lbs.	204 lbs.	249 lbs.	290 lbs.	339 lbs.
Crated Shipping Dimensions (L x W x H)	34" x 31.5" x 36.5"	40.5" x 34" x 36.5"	52.5" x 34" x 36.5"	62.5" x 34" x 36.5"	73.75" x 32" x 36.5"
Voltage	115V/60/1	115V/60/1	115V/60/1	115V/60/1	115V/60/1
Amperage (AMP)	2.7	2.5	3	3	3
HACR Breaker (AMP)	15	15	15	15	15
Energy Consumption (kWh / day) ASHRAE	0.65	0.69	1.05	0.927	1.12
Heat Rejection (BTU / hr) *	193	184	278	249	360
Voltage Range	104 - 126	104 - 126	104 - 126	104 - 126	104 - 126
Ambient Temp. Range	45° - 100°F	45° - 100°F	45° - 100°F	45° - 100°F	45° - 100°F
Temperature Range	32° - 52°F	32° - 52°F	32° - 52°F	32° - 52°F	32° - 52°F
Refrigerant	R290	R290	R290	R290	R290

*Based on 100°F ambient cycling at set point

**MADE TO ORDER - Please contact your local HOSHIZAKI Sales Representative for availability.



UNDERCOUNTER | REFRIGERATORS

Drawer/Door Combination

34" WORK HEIGHT W/ 4" CASTERS



UR48B-D2



UR60B-D2

- Stainless steel interior and exterior front sides and top
- Cabinet and drawers are insulated with 2" foamed-in-place polyurethane
- Door/Drawer configuration can be located in any cabinet section
- Enamel coated evaporator coil
- Engineered to maintain NSF-7 temperatures in 100°F ambient.
- Field reversible doors

Model Number	UR48B-D2**	UR60B-D2**
Interior Storage Capacity (AHAM)	12 ft ³	15.1 ft ³
Overall Dimensions (L x W x H)	48" x 30" x 33.75" (including 4" casters)	60" x 30" x 33.75" (including 4" casters)
Depth With Door Open At 90°	52.5"	58.5"
Depth With Drawer Fully Open	52"	52"
Door Opening Width x Height	19.5" x 23"	25.5" x 23"
Shelves (#) / Dimensions(W x D)	(1) / 21.5" x 16"	(1) / 27.25" x 16"
Drawer Pan Capacity (pans by others)	(1) 1/2 and (1) 1/3 size pans, 6" deep	12" x 20" x 6" deep (1) full size pan, 6" deep
Crated Shipping Weight	282 lbs.	292 lbs.
Crated Shipping Dimensions (L x W x H)	52.5" x 34" x 36.5"	62.5" x 34" x 36.5"
Voltage	115V/60/1	115V/60/1
Amperage (AMP)	3	3
HACR Breaker (AMP)	15	15
Energy Consumption (kWh / day) NSF	1.05	1.75
Heat Rejection (BTU / hr)	278	249
Voltage Range	104 - 126	104 - 126
Ambient Temp. Range	45° - 100°F	45° - 100°F
Temperature Range	32° - 52°F	32° - 52°F
Refrigerant	R290	R290

**MADE TO ORDER - Please contact your local HOSHIZAKI Sales Representative for availability.

UNDERCOUNTER | REFRIGERATORS

Drawers

34" WORK HEIGHT W/ 4" CASTERS



UR27B-D2



UR48B-D4



UR60B-D4



UR72B-D6

- Stainless steel interior and exterior front, sides and top
- Heavy duty drawers with removeable gaskets
- Cabinet and drawers are insulated with 2" foamed in place polyurethane
- 4" Stem casters standard

- Optional 2.25" casters for ADA Compliance 
- Engineered to maintain NSF-7 temperatures in 100°F ambient
- Enamel coated evaporator coil

Model Number	UR27B-D2	UR48B-D4	UR60B-D4	UR72B-D6
Interior Storage Capacity (AHAM)	6.21 ft ³	12 ft ³	15.27 ft ³	18 ft ³
Overall Dimensions (W x D x H including 4" casters)	27" x 30" x 33.75"	48" x 30" x 33.75"	60" x 30" x 33.75"	72" x 30" x 33.75"
Depth with Drawer Fully Open	52"	52"	52"	52"
Drawer Pan Capacity (pans by others)	(1) 12" x 20" x 6" deep pan per drawer	(1) 1/2 and (1) 1/3 size pan per drawer, 6" deep	(1) 12" x 20" x 6" deep pan per drawer	(1) 1/2 and (1) 1/3 size pan per drawer, 6" deep
Crated Shipping Weight	203 lbs.	314 lbs.	346 lbs.	443 lbs.
Crated Shipping Dimensions (L x W x H)	34" x 31.5" x 36.5"	52.5" x 34" x 36.5"	62.5" x 34" x 36.5"	73.75" x 32" x 36.5"
Voltage	115V/60/1	115V/60/1	115V/60/1	115V/60/1
Amperage (AMP)	2.5	3	3	3
HACR Breaker (AMP)	15	15	15	15
Energy Consumption (kWh / day) ASHRAE	0.65	1.05	1.75	1.12
Heat Rejection (BTU / hr)	152	278	249	360
Voltage Range	104 - 126	104 - 126	104 - 126	104 - 126
Ambient Temp. Range	45° - 100°F	45° - 100°F	45° - 100°F	45° - 100°F
Temperature Range	32° - 52°F	32° - 52°F	32° - 52°F	32° - 52°F
Refrigerant	R290	R290	R290	R290



UNDERCOUNTER | FREEZERS

Solid Doors

34" WORK HEIGHT W/ 4" CASTERS



UF27B(-01)



UF48B(-01)



UF60B(-01)★

- Stainless steel interior and exterior front, sides and top
- Cabinet and doors are insulated with 2" foamed-in-place polyurethane
- Engineered to maintain NSF-7 temperatures in 100°F ambient

- Optional 2.25" casters for ADA Compliance



- Field reversible doors
- Enamel coated evaporator coil

Model Number	UF27B UF27B-01** (01 Cylinder Door Lock)	UF48B UF48B-01** (01 Cylinder Door Lock)	UF60B ★ UF60B-01** (01 Cylinder Door Lock)
Interior Storage Capacity (AHAM)	6.21 ft³	12 ft³	15.1 ft³
Overall Dimensions (W x D x H including 4" casters)	27" x 30" x 33.75"	48" x 30" x 33.75"	60" x 30" x 33.75"
Depth with Doors Open at 90°	55.5"	52.5"	58.5"
Interior Door Opening Width	22.75"	19.5"	25.5"
Interior Door Opening Height	23"	23"	23"
Adjustable Shelves	1	2	2
Shelf Dimensions (W x D)	22" x 16"	21.5" x 16"	27.25" x 16"
Crated Shipping Weight	175 lbs.	258 lbs.	310 lbs.
Crated Shipping Dimensions (L x W x H)	34" x 31.5" x 36.5"	52.5" x 34" x 36.5"	62.5" x 34" x 36.5"
Voltage	115V/60/1	115V/60/1	115V/60/1
Amperage (AMP)	2.4	3.6	4
HACR Breaker (AMP)	15	15	15
Energy Consumption (kWh / day) ASHRAE	2.4	3.6	3.95
Heat Rejection (BTU / hr)	489	756	727
Voltage Range	104 - 126	104 - 126	104 - 126
Ambient Temp. Range	45° - 100°F	45° - 100°F	45° - 100°F
Temperature Range	-10° - +10°F	-10° - +10°F	-10° - +10°F
Refrigerant	R290	R290	R290

**MADE TO ORDER - Please contact your local HOSHIZAKI Sales Representative for availability.



UNDERCOUNTER | FREEZERS

Drawers

34" WORK HEIGHT W/ 4" CASTERS



UF27B-D2



UF48B-D4

- Stainless steel interior and exterior front, sides and top
- Cabinet and doors are insulated with 2" foamed-in-place polyurethane
- Engineered to maintain NSF-7 temperatures in 100°F ambient

- Optional 2.25" casters for ADA Compliance 
- Field reversible doors
- Enamel coated evaporator coil

Model Number	UF27B-D2	UF48B-D4
Interior Storage Capacity (AHAM)	6.21 ft ³	12 ft ³
Overall Dimensions (W x D x H including 4" casters)	27" x 30" x 33.75"	48" x 30" x 33.75"
Depth with Doors Open at 90°A	N/A	N/A
Interior Door Opening Width	N/A	N/A
Depth with Drawer Fully Open	N/A	52"
Interior Door Opening Height	52"	N/A
Drawer Pan Capacity (pans by others)	(1) 12" x 20" x 6" deep pan per drawer	(1) 1/2 size and (1) 1/3 size, 6" deep
Adjustable Shelves	N/A	N/A
Shelf Dimensions (W x D)	N/A	N/A
Crated Shipping Weight	207 lbs.	331 lbs.
Crated Shipping Dimensions (L x W x H)	34" x 31.5" x 36.5"	52.5" x 34" x 36.5"
Voltage	115V/60/1	115V/60/1
Amperage (AMP)	3	4
HACR Breaker (AMP)	15	15
Energy Consumption (kWh / day) ASHRAE	2.4	3.60
Heat Rejection (BTU / hr)	489	756
Voltage Range	104 - 126	104 - 126
Ambient Temp. Range	45° - 100°F	45° - 100°F
Temperature Range	-10° - +10°F	-10° - +10°F
Refrigerant	R290	R290





SIDEMOUNT REFRIGERATOR UNDERCOUNTERS AND WORKTOPS

MORE SPACE INSIDE AND OUT

The space saving design places the condenser on the side of the unit creating a front-breathing air flow which means more space inside and out for your operation to flow.

Requires a back wall clearance of just 1" and is shallower compared to rear mount units giving your operation more room to move.



- Hoshizaki's signature air flow movement circulates cold air top to bottom to surround food with uniform cool temperatures.
- More usable interior space, (fits full size pans in top and bottom shelves and drawers).
- Insulated with 2" CFC free, foamed in place polyurethane for superior cooling, temperature maintenance and reduced energy usage.
- Energy efficient hot gas condensate removal is standard.
- Stainless steel exterior and interior for superior durability.



Scan to
View
Sidemount
Models



UNDERCOUNTERS | SIDEMOUNTS

Refrigerators and Freezers with Doors

34" WORK HEIGHT W/ 4" CASTERS



ULR46B ★



ULR60B ★



ULR67B ★



ULR93B ★

- Front breathing air flow design allows for just 1" of rear wall clearance
- Stainless steel interior and exterior front, sides and top
- Engineered to maintain NSF-7 temperatures in 100°F ambient

- Heavy duty drawers with removeable gaskets
- Cabinet and drawers are insulated with 2" foamed-in-place polyurethane
- 4" Stem casters standard

Model Number	ULR46B ★	ULR60B ★	ULR67B ★	ULR93B ★	ULF46B	ULF60B	ULF67B
Interior Storage Capacity (AHAM)	11.78 ft³	17.22 ft³	19.97 ft³	30.17 ft³	11.78 ft³	17.22 ft³	19.97 ft³
Overall Dimensions *(W x D x H including 4" casters)	46" x 33.25" x 33.875"*	60" x 33.25" x 33.875"*	67" x 33.25" x 33.875"*	93" x 33.25" x 33.875"*	46" x 33.25" x 33.875"*	60" x 33.25" x 33.875"*	67" x 33.25" x 33.875"*
Depth with Doors Open at 90°	60.5"	54.75"	57.75"	57.75"	60.5"	54.75"	57.75"
Interior Door Opening Width	25.5"	19.5"	22.5"	22.5"	22.5"	19.5"	22.5"
Interior Door Opening Height	23"	23"	23"	23"	23"	23"	23"
Adjustable Shelves	2	4	4	4	2	4	4
Shelf Dimensions (W x D)	28.75" x 25.5"	21.5" x 25.5"	24.75" x 25.5"	24.75" x 25.5"	28.75" x 25.5"	21.5" x 25.5"	24.75" x 25.5"
Crated Shipping Weight	263 lbs.	322 lbs.	345 lbs.	455 lbs.	263 lbs.	322 lbs.	345 lbs.
Crated Shipping Dimensions (L x W x H)	48.75" x 34.75" x 36"	63.75" x 35.75" x 36"	70.75" x 35.75" x 36"	95.25" x 34.5" x 36"	48.75" x 34.75" x 36"	63.75" x 35.75" x 36"	70.75" x 35.75" x 36"
Voltage	115V/60/1	115V/60/1	115V/60/1	115V/60/1	115V/60/1	115V/60/1	115V/60/1
Amperage (AMP)	3	3	3	5	4	5	5
HACR Breaker (AMP)	15	15	15	15	15	15	15
Energy Consumption (kWh / day) ASHRAE	0.92	1.26	1.33	1.87	3.36	4.50	4.49
Heat Rejection (BTU / hr)	333	312	341	448	645	786	851
Voltage Range	104 - 126	104 - 126	104 - 126	104 - 126	104 - 126	104 - 126	104 - 126
Ambient Temp. Range	45° - 100°F	45° - 100°F	45° - 100°F	45° - 100°F	45° - 100°F	45° - 100°F	45° - 100°F
Control Setpoint Range	28° to 45°F	28° to 45°F	28° to 45°F	28° to 45°F	-10 to 10°F	-10 to 10°F	-10 to 10°F
Refrigerant	R290	R290	R290	R290	R290	R290	R290



UNDERCOUNTERS | SIDEMOUNTS

Refrigerator Drawer/Door Combinations

34" WORK HEIGHT W/ 4" CASTERS



ULR60B-D2



ULR67B-D2



ULR93B-D2



ULR93B-D4

- Front breathing air flow design allows for just 1" of rear wall clearance
- Stainless steel interior and exterior front, sides and top
- Engineered to maintain NSF-7 temperatures in 100°F ambient

- Heavy duty drawers with removeable gaskets
- Cabinet and drawers are insulated with 2" foamed-in-place polyurethane
- 4" Stem casters standard

Model Number	ULR60B-D2	ULR67B-D2	ULR93B-D2	ULR93B-D4
Interior Storage Capacity (AHAM)	17.22 ft³	19.97 ft³	30.17 ft³	30.17 ft³
Overall Dimensions *(L x W x H including 4" casters)	60" x 33.25" x 33.875"*	67" x 33.25" x 33.875"*	93" x 33.25" x 33.875"*	93" x 33.25" x 33.875"*
Depth with Door Fully Open (including 1" bumper)	54.75"	54.75"	57.75"	57.75"
Depth With Drawer Fully Open	57.5"	57.5"	57.5"	57.5"
Door/Drawer Opening Width x Height	19.5" x 23"(door) / 19.5" x 9" (drawer)	22.5" x 23"(door) / 19.5" x 9" (drawer)	22.5" x 23"(door) / 19.5" x 9" (drawer)	22.5" x 23"(door) / 19.5" x 9" (drawer)
Shelves (#) / Dimensions(W x D)	2 / 21.5" x 25.5"	2 / 24.5" x 25.5"	4 / 24.5" x 25.5"	4 / 24.5" x 25.5"
Drawer Pan Capacity (pans by others)	(1) 12 x 20 full size pan and (2) ¼ size, 6" deep pans	(2) 12 x 20 x 6" deep pans	(2) 12 x 20 x 6" deep pans	(2) 12 x 20 x 6" deep pans
Crated Shipping Weight	363 lbs.	404 lbs.	500 lbs.	545 lbs.
Crated Shipping Dimensions (L x W x H)	63.75" x 35.75" x 36"	70.75" x 35.75" x 36"	95.25" x 34.5" x 36"	95.25" x 34.5" x 36"
Voltage	115V/60/1	115V/60/1	115V/60/1	115V/60/1
Amperage (AMP)	3	3	5	5
HACR Breaker (AMP)	15	15	15	15
Energy Consumption (kWh / day) NSF	1.272	1.320	1.879	1.879
Heat Rejection (BTU / hr)	305	414	448	448
Voltage Range	104 - 126	104-126	104-126	104-126
Ambient Temp. Range	45° -100°F	45° -100°F	45° -100°F	45° -100°F
Control Setpoint Range	28° to 45°F	28° to 45°F	28° to 45°F	28° to 45°F
Refrigerant	R290	R290	R290	R290

UNDERCOUNTERS | SIDEMOUNTS

Refrigerators with Drawers

34" WORK HEIGHT W/ 4" CASTERS



ULR46B-D2



ULR60B-D4



ULR67B-D4



ULR93B-D6

- Front breathing air flow design allows for just 1" of rear wall clearance
- Stainless steel interior and exterior front, sides and top
- Engineered to maintain NSF-7 temperatures in 100°F ambient
- Heavy duty drawers with removeable gaskets
- Cabinet and drawers are insulated with 2" foamed-in-place polyurethane
- 4" Stem casters standard

Model Number	ULR46B-D2	ULR60B-D4	ULR67B-D4	ULR93B-D6
Interior Storage Capacity (AHAM)	11.78 ft ³	17.22 ft ³	19.97 ft ³	30.17 ft ³
Overall Dimensions *(W x D x H including 4" casters)	46" x 33.25" x 33.875"*	60" x 33.25" x 33.875"*	67" x 33.25" x 33.875"*	93" x 33.25" x 33.875"
Depth with Drawer Fully Open	57.5"	57.5"	57.5"	57.5"
Drawer Pan Capacity (pans by others)	(2) 12 x 20" full size, 6" deep pans	(2) 12 x 10" half size pans and (2) 12 x 6.5" 1/3 size pans, 6" deep pans	22.5"	(2) 12 x 20" full size, 6" deep pans
Crated Shipping Weight	313 lbs.	408 lbs.	443 lbs.	589 lbs.
Crated Shipping Dimensions (L x W x H)	48.75" x 34.75" x 36"	63.75" x 35.75" x 36"	70.75" x 35.75" x 36"	95.25" x 34.5" x 36"
Voltage	115/60/1	115/60/1	115/60/1	115/60/1
Amperage (AMP)	3	3	3	5
HACR Breaker (AMP)	15	15	15	15
Energy Consumption (kWh / day) ASHRAE	0.92	1.26	1.33	1.87
Heat Rejection (BTU / hr)	333	305	381	576
Voltage Range	104-126	104-126	104-126	104-126
Ambient Temp. Range	45° to 100°F	45° to 100°F	45° to 100°F	45° to 100°F
Temperature Range	28° to 45°F	28° to 45°F	28° to 45°F	28° to 45°F
Refrigerant	R290	R290	R290	R290



UNDERCOUNTER | LOW-PROFILE

Refrigerator Solid Doors

32" WORK HEIGHT W/ 2.25" CASTERS



UR27B-LP(-01)★



UR48B-LP★

- Specifically designed to fit under an ADA compliant 34" work surface height counter 
- Engineered to maintain NSF-7 temperatures in 100°F ambient
- Stainless steel exterior front, sides and top with stainless steel interior sides, back, and floor
- Innovative air distribution system distributes air evenly

Model Number	UR27B-LP★ UR27B-LP-01* (01 Cylinder Door Lock)	UR36B-LP★ UR36B-LP-01* (01 Cylinder Door Lock)	UR48B-LP★ UR48B-LP-01* (01 Cylinder Door Lock)	UR60B-LP★ UR60B-LP-01* (01 Cylinder Door Lock)	UR72B-LP★ UR72B-LP-01* (01 Cylinder Door Lock)
Interior Storage Capacity (AHAM)	6.21 ft ³	8.64 ft ³	12 ft ³	15.1 ft ³	18.27 ft ³
Overall Dimensions W x D x H including (2.25" casters)	27" x 30" x 31.9"	36" x 30" x 31.9"	48" x 30" x 31.9"	60" x 30" x 31.9"	72" x 30" x 31.9"
Depth with Doors Open at 90°	54.5"	57.5"	51.5"	57.5"	51.5"
Interior Door Opening Width	22.75"	25.5"	19.5"	27.25"	19.5"
Interior Door Opening Height	23"	23"	23"	23"	23"
Adjustable Shelves	1	1	2	6	3
Shelf Dimensions (W x D)	22" x 16"	31" x 16"	21.5" x 16"	27.25" x 16"	22" x 16"
Crated Shipping Weight	173 lbs.	204 lbs.	249 lbs.	290 lbs.	339 lbs.
Crated Shipping Dimensions (L x W x H)	34" x 31.5" x 35.5"	40.5" x 34" x 35.5"	52.5" x 34" x 35.5"	62.5" x 34" x 35.5"	73.75" x 32" x 35.5"
Voltage	115V/60/1	115V/60/1	115V/60/1	115V/60/1	115V/60/1
Amperage (AMP)	2.7	2.5	3	3	3
HACR Breaker (AMP)	15	15	15	15	15
Energy Consumption (kWh / day) ASHRAE	0.65	0.69	1.05	0.94	1.12
Heat Rejection (BTU / hr)	193	184	278	249	360
Voltage Range	104 - 126	104 - 126	104 - 126	104 - 126	104 - 126
Ambient Temp. Range	45° - 100°F	45° - 100°F	45° - 100°F	45° - 100°F	45° - 100°F
Control Setpoint Range	32° - 52°F	32° - 52°F	32° - 52°F	32° - 52°F	32° - 52°F
Refrigerant	R290	R290	R290	R290	R290

*MADE TO ORDER - Please contact your local HOSHIZAKI Sales Representative for availability.



UNDERCOUNTER | LOW-PROFILE

Refrigerator Drawer/Door Combinations

32" WORK HEIGHT W/ 2.25" CASTERS



UR48B-LPD4



UR60B-LPD2

- Specifically designed to fit under an ADA compliant 34" work surface height counter 
- Engineered to maintain NSF-7 temperatures in 100°F ambient
- Stainless steel exterior front, sides and top with stainless steel interior sides, back, and floor
- Innovative air distribution system distributes air evenly

Model Number	UR27B-LPD2	UR48B-LPD2	UR48B-LPD4	UR60B-LPD2	UR60B-LPD4	UR72B-LPD6
Interior Storage Capacity (AHAM)	6.21 ft ³	12 ft ³	12 ft ³	15.1 ft ³	15.1 ft ³	18.27 ft ³
Overall Dimensions W x D x H including (2.25" casters)	27" x 30" x 31.9"	48" x 30" x 31.9"	48" x 30" x 31.9"	60" x 30" x 31.9"	60" x 30" x 31.9"	72" x 30" x 31.9"
Depth With Drawer Fully Open	51"	51"	51"	51"	51"	51"
Drawer Opening Width x Height	22.75" x 23"	19.5" x 23"	19.5" x 23"	25.5" x 23"	25.5" x 23"	19.5" x 23"
Drawer Pan Capacity (pans by others)	(1) 12 x 20 full size pan & (2) ¼ size pans	(1) ½ size pan & (1) 1/3 size pan	(1) ½ size pan & (1) 1/3 size pan	(1) ½ size pan & (1) 1/3 size pan	(1) 12 x 20 full size pan & (2) ¼ size pans	(1) ½ size pan & (1) 1/3 size pan
Crated Shipping Weight	203 lbs.	282 lbs.	314 lbs.	292 lbs.	346 lbs.	443 lbs.
Crated Shipping Dimensions (L x W x H)	34" x 31.5" x 35.5"	52.5" x 34" x 35.5"	52.5" x 34" x 35.5"	62.5" x 34" x 35.5"	62.5" x 34" x 35.5"	73.75" x 32" x 35.5"
Voltage	115V/60/1	115V/60/1	115V/60/1	115V/60/1	115V/60/1	115V/60/1
Amperage (AMP)	3	3	3	3	3	3
HACR Breaker (AMP)	15	15	15	15	15	15
Energy Consumption (kWh / day) NSF	0.65	1.05	1.05	0.94	0.94	1.12
Heat Rejection (BTU / hr)	152	278	278	249	249	360
Voltage Range	104 - 126	104 - 126	104 - 126	104 - 126	104 - 126	104 - 126
Ambient Temp. Range	45° - 100°F	45° - 100°F	45° - 100°F	45° - 100°F	45° - 100°F	45° - 100°F
Control Setpoint Range	32° - 52°F	32° - 52°F	32° - 52°F	32° - 52°F	32° - 52°F	32° - 52°F
Refrigerant	R290	R290	R290	R290	R290	R290



UNDERCOUNTER | LOW-PROFILE

Freezers Drawers and Doors

32" WORK HEIGHT W/ 2.25" CASTERS



UF27B-LP(-01)



UF27B-LPD2



UF48B-LP(-01)



UF48B-LPD4

- Specifically designed to fit under an ADA compliant 34" work surface height counter 
- Engineered to maintain NSF-7 temperatures in 100°F ambient
- Stainless steel exterior front, sides and top with stainless steel interior sides, back, and floor
- Innovative air distribution system distributes air evenly

Model Number	UF27B-LP UF27B-LP-01 (01 Cylinder Door Lock)	UF48B-LP UF48B-LP01 (01 Cylinder Door Lock)	UF60B-LP UF60B-LP-01 (01 Cylinder Door Lock)	UF27B-LPD2	UF48B-LPD2	UF48B-LPD4
Interior Storage Capacity (AHAM)	6.21 ft ³	12 ft ³	15.1 ft ³	6.21 ft ³	12 ft ³	12 ft ³
Overall Dimensions W x D x H including (2.25" casters)	N/A	N/A	N/A	27" x 30" x 31.9"	48" x 30" x 31.9"	48" x 30" x 31.9"
Depth With Drawer Fully Open	N/A	N/A	N/A	51"	51.5"	51"
Drawer Opening Width x Height	N/A	N/A	N/A	22.75" x 23"	19.5" x 23"	19.5" x 23"
Drawer Pan Capacity (pans by others)	N/A	N/A	N/A	(1) 12 x 20 full size pan and (2) ¼ size pans	(1) ½ size pan & (1) 1/3 size pan	(1) ½ size pan & (1) 1/3 size pan
Crated Shipping Weight	175 lbs.	258 lbs.	310 lbs.	207 lbs.	295 lbs.	331 lbs.
Crated Shipping Dimensions (L x W x H)	34" x 31.5" x 35.5"	52.5" x 34" x 35.5"	62.5" x 34" x 35.5"	34" x 31.5" x 35.5"	52.5" x 34" x 35.5"	52.5" x 34" x 35.5"
Voltage	115V/60/1	115V/60/1	115V/60/1	115/60/1	115/60/1	115/60/1
Amperage (AMP)	2.4	3.6	4	3	4	4
HACR Breaker (AMP)	15	15	15	15	15	15
Energy Consumption (kWh / day) NSF	2.4	3.6	3.95	2.4	3.6	3.6
Heat Rejection (BTU / hr)	509	756	727	489	756	756
Voltage Range	104 - 126	104 - 126	104 - 126	104 - 126	104 - 126	104 - 126
Ambient Temp. Range	45° - 100°F	45° - 100°F	45° - 100°F	45° to 100°F	45° to 100°F	45° to 100°F
Control Setpoint Range	-10° to 10°F	-18° to 10°F	-18° to 10°F	-12° to 11°F	-18° to 10°F	-12° to 11°F
Refrigerant	R290	R290	R290	R290	R290	R290

UNDERCOUNTER | LOW-PROFILE

Glass Door Refrigerators and Freezer 32" WORK HEIGHT W/ 2.25" CASTERS



UR27B-GLP01 ★



UR48B-GLP01 ★



UF27B-GLP01

- Stainless steel interior and exterior front, sides and top
- Energy efficient LED interior lights with on/off switch
- Standard 2.25" casters (2 with brakes)

- Meets ADA requirements 
- Glass doors with locks are energy efficient multi pane, argon filled
- Field reversible glass doors

Model Number	UR27B-GLP01 ★	UR48B-GLP01 ★	UF27B-GLP01
Interior Storage Capacity (AHAM)	6.21 ft ³	12 ft ³	6.21 ft ³
Overall Dimensions W x D x H including (2.25" casters)	27" x 31" x 32"	48" x 31" x 32"	27" x 31" x 32"
Depth with Doors Open at 90°	55.5"	52"	55.5"
Interior Door Opening Width	22.75"	19.5"	22.75"
Interior Door Opening Height	23"	23"	23"
Adjustable Shelves	1	2	1
Shelf Dimensions (W x D)	22" x 16"	21.5" x 16"	22" x 16"
Crated Shipping Weight	183 lbs.	249 lbs.	189 lbs.
Crated Shipping Dimensions (L x W x H)	36" x 31.5" x 35.5"	52.5" x 34" x 36.5"	36" x 31.5" x 35.5"
Voltage	115V/60/1	115V/60/1	115V/60/1
Amperage (AMP)	3	3	3
HACR Breaker (AMP)	15	15	15
Energy Consumption (kWh / day) ASHRAE	1.15	1.46	4.32
Heat Rejection (BTU / hr)	263	432	468
Voltage Range	104 - 126	104 - 126	104 - 126
Ambient Temp. Range	45° - 100°F	45° - 100°F	45° - 80°F
Temperature Range	32° - 52°F	32° - 52°F	-10° - 10°F
Refrigerant	R290	R290	R290





STEELHEART® WORKTOPS AT THE READY.



STANDALONE UNITS WITH A
4" BACK EDGE TO PREVENT
SPILLS AND CONTAIN SUPPLIES.

Hoshizaki's worktop refrigerators and
freezers combine cold storage with
a built-in prep surface, delivering
reliable cooling and space-saving
efficiency for busy commercial
kitchens and bars.



Scan to
View
Worktop
Models



WORKTOPS | REFRIGERATORS

Solid Doors

36" WORK HEIGHT W/ 6" CASTERS



WR27B(-01)★



WR36B(-01)★



WR60B(-01)★



WR72B(-01)★

- Stainless steel interior and exterior front, sides and top
- Field reversible doors
- Cabinet and doors are insulated with 2" foamed in place polyurethane
- Enamel coated evaporator coil
- Engineered to maintain NSF-7 temperatures in 100°F ambient
- 6" Stern casters standard

Model Number	WR27B ★ WR27B-01* (01 Cylinder Door Lock)	WR36B ★ WR36B-01* (01 Cylinder Door Lock)	WR48B ★ WR48B-01* (01 Cylinder Door Lock)	WR60B ★ WR60B-01* (01 Cylinder Door Lock)	WR72B ★ WR72B-01* (01 Cylinder Door Lock)
Interior Storage Capacity (AHAM)	6.21 ft ³	8.64 ft ³	12 ft ³	15.1 ft ³	18.27 ft ³
Overall Dimensions (W x D x H including 6" casters)	27" x 30" x 40"	36" x 30" x 40"	48" x 30" x 40"	60" x 30" x 40"	72" x 30" x 40"
Depth with Doors Open at 90°	55.5"	58.5"	52.5"	58.5"	52.5"
Interior Door Opening Width x Height	22.75" x 23"	25.5" x 23"	19.5" x 23"	25.5" x 23"	19.5" x 23"
Adjustable Shelves	1	1	2	2	3
Shelf Dimensions (W x D)	22" x 16"	31" x 16"	21.5" x 16"	27.25" x 16"	22" x 16"
Crated Shipping Weight	183 lbs.	216 lbs.	264 lbs.	302 lbs.	350 lbs.
Crated Shipping Dimensions (L x W x H)	34" x 31.5" x 40.5"	40.5" x 34" x 40.5"	52.5" x 34" x 40.5"	62.5" x 34" x 40.5"	73.75" x 32" x 36.5"
Voltage	115V/60/1	115V/60/1	115V/60/1	115V/60/1	115V/60/1
Amperage (AMP)	2.7	2.5	3	3	3
HACR Breaker (AMP)	15	15	15	15	15
Energy Consumption (kWh / day) ASHRAE	0.65	0.69	1.05	0.927	1.12
Heat Rejection (BTU / hr)	193	184	278	249	360
Voltage Range	104 - 126	104 - 126	104 - 126	104 - 126	104 - 126
Ambient Temp. Range	45° - 100°F	45° - 100°F	45° - 100°F	45° - 100°F	45° - 100°F
Temperature Range	32° - 52°F	32° - 52°F	32° - 52°F	32° - 52°F	32° - 52°F
Refrigerant	R290	R290	R290	R290	R290

*MADE TO ORDER - Please contact your local HOSHIZAKI Sales Representative for availability.



WORKTOP | REFRIGERATORS

Drawer/Door Combination

36" WORK HEIGHT W/ 6" CASTERS



WR48B-D2



WR60B-D2

- Stainless steel interior and exterior front sides and top
- Cabinet and drawers are insulated with 2" foamed-in-place polyurethane
- Door/Drawer configuration can be located in any cabinet section
- Enamel coated evaporator coil
- Engineered to maintain NSF-7 temperatures in 100°F ambient.
- Field reversible doors

Model Number	WR48B-D2	WR60B-D2
Interior Storage Capacity (AHAM)	12 ft ³	15.1 ft ³
Overall Dimensions (L x W x H)	48" x 30" x 40" (including 6" casters)	60" x 30" x 40" (including 6" casters)
Depth With Door Open At 90°	52.5"	58.5"
Depth With Drawer Fully Open	52.5"	52"
Door Opening Width x Height	19.5" x 23"	25.5" x 23"
Shelves (#) / Dimensions(W x D)	(1) / 21.5" x 16"	(1) / 27.25" x 16"
Drawer Pan Capacity (pans by others)	(1) 1/2 and (1) 1/3 size pans, 6" deep	12" x 20" x 6" deep (1) full size pan, 6" deep
Crated Shipping Weight	295 lbs.	346 lbs.
Crated Shipping Dimensions (L x W x H)	52.5" x 34" x 40.5"	62.5" x 34" x 40.5"
Voltage	115V/60/1	115V/60/1
Amperage (AMP)	3	3
HACR Breaker (AMP)	15	15
Energy Consumption (kWh / day) NSF	1.05	1.75
Heat Rejection (BTU / hr)	278	249
Voltage Range	104 - 126	104 - 126
Ambient Temp. Range	45° -100°F	45° -100°F
Temperature Range	32° - 52°F	32° - 52°F
Refrigerant	R290	R290

WORKTOP | REFRIGERATORS

Drawers

36" WORK HEIGHT W/ 6" CASTERS



WR27B-D2

WR48B-D4

WR60B-D4

WR72B-D6

- Stainless steel interior and exterior front, sides and top
- Cabinet and drawers are insulated with 2" foamed-in-place polyurethane
- Engineered to maintain NSF-7 temperatures in 100°F ambient
- Heavy duty drawers with removeable gaskets
- 6" Stem casters standard
- Electronic controls

Model Number	WR27B-D2	WR48B-D4	WR60B-D4	WR72B-D6
Interior Storage Capacity (AHAM)	6.21 ft ³	12 ft ³	15.1 ft ³	18.27 ft ³
Overall Dimensions (W x D x H including 6" casters)	27" x 30" x 40"	48" x 30" x 40"	60" x 30" x 40"	72" x 30" x 40"
Depth with Drawer Fully Open	52"	52"	52"	52"
Drawer Pan Capacity (pans by others)	(1) 12" x 20" x 6" deep pan per drawer	(1) 1/2 and (1) 1/3 size pan per drawer, 6" deep	(1) 12" x 20" x 6" deep pan per drawer	(1) 1/2 and (1) 1/3 size pan per drawer, 6" deep
Crated Shipping Weight	214 lbs.	332 lbs.	381 lbs.	460 lbs.
Crated Shipping Dimensions (L x W x H)	34" x 31.5" x 40.5"	52.5" x 34" x 40.5"	62.5" x 34" x 40.5"	73.75" x 32" x 40.5"
Voltage	115V/60/1	115V/60/1	115V/60/1	115V/60/1
Amperage (AMP)	3	3	3	3
HACR Breaker (AMP)	15	15	15	15
Energy Consumption (kWh / day) ASHRAE	0.65	1.05	1.75	1.12
Heat Rejection (BTU / hr)	152	278	249	360
Voltage Range	104 - 126	104 - 126	104 - 126	104 - 126
Ambient Temp. Range	45° - 100°F	45° - 100°F	45° - 100°F	45° - 100°F
Temperature Range	32° - 52°F	32° - 52°F	32° - 52°F	32° - 52°F
Refrigerant	R290	R290	R290	R290



WORKTOP | FREEZERS

Solid Doors

36" WORK HEIGHT W/ 6" CASTERS



WF27B(-01)



WF48B(-01)



WF60B(-01)★

- Stainless steel interior and exterior front, sides and top
- Field reversible doors
- Cabinet and doors are insulated with 2" foamed-in-place polyurethane
- Electronic controls
- Engineered to maintain NSF-7 temperatures in 100°F ambient
- 6" Stem casters standard

Model Number	WF27B WF27B-01* (01 Cylinder Door Lock)	WF48B WF48B-01* (01 Cylinder Door Lock)	WF60B ★ WF60B-01* (01 Cylinder Door Lock)
Interior Storage Capacity (AHAM)	7.21 ft ³	13.66 ft ³	17.55 ft ³
Overall Dimensions (W x D x H including 4" casters)	27" x 30" x 40"	48" x 30" x 40"	60" x 30" x 40"
Depth with Doors Open at 90°	55.5"	52.5"	58.5"
Interior Door Opening Width	22.75"	19.5"	25.5"
Interior Door Opening Height	23"	23"	23"
Adjustable Shelves	1	2	2
Shelf Dimensions (W x D)	22" x 16"	21.38" x 16"	27.25" x 16"
Crated Shipping Weight	185 lbs.	285 lbs.	320 lbs.
Crated Shipping Dimensions (L x W x H)	34" x 31.5" x 40.5"	51" x 32" x 40.25"	62" x 34" x 40.25"
Voltage	115V/60/1	115V/60/1	115V/60/1
Amperage (AMP)	2.4	5.9	5.6
HACR Breaker (AMP)	15	15	15
Energy Consumption (kWh / day) ASHRAE	2.4	3.64	4.22
Heat Rejection (BTU / hr)	489	656	804.2zz
Voltage Range	104 - 126	104 - 126	104 - 126
Ambient Temp. Range	45° - 100°F	45° - 100°F	45° - 100°F
Temperature Range	-10° - +10°F	-10° - +10°F	-10° - +10°F
Refrigerant	R290	R290	R290

*MADE TO ORDER - Please contact your local HOSHIZAKI Sales Representative for availability.



WORKTOP | FREEZERS

Drawers

36" WORK HEIGHT W/ 6" CASTERS



WF27B-D2



WF48B-D4

- Stainless steel interior and exterior front, sides and top
- Heavy duty drawers with removeable gaskets
- Cabinet and drawers are insulated with 2" foamed-in-place polyurethane
- Engineered to maintain NSF-7 temperatures in 100°F ambient
- 6" Stem casters standard
- Electronic controls

Model Number	WF27B-D2	WF48B-D4
Interior Storage Capacity (AHAM)	6.21 ft ³	12 ft ³
Overall Dimensions (W x D x H including 6" casters)	27" x 30" x 40"	48" x 30" x 40"
Depth with Drawer Fully Open	52"	52"
Drawer Pan Capacity (pans by others)	(1) 12" x 20" x 6" deep pan per drawer	(1) 1/2 Size and (1) 1/3 Size, 6" deep
Crated Shipping Weight	218 lbs.	346 lbs.
Crated Shipping Dimensions (L x W x H)	34" x 31.5" x 40.5"	52.5" x 34" x 40.5"
Voltage	115V/60/1	115V/60/1
Amperage (AMP)	3	4
HACR Breaker (AMP)	15	15
Energy Consumption (kWh / day) ASHRAE	2.4	3.60
Heat Rejection (BTU / hr)	489	756
Voltage Range	104 - 126	104 - 126
Ambient Temp. Range	45° - 100°F	45° - 100°F
Temperature Range	-10° - +10°F	-10° - +10°F
Refrigerant	R290	R290



WORKTOP | SIDEMOUNTS

Refrigerators & Freezers With Solid Doors

36" WORK HEIGHT W/ 6" CASTERS



WLR46B ★



WLR60B ★



WLR67B ★



WLR93B ★

- Front breathing air flow design allows for just 1" of rear wall clearance
- Stainless steel interior and exterior front, sides and top
- Engineered to maintain NSF-7 temperatures in 100°F ambient
- Heavy duty field reversible doors
- Cabinet and drawers are insulated with 2" foamed-in-place polyurethane
- 6" Stem casters standard

Model Number	WLR46B ★	WLR60B ★	WLR67B ★	WLR93B ★	WLF46B	WLF60B	WLF67B
Interior Storage Capacity (AHAM)	11.78 ft ³	17.22 ft ³	19.97 ft ³	30.17 ft ³	11.78 ft ³	17.22 ft ³	19.97 ft ³
Overall Dimensions *(W x D x H including 6" casters)	46" x 33.25" x 40.25"*	60" x 33.25" x 40.25"*	67" x 33.25" x 40.25"*	93" x 33.25" x 40.25"*	46" x 33.25" x 40.25"*	60" x 33.25" x 40.25"*	67" x 33.25" x 40.25"*
Depth with Doors Open at 90°	60.5"	54.75"	57.75"	57.75"	60.5"	54.75"	57.75"
Interior Door Opening Width	25.5"	19.5"	22.5"	22.5"	25.5"	19.5"	22.5"
Interior Door Opening Height	23"	23"	23"	23"	23"	23"	23"
Adjustable Shelves	2	4	4	6	2	4	4
Shelf Dimensions (W x D)	28.75" x 25.5"	21.5" x 25.5"	24.75" x 25.5"	24.75" x 25.5"	28.75" x 25.5"	21.5" x 25.5"	24.75" x 25.5"
Crated Shipping Weight	278 lbs.	344 lbs.	354 lbs.	478 lbs.	278 lbs.	344 lbs.	354 lbs.
Crated Shipping Dimensions (L x W x H)	48.75" x 34.75" x 40"	63.75" x 35.75" x 40"	70.75" x 35.75" x 40"	95.25" x 34.5" x 40"	48.75" x 34.75" x 40"	63.75" x 35.75" x 40"	70.75" x 35.75" x 40"
Voltage	115V/60/1	115/60/1	115/60/1	115/60/1v	115V/60/1	115/60/1	115/60/1
Amperage (AMP)	3	3	3	5	4	5	5
HACR Breaker (AMP)	15	15	15	15	15	15	15
Energy Consumption (kWh / day) ASHRAE	0.92	1.26	1.33	1.87	3.36	4.50	4.49
Heat Rejection (BTU / hr)	333	312	341	448	645	786	851
Voltage Range	104 - 126	104 - 126	104 - 126	104 - 126	104 - 126	104 - 126	104 - 126
Ambient Temp. Range	45° - 100°F	45° - 100°F	45° - 100°F	45° - 100°F	45° - 100°F	45° - 100°F	45° - 100°F
Control Setpoint Range	28° to 45°F	28° to 45°F	28° to 45°F	28° to 45°F	-10° to 10°F	-10° to 10°F	-10° to 10°F
Refrigerant	R290	R290	R290	R290	R290	R290	R290

WORKTOP | SIDEMOUNTS

Refrigerator Drawer/Door Combinations

36" WORK HEIGHT W/ 6" CASTERS



WLR46B-D2



WLR67B-D2



WLR67B-D4



WLR93B-D4

- Front breathing air flow design allows for just 1" of rear wall clearance
- Stainless steel interior and exterior front, sides and top
- Engineered to maintain NSF-7 temperatures in 100°F ambient
- Heavy duty drawers with removeable gaskets
- Cabinet and drawers are insulated with 2" foamed-in-place polyurethane
- 6" Stem casters standard

Model Number	WLR46B-D2	WLR60B-D2	WLR60B-D4	WLR67B-D2	WLR67B-D4	WLR93B-D2	WLR93B-D4	WLR93B-D6
Interior Storage Capacity (AHAM)	11.78 ft³	17.22 ft³	17.22 ft³	19.97 ft³	19.97 ft³	30.17 ft³	30.17 ft³	30.17 ft³
Overall Dimensions *(W x D x H including 6" casters)	46" x 33.25" x 40.25"*	60" x 33.25" x 40.25"*	60" x 33.25" x 40.25"*	67" x 33.25" x 40.25"*	67" x 33.25" x 40.25"*	97" x 33.25" x 40.25"*	97" x 33.25" x 40.25"*	93" x 33.25" x 40.25"*
Depth with Drawer Fully Open (including 1" bumper)	57.5"	57.5"	57.5"	57.5"	57.5"	57.5"	57.5"	57.5"
Drawer Pan Capacity (pans by others)	(2) 12 x 20" full size, 6" deep pans	(2) 12 x 10" half size pans and (2) 12 x 6.5" 1/3 size pans, 6" deep pans	(2) 12 x 10" half size pans and (2) 12 x 6.5" 1/3 size pans, 6" deep pans	(2) 12 x 20 x 6" deep pans	(2) 12 x 20" full size, 6" deep pans	(2) 12 x 20 x 6" deep pans	(2) 12 x 20 x 6" deep pans	(2) 12 x 20" full size, 6" deep pans
Crated Shipping Weight	328 lbs.	385 lbs.	430 lbs.	404 lbs.	452 lbs.	523 lbs.	568 lbs.	612 lbs.
Crated Shipping Dimensions (L x W x H)	48.75" x 34.75" x 40"	63.75" x 35.75" x 40"	63.75" x 35.75" x 40"	70.75" x 35.75" x 40"	70.75" x 35.75" x 40"	95.25" x 34.5" x 40"	95.25" x 34.5" x 40"	95.25" x 34.5" x 40"
Voltage	115V/60/1	115V/60/1	115V/60/1	115V/60/1	115V/60/1	115V/60/1	115V/60/1	115V/60/1
Amperage (AMP)	3	3	3	3	3	3	3	3
HACR Breaker (AMP)	15	15	15	15	15	15	15	15
Energy Consumption (kWh / day) ASHRAE	0.92	1.26	1.26	1.320	1.33	1.879	1.879	1.87
Heat Rejection (BTU / hr)	333	305	305	414	381	448	448	576
Voltage Range	104 - 126	104 - 126	104 - 126	104 - 126	104 - 126	104 - 126	104 - 126	104 - 126
Ambient Temp. Range	45° - 100°F	45° - 100°F	45° - 100°F	45° - 100°F	45° - 100°F	45° - 100°F	45° - 100°F	45° - 100°F
Temperature Range	28° to 45°F	28° to 45°F	28° to 45°F	28° to 45°F	28° to 45°F	28° to 45°F	28° to 45°F	28° to 45°F
Refrigerant	R290	R290	R290	R290	R290	R290	R290	R290





STEELHEART® PREP TABLES

WHAT YOU NEED, WHERE YOU NEED IT.



ENGINEERED FOR SUPERIOR COOLING
ONLY AVAILABLE FROM HOSHIZAKI




Hoshizaki's exclusive design distributes cold air through a system of louvered ducts positioned throughout the cabinet. Constant air movement circulates top to bottom and at each individual shelf to surround food with uniform cool temperatures.

Available in Sandwich Prep and Mega Top Sizes.



Scan to View
Drawer and Pan
Configuration
Guides



PREP TABLES | SANDWICH TOPS

Solid Doors

36" WORK HEIGHT W/ 6" CASTERS



SR27B-8



SR36B-10



SR48B-8



SR48B-12

- Stainless steel interior and exterior front, sides and top
- Cabinet and doors are insulated with 2" foamed-in-place polyurethane
- Provided with full complement of polycarbonate plastic 1/6th size pans 4" deep
- 1/2" x 10" Cutting board standard
- Engineered to maintain NSF-7 temperatures in 100°F ambient.
- Field reversible doors
- Divider Bars Included

Model Number	SR27B-8	SR36B-10	SR48B-8	SR48B-12
Interior Storage Capacity (AHAM)	6.21 ft³	8.7 ft³	12 ft³	12 ft³
Overall Dimensions (W x D x H including 6" casters)	27" x 30" x 44.25"	36" x 30" x 44.25"	48" x 34" x 44.25"	48" x 34" x 44.25"
Depth with Cutting Board installed	30.5"	30.5"	30.5"	30.5"
Depth with Doors Open at 90°	55.5"	57.5"	52.5"	52.5"
Interior Door Opening Width	22.75"	25.5"	19.5"	19.5"
Interior Door Opening Height	23"	23"	23"	23"
Adjustable Shelves	1	1	2	2
Shelf Dimensions (W x D)	22" x 16"	31" x 16"	21.25" x 16"	21.25" x 16"
Pan Capacity (# of 1/6 size x 4" deep)	8	10	8	12
Crated Shipping Weight	202 lbs.	245 lbs.	292 lbs.	301 lbs.
Crated Shipping Dimensions (L x W x H)	32" x 31.5" x 46.5"	40.5" x 32" x 46.5"	52.5" x 36" x 46.5"	52.5" x 36" x 46.5"
Voltage	115V/60/1	115V/60/1	115V/60/1	115V/60/1
Amperage (AMP)	2.3	2.7	3	3
HACR Breaker (AMP)	15	15	15	15
Energy Consumption (kWh / day) NSF	2.54	2.6	2.38	2.38
Heat Rejection (BTU / hr)	361	364.1	403	403
Voltage Range	104 - 126	104 - 126	104 - 126	104 - 126
Ambient Temp. Range	45° - 100°F	45° - 100°F	45° - 100°F	45° - 100°F
Temperature Range	32° - 52°F	32° - 52°F	32° - 52°F	32° - 52°F
Refrigerant	R290	R290	R290	R290



PREP TABLES | SANDWICH TOPS

Solid Doors

36" WORK HEIGHT W/ 6" CASTERS



SR60B-8



SR72B-16



SR72B-18

- Stainless steel interior and exterior front, sides and top
- Cabinet and doors are insulated with 2" foamed-in-place polyurethane
- Provided with full complement of polycarbonate plastic 1/6th size pans 4" deep
- 1/2" x 10" Cutting board standard
- Engineered to maintain NSF-7 temperatures in 100°F ambient.
- Field reversible doors

Model Number	SR60B-8	SR60B-12	SR60B-16	SR72B-12	SR72B-16	SR72B-18
Interior Storage Capacity (AHAM)	14.8 ft³	14.8 ft³	14.8 ft³	18 ft³	18 ft³	18 ft³
Overall Dimensions (W x D x H including 6" casters)	60" x 30" x 44.25"	60" x 30" x 44.25"	60" x 30" x 44.25"	72" x 30" x 44.25"	72" x 30" x 44.25"	72" x 30" x 44.25"
Depth with Cutting Board installed	30.5"	30.5"	30.5"	30.5"	30.5"	30.5"
Depth with Doors Open at 90°	58.5"	58.5"	58.5"	52.5"	52.5"	52.5"
Interior Door Opening Width	25.5"	25.5"	25.5"	19.5"	19.5"	19.5"
Interior Door Opening Height	23"	23"	23"	23"	23"	23"
Adjustable Shelves	2	2	2	3	3	3
Shelf Dimensions (W x D)	27.25" x 16"	27.25" x 16"	27.25" x 16"	22" x 16"	22" x 16"	22" x 16"
Pan Capacity (# of 1/6 size x 4" deep)	8	12	16	12	16	18
Crated Shipping Weight	346 lbs.	348 lbs.	359 lbs.	404 lbs.	406 lbs.	419 lbs.
Crated Shipping Dimensions (L x W x H)	61.75" X 32" X 46.5"	61.75" X 32" X 46.5"	61.75" X 32" X 46.5"	73.75" x 32" x 46.5"	73.75" x 32" x 46.5"	73.75" x 32" x 46.5"
Voltage	115V/60/1	115V/60/1	115V/60/1	115V/60/1	115V/60/1	115V/60/1
Amperage (AMP)	4	4	4	4	4	4
HACR Breaker (AMP)	15	15	15	15	15	15
Energy Consumption (kWh / day) NSF	4.05	4.05	4.05	5.05	5.05	5.05
Heat Rejection (BTU / hr)	575	575	575	719	719	719
Voltage Range	104 - 126	104 - 126	104 - 126	104 - 126	104 - 126	104 - 126
Ambient Temp. Range	45° - 100°F	45° - 100°F	45° - 100°F	45° - 100°F	45° - 100°F	45° - 100°F
Temperature Range	32° - 52°F	32° - 52°F	32° - 52°F	32° - 52°F	32° - 52°F	32° - 52°F
Refrigerant	R290	R290	R290	R290	R290	R290



PREP TABLES | SANDWICH TOPS

Drawers

36" WORK HEIGHT W/ 6" CASTERS



SR27B-8D2



SR48B-12D4



SR48B-12D2**

- Stainless steel interior and exterior front, sides and top
- Cabinet and drawers are insulated with 2" foamed-in-place polyurethane
- Provided with full complement of polycarbonate plastic 1/6th size pans 4" deep
- 1/2" x 10" Cutting board standard
- Engineered to maintain NSF-7 temperatures in 100°F ambient
- 6" Stem casters standard

Model Number	SR27B-8D2	SR48B-12D4	SR48B-12D2
Interior Storage Capacity (AHAM)	6.22 ft ³	12 ft ³	12 ft ³
Overall Dimensions (W x D x H including 6" casters)	27" x 30" x 44.25"	48" x 34" x 44.25"	48" x 34" x 44.25"
Depth With Cutting Board Installed	30.5"	30.5"	30.5"
Depth With Door Open At 90°	N/A	N/A	52.5"
Depth With Drawer Fully Open	52"	52"	52"
Door/Drawer Opening Width	19.5"	19.5"	19.5"
Adjustable Shelves / Shelf Dimensions (WxD)	N/A	N/A	(2) 21.25" x 16"
Drawer Pan Capacity (pans by others)	(1) 12 x 20 full size pan and (2) ¼ size pans. Bottom drawer will accommodate (1) full size pan.	(1) 1/2 and (1) 1/3 size pan per drawer, 6" deep	(1) 1/2 and (1) 1/3 size pans 6" deep
Pan Capacity (# of 1/6 size x 4" deep)	8 (6" max. pan depth)	12 (6" max. pan depth)	12 (6" max. pan depth)
Crated Shipping Weight	242 lbs	382 lbs.	355 lbs.
Crated Shipping Dimensions (L x W x H)	32"x 31.5" x 46.5"	52.5" x 36" x 46.5"	52.5" x 36" x 46.5"
Voltage	115V/60/1	115V/60/1	115V/60/1
Amperage (AMP)	2.3	3	3
HACR Breaker (AMP)	15	15	15
Energy Consumption (kWh / day) NSF	2.54	2.83	2.83
Heat Rejection (BTU / hr)	361	403	403
Voltage Range	104 - 126	104 - 126	104 - 126
Ambient Temp. Range	45° - 100°F	45° - 100°F	45° - 100°F
Temperature Range	32° - 52°F	32° - 52°F	32° - 52°F
Refrigerant	R290	R290	R290



PREP TABLES | MEGA TOPS

Solid Doors

36" WORK HEIGHT W/ 6" CASTERS



- Stainless steel interior and exterior front, sides and top
- Cabinet and doors insulated with 2" foamed-in-place polyurethane
- Provided with full complement of polycarbonate plastic 1/6th size pans
- 1/2" x 10" Cutting board with extended top for greater stability
- Engineered to maintain NSF-7 temperatures in 100°F ambient
- 6" Stem casters standard

Model Number	SR27B-12M	SR36B-15M	SR48B-12M	SR48B-18M
Interior Storage Capacity (AHAM)	6.22 ft³	8.7 ft³	12 ft³	12 ft³
Overall Dimensions (W x D x H including 6" casters)	27" x 34" x 44.25"	36" x 34" x 44.25"	48" x 34" x 44.25"	48" x 34" x 44.25"
Depth with Cutting Board installed	36.5"	36.5"	36.5"	36.5"
Depth with Doors Open at 90°	52.5"	58.5"	52.5"	52.5"
Interior Door Opening Width	22.75"	25.5"	19.5"	19.5"
Interior Door Opening Height	23"	23"	23"	23"
Adjustable Shelves	1	1	2	2
Shelf Dimensions (W x D)	22" x 16"	31" x 16"	21.5" x 16"	21.2" x 16"
Pan Capacity (# of 1/6 size x 4" deep)	12	15	12	18
Crated Shipping Weight	217 lbs.	258 lbs.	303 lbs.	315 lbs.
Crated Shipping Dimensions (L x W x H)	36" x 31.5" x 46.5"	40.5" x 36" x 46.5"	52.5" x 36" x 46.5"	52.5" x 36" x 46.5"
Voltage	115V/60/1	115V/60/1	115V/60/1	115V/60/1
Amperage (AMP)	2.3	2.3	3	3
HACR Breaker (AMP)	15	15	15	15
Energy Consumption (kWh / day) NSF	2.54	1.82	2.83	2.83
Heat Rejection (BTU / hr)	361	258	403	403
Voltage Range	104 - 126	104 - 126	104 - 126	104 - 126
Ambient Temp. Range	45° - 100°F	45° - 100°F	45° - 100°F	45° - 100°F
Temperature Range	32° - 52°F	32° - 52°F	32° - 52°F	32° - 52°F
Refrigerant	R290	R290	R290	R290

PREP TABLES | MEGA TOPS

Solid Doors

36" WORK HEIGHT W/ 6" CASTERS



- Stainless steel interior and exterior front, sides and top
- Cabinet and doors are insulated with 2" foamed-in-place polyurethane
- Provided with full complement of polycarbonate plastic 1/6th size pans
- 1/2" x 10" Cutting board with extended top for greater stability
- Engineered to maintain NSF-7 temperatures in 100°F ambient
- 6" Stem casters standard

Model Number	SR60B-12M	SR60B-18M	SR60B-24M	SR72B-18M	SR72B-24M	SR72B-30M
Interior Storage Capacity (AHAM)	14.8 ft ³	14.8 ft ³	14.8 ft ³	18 ft ³	18 ft ³	18 ft ³
Overall Dimensions (W x D x H including 6" casters)	60" x 34" x 44.25"	60" x 34" x 44.25"	60" x 34" x 44.25"	72" x 34" x 44.25"	72" x 34" x 44.25"	72" x 34" x 44.25"
Depth With Cutting Board Installed	36.5"	36.5"	36.5"	36.5"	36.5"	36.5"
Depth With Doors Open At 90°	58.5"	58.5"	58.5"	52.5"	52.5"	52.5"
Interior Door Opening Width	25.5"	25.5"	25.5"	19.5"	19.5"	19.5"
Interior Door Opening Height	23"	23"	23"	23"	23"	23"
Adjustable Shelves	2	2	2	2	2	2
Shelf Dimensions (W x D)	27.25" x 16"	27.25" x 16"	27.25" x 16"	22" x 16"	22" x 16"	22" x 16"
Pan Capacity (# of 1/6 size x 4" deep)	12	18	24	18	24	30
Crated Shipping Weight	346 lbs.	368 lbs.	383 lbs.	418 lbs.	435 lbs.	449 lbs.
Crated Shipping Dimensions (L x W x H)	61.75" x 36" x 46"	61.75" x 36" x 46"	61.75" x 36" x 46"	73.75" x 36" x 4.5"	73.75" x 36" x 46"	73.75" x 36" x 46"
Voltage	115V/60/1	115V/60/1	115V/60/1	115V/60/1	115V/60/1	115V/60/1
Amperage (AMP)	4	4	4	4	4	4
HACR Breaker (AMP)	15	15	15	15	15	15
Energy Consumption (kWh / day) NSF	4.05	4.05	4.05	4.77	4.77	4.77
Heat Rejection (BTU / hr)	575	575	575	719	719	719
Voltage Range	104 - 126	104 - 126	104 - 126	104 - 126	104 - 126	104 - 126
Ambient Temp. Range	45° - 100°F	45° - 100°F	45° - 100°F	45° - 100°F	45° - 100°F	45° - 100°F
Temperature Range	32° - 52°F	32° - 52°F	32° - 52°F	32° - 52°F	32° - 52°F	32° - 52°F
Refrigerant	R290	R290	R290	R290	R290	R290



PREP TABLES | MEGA TOPS

Drawer/Door Combinations

36" WORK HEIGHT W/ 6" CASTERS



- Stainless steel interior and exterior front sides and top
- Cabinet and drawers are insulated with 2" foamed-in-place polyurethane
- Engineered to maintain NSF-7 temperatures in 100°F ambient
- Provided with full complement of polycarbonate plastic 1/6th size pans 4" deep
- Door/Drawer configuration can be located in any cabinet section
- Field reversible doors

Model Number	SR48B-18MD2	SR60B-24MD2	SR72B-30MD2	SR72B-30MD4
Interior Storage Capacity (AHAM)	12 ft ³	14.8 ft ³	18 ft ³	18 ft ³
Overall Dimensions (W x D x H including 6" casters)	48" x 34" x 44.25"	60" x 34" x 44.25"	72" x 34" x 44.25"	72" x 34" x 44.25"
Depth with Cutting Board installed	36.5"	36.5"	36.5"	36.5"
Depth with Door Open at 90°	52"	58.5"	52.5"	52.5"
Depth With Drawer Fully Open	52.5"	52"	52"	52"
Shelves (#) / Dimensions (WxD)	(2) / 21.25" x 16"	(1) / 27.25" x 16"	(2) / 22" x 16"	(1) / 22" x 16"
Drawer Pan Capacity (pans by others)	(1) 1/2 and (1) 1/3 size pan per drawer, 6" deep	(1) full size pan 6" deep	(1) 1/2 and (1) 1/3 size pan per drawer, 6" deep	(1) 1/2 and (1) 1/3 size pan per drawer, 6" deep
Pan Capacity (# of 1/6 size x 4" deep)	18 (6" max. pan depth)	24 (6" max. pan depth)	30 (6" max. pan depth)	30 (6" max. pan depth)
Crated Shipping Weight	355 lbs.	420 lbs.	475 lbs.	510 lbs.
Crated Shipping Dimensions (L x W x H)	52.5" x 36" x 46.5"	62.5" x 36" x 46.5"	73.75" x 36" x 46.5"	73.75" x 36" x 46.5"
Voltage	115V/60/1	115V/60/1	115V/60/1	115V/60/1
Amperage (AMP)	3	4	4	4
HACR Breaker (AMP)	15	15	15	15
Energy Consumption (kWh / day) NSF	2.83	4.05	5.05	5.05
Heat Rejection (BTU / hr)	403	575	719	719
Voltage Range	104 - 126	104 - 126	104 - 126	104 - 126
Ambient Temp. Range	45° - 100°F	45° - 100°F	45° - 100°F	45° - 100°F
Temperature Range	32° - 52°F	32° - 52°F	32° - 52°F	32° - 52°F
Refrigerant	R290	R290	R290	R290

PREP TABLES | MEGA TOPS

Drawers

36" WORK HEIGHT W/ 6" CASTERS



- Stainless steel interior and exterior front, sides and top
- Cabinet and drawers are insulated with 2" foamed-in-place polyurethane
- Provided with full complement of polycarbonate plastic 1/6th size pans 4" deep
- 1/2" x 10" Cutting board with extended top for greater stability
- Engineered to maintain NSF-7 temperatures in 100°F ambient
- 6" Stem casters standard

Model Number	SR27B-12MD2	SR48B-18MD4	SR60B-24MD4	SR72B-30MD6
Interior Storage Capacity (AHAM)	6.22 ft ³	12 ft ³	14.8 ft ³	18 ft ³
Overall Dimensions (W x D x H including 6" casters)	27" x 34" x 44.25"	48" x 34" x 44.25"	60" x 34" x 44.25"	72" x 34" x 44.25"
Depth With Cutting Board Installed	36.5"	36.5"	36.5"	36.5"
Depth With Drawer Fully Open	52"	52"	52"	52"
Drawer Pan Capacity (pans by others)	(1) 12" x 20" x 6" deep pan per drawer	(1) 1/2 and (1) 1/3 size pan per drawer, 6" deep	(1) 12" x 20" x 6" deep pan per drawer	(1) 1/2 and (1) 1/3 size pan per drawer, 6" deep
Pan Capacity (# of 1/6 size x 4" deep)	12 (6" max. pan depth)	18 (6" max. pan depth)	24 (6" max. pan depth)	30 (6" max. pan depth)
Crated Shipping Weight	254 lbs.	382 lbs.	457 lbs.	539 lbs.
Crated Shipping Dimensions (L x W x H)	36" x 31.5" x 46.5"	52.5" x 36" x 46.5"	62.5" x 36" x 46.5"	73.75" x 36" x 46.5"
Voltage	115V/60/1	115V/60/1	115V/60/1	115V/60/1
Amperage (AMP)	2.3	3	4	4
HACR Breaker (AMP)	15	15	15	15
Energy Consumption (kWh / day) NSF	2.54	2.83	4.05	5.05
Heat Rejection (BTU / hr)	361	403	575	719
Voltage Range	104 - 126	104 - 126	104 - 126	104 - 126
Ambient Temp. Range	45° -100°F	45° -100°F	45° -100°F	45° -100°F
Temperature Range	32° - 52°F	32° - 52°F	32° - 52°F	32° - 52°F
Refrigerant	R290	R290	R290	R290





STEELHEART® FLAT LID PREP TABLES


FLEXIBILITY ON ALL SIDES.



Steelheart® Flat Lid Prep Tables are an excellent choice for providing ingredient access in flexible workspaces, especially in operations where ingredients need to be accessed from both sides.

Just like standard pivot-top prep tables, Hoshizaki's exclusive design distributes cold air through a system of louvered ducts positioned throughout the cabinet. Constant air movement circulates top to bottom and at each individual shelf to surround food with uniform cool temperatures.

Available in Sandwich Prep and Mega Top Sizes.



Scan to View Drawer and Pan Configuration Guides



PREP TABLES | FLAT LIDS REFRIGERATORS

SANDWICH TOPS

	Description	# of Lids	Dimensions (W x D x H)	Crated Dimensions (L x D x H)
SR27B-8FL	27" one-section with one door	1	27" x 30" x 36.5"	32" x 31.5" x 37"
SR27B-8D2FL	27" one-section with two drawers	1	27" x 30" x 36.5"	32" x 31.5" x 37"
SR36B-10FL	36" one-section with one door	1	36" x 30" x 36.5"	40.5" x 32" x 37"
SR48B-8FL	48" two-section with two doors	1	48" x 30" x 36.5"	52.5" x 30" x 37"
SR48B-12FL	48" two-section with two doors	1	48" x 30" x 36.5"	52.5" x 30" x 37"
SR48B-12D2FL	48" two-section with one door, two drawers	1	48" x 30" x 36.5"	52.5" x 30" x 37"
SR48B-12D4FL	48" two-section with four drawers	1	48" x 30" x 36.5"	52.5" x 30" x 37"
SR60B-8FL	60" two-section with two doors	1	60" x 30" x 36.5"	61.75" x 32" x 37"
SR60B-12FL	60" two-section with two doors	1	60" x 30" x 36.5"	61.75" x 32" x 37"
SR60B-16FL	60" two-section with two doors	1	60" x 30" x 36.5"	61.75" x 32" x 37"
SR72B-12FL	72" three-section with three doors	1	72" x 30" x 36.5"	73.75" x 32" x 37"
SR72B-16FL	72" three-section with three doors	1	72" x 30" x 36.5"	73.75" x 32" x 37"
SR72B-18FL	72" three-section with three doors	1	72" x 30" x 36.5"	73.75" x 32" x 37"

36.5" height to work surface/
installed with casters

37" height to work surface/
installed with casters

MEGA TOPS

	Description	# of Lids	Dimensions (W x D x H)	Crated Dimensions (L x D x H)
SR27B-12MFL	7" one-section with one door	1	27" x 34" x 36.5"	36" x 31.5" x 37"
SR27B-12MD2FL	27" one-section with two drawers	1	27" x 34" x 36.5"	36" x 31.5" x 37"
SR36B-15MFL	36" one-section with one door	1	36" x 34" x 36.5"	40.5" x 36" x 37"
SR48B-12MFL	48" two-section with two doors	1	48" x 34" x 36.5"	52.5" x 36" x 37"
SR48B-18MFL	48" two-section with two doors	1	48" x 34" x 36.5"	52.5" x 36" x 37"
SR48B-18MD2FL	48" two-section with one door, two drawers	1	48" x 34" x 36.5"	52.5" x 36" x 37"
SR48B-18MD4FL	48" two-section with four drawers	1	48" x 34" x 36.5"	52.5" x 36" x 37"
SR60B-12MFL	60" two-section with two doors	1	60" x 34" x 36.5"	61.75" x 36" x 37"
SR60B-18MFL	60" two-section with two doors	1	60" x 34" x 36.5"	61.75" x 36" x 37"
SR60B-24MFL	60" two-section with two doors	2	60" x 34" x 36.5"	61.75" x 36" x 37"
SR60B-24MD2FL	60" two-section with one door, two drawers	2	60" x 34" x 36.5"	61.75" x 36" x 37"
SR60B-24MD4FL	60" two-section with four doors	2	60" x 34" x 36.5"	61.75" x 36" x 37"
SR72B-18MFL	72" three-section with three doors	1	72" x 34" x 36.5"	73.75" x 36" x 37"
SR72B-24MFL	72" three-section with three doors	2	72" x 34" x 36.5"	73.75" x 36" x 37"
SR72B-30MFL	72" three-section with three doors	2	72" x 34" x 36.5"	73.75" x 36" x 37"
SR72B-30MD2FL	72" three-section with two doors, two drawers	2	72" x 34" x 36.5"	73.75" x 36" x 37"
SR72B-30MD4FL	72" three-section with one door, four drawers	2	72" x 34" x 36.5"	73.75" x 36" x 37"
SR72B-30MD6FL	72" three-section with six drawers	2	72" x 34" x 36.5"	73.75" x 36" x 37"

36.5" height to work surface/
installed with casters

37" height to work surface/
installed with casters



FEATURES ONLY ON

STEELHEART® PIZZA PREP TABLES



HOSHIZAKI EXCLUSIVE Night/Day Mode

When the lid is open, the set point drops to keep food cool in the rail. When the lid is closed, the set point returns to normal so food can stay in the rail overnight without freezing.

Removable Air Filter

Easily wash the filter of flour and debris, ensuring consistent operation.

Independent Temperature Controls

Set different temperatures for the rail and cabinet operation's needs.



Optimal Airflow in Rail

Hoshizaki's exclusive Back-To-Front Airflow surrounds each pan for consistent cooling.



Scan to View
Pizza Pan
Configuration
Guides



PREP TABLES | PIZZA

With Doors

36" WORK HEIGHT W/ 6" CASTERS



PR46B



PR60B



PR67B



PR93B

- Stainless steel interior and exterior front, sides and top
- Adjustable ducted air distribution for rail/cabinet
- Solid state digital controller with temperature alarms and LED display (Fahrenheit or Celsius)
- Full complement of 1/3rd size pans are standard
- Engineered to maintain NSF-7 temperatures in 100°F ambient
- 1/2" x 19" Cutting board standard
- Night/Day Mode- when lid is open set point drops to keep food cool in rail; when lid is closed set point returns to normal so food can stay in rail overnight without freezing

Model Number	PR46B	PR60B	PR67B	PR93B
Interior Storage Capacity (AHAM)	11.23 ft³	16.63 ft³	19.29 ft³	29.3 ft³
Overall Dimensions (W x D x H including 6" casters)	46" x 33.25" x 43.25"	60" x 33.25" x 43.25"	67" x 32.25" x 43.25"	93" x 33.25" x 43.25"
Depth with Cutting Board installed	36.25"	36.25"	36.25"	35.25"
Depth with Doors Open at 90°	59.5"	53.75"	56.75"	56.75"
Interior Door Opening Width	25.5"	19.5"	22.5"	22.5"
Interior Door Opening Height	23"	23"	23"	23"
Adjustable Shelves	2	4	4	6
Shelf Dimensions (W X D)	28.75" x 25.5"	21.5" x 25.5"	24.75" x 25.5"	24.75" x 25.5"
Pan Capacity (# of 1/3 size x 4" deep)	6 (6" max. pan depth)	8 (6" max. pan depth)	9 (6" max. pan depth)	12 (6" max. pan depth)
Crated Shipping Weight	336 lbs.	410 lbs.	439 lbs.	578 lbs.
Crated Shipping Dimensions (L x W x H)	48.75" x 34.75" x 45"	63.75" x 35.75" x 45"	70.75" x 35.75" x 45"	96.75" x 35.75" x 45"
Voltage	115V/60/1	115V/60/1	115V/60/1	115V/60/1
Amperage (AMP)	6	4	6	6
HACR Breaker (AMP)	15	15	15	15
Energy Consumption (kWh / day) NSF	5.69	5.63	6.26	7.31
Heat Rejection (BTU / hr)	808	801	890	1039
Voltage Range	104 - 126	104 - 126	104 - 126	104 - 126
Ambient Temp. Range	45° -100°F	45° -100°F	45° -100°F	45° -100°F
Control Set Point Range	16° to 36°F (rail) / 28° to 40°F (cabin)	16° to 36°F (rail) / 28° to 40°F (cabin)	16° to 36°F (rail) / 28° to 40°F (cabin)	16° to 36°F (rail) / 28° to 40°F (cabin)
Refrigerant	R290	R290	R290	R290



Intertek

Intertek

PREP TABLES | PIZZA

Drawer/Door Combinations

36" WORK HEIGHT W/ 6" CASTERS



PR60B-D2



PR67B-D2



PR93B-D2



PR93B-D4

- Stainless steel interior and exterior front sides and top
- Cabinet and drawers are insulated with 2" foamed-in-place polyurethane
- Provided with full complement of polycarbonate plastic 1/3rd size pans 4" deep
- Door/Drawer configuration can be located in any cabinet section
- Enamel coated evaporator coil
- Engineered to maintain NSF-7 temperatures in 100°F ambient
- Night/Day Mode- when lid is open set point drops to keep food cool in rail; when lid is closed set point returns to normal so food can stay in rail overnight without freezing

Model Number	PR60B-D2	PR67B-D2	PR93B-D2	PR93B-D4
Interior Storage Capacity (AHAM)	16.63 ft³	19.29 ft³	29.3 ft³	29.3 ft³
Overall Dimensions (W x D x H including 6" casters)	60" x 33.25" x 43.25"	67" x 33.25" x 43.25"	67" x 33.25" x 43.25"	67" x 33.25" x 43.25"
Depth with Cutting Board installed	36.25"	36.25"	36.25"	36.25"
Depth with Door Open at 90°	54.75"	57.75"	56.75"	56.75"
Depth with Drawer Fully Open	(2) 12" x 20" x 6" deep pans	57.5"	56.5"	56.5"
Door Opening Width	19.5"	22.5"	22.5"	22.5"
Door Opening Height	23"	23"	23"	23"
Shelves (#) / Dimensions (WxD)	(2) / 21.5" x 25.5"	(2) / 24.75" x 25.5"	(4) / 24.75" x 25.5"	(4) / 24.75" x 25.5"
Drawer Pan Capacity (pans by others)	(2) 12" x 20" x 6" deep pans	(2) 12" x 20" x 6" deep pans	(2) 12" x 20" x 6" deep pans	(2) 12" x 20" x 6" deep pans
Pan Capacity (# of 1/3 size x 4" deep)	8	9	12	12
Crated Shipping Weight	430 lbs.	486 lbs.	620 lbs.	675 lbs.
Crated Shipping Dimensions (L x W x H)	63.75" x 35.75" x 45"	70.75" x 35.75" x 45"	96.75" x 35.75" x 45"	96.75" x 35.75" x 45"
Voltage	115V/60/1	115V/60/1	115V/60/1	115V/60/1
Amperage (AMP)	4	6	6	6
HACR Breaker (AMP)	15	15	15	15
Energy Consumption (kWh / day) NSF	5.63	6.26	7.31	7.31
Heat Rejection (BTU / hr)	801	890	1039	1039
Voltage Range	104 - 126	104 - 126	104 - 126	104 - 126
Ambient Temp. Range	45° -100°F	45° -100°F	45° -100°F	45° -100°F
Temperature Range	16° to 36°F (rail) / 28° to 40°F (cabin)	16° - 36°F (rail) / 28° to 40°F (cabin)	16° to 36°F (rail) / 28° to 40°F (cabin)	16° to 36°F (rail) / 28° to 40°F (cabin)
Refrigerant	R290	R290	R290	R290

PREP TABLES | PIZZA

Drawers

36" WORK HEIGHT W/ 6" CASTERS



PR46B-D2



PR60B-D4



PR67B-D4



PR93B-D6

- Stainless steel interior and exterior front, sides and top
- Solid state digital controller with temperature alarms and LED display (Fahrenheit or Celsius)
- Cabinet and drawers are insulated with 2" of CFC free, foamed-in-place polyurethane
- Provided with full complement of polycarbonate plastic 1/3rd size pans 4" deep
- 1/2" x 19" Cutting board standard
- Engineered to maintain NSF-7 temperatures in 100°F ambient
- Night/Day Mode- when lid is open set point drops to keep food cool in rail; when lid is closed set point returns to normal so food can stay in rail overnight without freezing

Model Number	PR46B-D2	PR60B-D4	PR67B-D4	PR93B-D6
Interior Storage Capacity (AHAM)	11.23 ft³	16.63 ft³	19.29 ft³	29.34 ft³
Overall Dimensions (W x D x H including casters)	46" x 32.25" x 43.25"	60" x 33.25" x 43.25"	67" x 33.25" x 43.25"	93" x 33.25" x 43.25"
Depth with Cutting Board installed	35.25"	35.25"	36.25"	36.25"
Depth with Drawer Fully Open	56.5"	56.5"	57.5"	57.5"
Drawer Pan Capacity (pans by others)	(2) 12" x 20" x 6" deep pans	(2) 12" x 20" x 6" deep pans	(2) 12" x 20" x 6" deep pans	(2) 12" x 20" x 6" deep pans
Pan Capacity (# of 1/3 size x 4" deep)	6	8	9	12
Crated Shipping Weight	383 lbs.	450 lbs.	531 lbs.	711 lbs.
Crated Shipping Dimensions (L x W x H)	48.75" x 34.75" x 45"	63.75" x 35.75" x 45"	70.75" x 35.75" x 45"	95.75" x 35.75" x 45"
Voltage	115V/60/1	115V/60/1	115V/60/1	115V/60/1
Amperage (AMP)	4	4	6	6
HACR Breaker (AMP)	15	15	15	15
Energy Consumption (kWh / day) NSF	5.69	5.63	6.26	7.31
Heat Rejection (BTU / hr)	808	801	890	1039
Voltage Range	104 - 126	104 - 126	104 - 126	104 - 126
Ambient Temp. Range	45° -100°F	45° -100°F	45° -100°F	45° -100°F
Control Set Point Range	16° to 36°F (rail) / 28° to 40°F (cabin)	16° to 36°F (rail) / 28° to 40°F (cabin)	16° - 36°F (rail) / 28° to 40°F (cabin)	16° - 36°F (rail) / 28° to 40°F (cabin)
Refrigerant	R290	R290	R290	R290





STEELHEART® CHEF BASE

STAY COOL BELOW, WHEN IT'S **HOT ON TOP**



- Hoshizaki's integrated ceramic heat shield assures stored food products are cool and safe during blazing hot cooking!
- Heavy duty 16-gauge stainless steel top surface.
- 90° side edges maximize top surface area and stability for cooking equipment. Marine edges on both front and back allow for easy cleaning.

CHEF BASE | FREEZERS Drawers

Scan to View
All Chef Bases



NEW!

MODEL	DESCRIPTION	DIMENSIONS (W x D x H)
CF36B (-L)	One-section with 2 drawers	36.5" x 32.25" x 26"
CF49B (-L)	One-section with 2 drawers	49" x 32.25" x 26"
CF60B (-L)	One-section with 2 drawers	60.5" x 32.25" x 26"
CF72B (-L)	Two-section with 4 drawers	72.5" x 33.25" x 26"

-L models place condenser on left side of cabinet.

CHEF BASE | REFRIGERATORS

Drawers



- Stainless steel interior and exterior front, sides and top
- 16 gauge stainless steel top with marine edge front and rear and 1" turn-up at each end
- Solid state digital controller with temperature alarms and LED display (Fahrenheit or Celsius)
- Top is provided with an exclusive, built in, ceramic heat shield
- Standard with (4-8) 4" casters all with brakes
- Electronic controls

Model Number	CR36A	CR49A	CR60A	CR72A	CR85A	CR98A	CR110A
Interior Storage Capacity (AHAM)	6.12 ft ³	9.52 ft ³	9.52 ft ³	15.44 ft ³	18.95 ft ³	22.2 ft ³	22.2 ft ³
Overall Dimensions (W x D x H including 4" casters)	36.5" x 32.25" x 27"	49" x 32.25" x 27"	60.5" x 32.25" x 27"	72.52" x 32.25" x 27"	85" x 32.25" x 27"	98" x 32.25" x 27"	110.5" x 32.25" x 27"
Depth with Drawer Fully Open	55.75"	55.75"	55.75"	55.75"	55.75"	55.75"	55.75"
Maximum Pan Depth	6"	6"	6"	6"	6"	6"	6"
Worktop Maximum Load Capacity	1000 lbs	1000 lbs	1000 lbs	1500 lbs	1500 lbs	2000 lbs	2000 lbs
Drawer Pan Capacity (pans by others)	(1) 12" x 20" x 6" deep pans and (1) 1/2 long pan 6" deep (pans by others)	(2) 12" x 20" x 6" deep pans	(2) 12" x 20" x 6" deep pans	(2) 12" x 20" x 6" deep pans	Left drawers: (3) 12" x 20" x 6" deep pans Right drawers: (2) 12" x 20" x 6" deep pans	(3) 12" x 20" x 6" deep pans	(3) 12" x 20" x 6" deep pans
Pan Capacity (12" x 20")	2	2.5	2.5	8	10	12	12
Crated Shipping Weight	295 lbs.	327 lbs.	369 lbs.	500 lbs.	567 lbs.	639 lbs.	671 lbs.
Crated Shipping Dimensions (L x W x H)	38" x 34.5" x 30.5"	51" x 35.5" x 30.5"	62" x 35.5" x 30.5"	74" x 34.5" x 30.5"	87.25" x 34.5" x 30.5"	100" x 34.5" x 30.5"	112.5" x 34.5" x 30.5"
Voltage	115V/60/1	115V/60/1	115V/60/1	115V/60/1	115V/60/1	115V/60/1	115V/60/1
Amperage (AMP)	2.2	2.7	2.7	3.0	3.0	3.0	3.0
HACR Breaker (AMP)	15	15	15	15	15	15	15
Energy Consumption (kWh / day) NSF	1.6	2.1	2.1	2.78	2.9	3.69	3.69
Heat Rejection (BTU / hr) @ NSF	223	303	303	395	415	525	525
Voltage Range	104 - 126	104 - 126	104 - 126	104 - 126	104 - 126	104 - 126	104 - 126
Ambient Temp. Range	45° - 100°F	45° - 100°F	45° - 100°F	45° - 100°F	45° - 100°F	45° - 100°F	45° - 100°F
Control Set Point Range	32° - 52°F	32° - 52°F	32° - 52°F	32° - 52°F	32° - 52°F	32° - 52°F	32° - 52°F
Refrigerant	R290	R290	R290	R290	R290	R290	R290



NEW

VALIANCE[®]

by  **HOSHIZAKI**

RELIABLE. PRACTICAL. SMART-VALUE.

ENGINEERED FOR EVERYDAY DEMANDS.

Valiance[™] by Hoshizaki is designed for operators who want reliable, quality refrigeration that delivers exceptional value. With Valiance[™], you get a product that stands toe-to-toe with leading competitors-giving you the confidence to run your operation smoothly and efficiently, without overextending your budget.

Choose Valiance[™] when you want proven performance and peace of mind at a price that makes sense for your business growth.

- Environmentally friendly R290 hydrocarbon refrigerant
- Field reversible stay-open doors - no kit needed
- Uprights accommodate full size tray pans.



More models coming soon. Scan to see current offerings



Refrigerators and Freezers



VR1A-FS ★ / VF1A-FS ★



VR2A-FS ★ / VF2A-FS ★

Model Number	VR1A-FS ★	VF1A-FS ★	VR2A-FS ★	VF2A-FS ★
Interior Storage Capacity (AHAM)	19.07 ft³	19.07 ft³	42.45 ft³	42.45 ft³
Overall Dimensions (W x D x H including 4" casters)	26.88" x 32.00" x 81.70"	26.88" x 32.00" x 81.70"	54.31" x 32.00" x 81.70"	54.31" x 32.00" x 81.70"
Depth with Doors Open at 90°	57.87"	57.87"	57.5"	57.5"
Interior Door Opening Width	22.25"	22.25"	22.63"	22.63"
Interior Door Opening Height	52.31"	52.31"	52.31"	52.31"
Adjustable Shelves	3	3	6	6
Shelf Dimensions (W x D)	21.56" x 24.88"	21.65" x 24.88"	23.94" x 25.16"	23.94" x 25.16"
Crated Shipping Weight	286 lbs.	310 lbs.	471 lbs.	543 lbs.
Crated Shipping Dimensions (L x W x H)	33.50" x 28.75" x 83.88"	33.50" x 28.75" x 83.88"	58" x 33.5" x 83.88"	58" x 33.5" x 83.88"
Voltage	115V/60/1	115V/60/1	115V/60/1	115V/60/1
Amperage (AMP)	2.1	4.1	3.5	4.6
HACR Breaker (AMP)	15	15	15	15
Energy Consumption (kWh / day) ASHRAE	0.96	3.89	1.48	6.94
Approx. Nominal Compres. BTU/HR (HP)	1461	1115	2322(1/2)	1718(1/2HP)
Voltage Range	103 - 127	103 - 127	103 - 127	103 - 127
Ambient Temp. Range	45° to 100°F	45° to 100°F	45° to 100°F	45° to 100°F
Control Set Point Range	36° to 42°F	-4° to 4°F	36° to 42°F	-4° to 4°F
Refrigerant	R290	R290	R290	R290



VALIANCE™ | UNDERCOUNTERS

Refrigerators and Freezers



VUR27A ★ / VUF27A ★



VUR48A ★ / VUF48A ★

Model Number	VUR27A ★	VUF27A ★	VUR48A ★	VUF48A ★
Interior Storage Capacity (AHAM)	6.33 ft³	6.33 ft³	12.09 ft³	12.09 ft³
Overall Dimensions (W x D x H including 4" casters)	27" x 30" x 33.75"	27" x 30" x 33.75"	47.75" x 30" x 33.75"	47.75" x 30" x 33.75"
Depth with Doors Open at 90°	54.50"	55.75"	51.50"	52.75"
Interior Door Opening Width	22.60"	22.60"	19.50"	19.50"
Interior Door Opening Height	22.75"	22.75"	22.75"	22.75"
Adjustable Shelves	1	1	2	2
Shelf Dimensions (W x D)	22" x 16"	22" x 16"	21.25" x 16"	21.25" x 16"
Crated Shipping Weight	200 lbs.	200 lbs.	290 lbs.	290 lbs.
Crated Shipping Dimensions (L x W x H)	33" x 29" x 37"	33" x 29" x 37"	52" x 33" x 37"	52" x 33" x 37"
Voltage	115V/60/1	115V/60/1	115V/60/1	115V/60/1
Amperage (AMP)	1.5	1.2	1.8	1.7
HACR Breaker (AMP)	15	15	15	15
Energy Consumption (kWh / day) ASHRAE	0.95	1.92	1.21	3.44
Approx. Nominal Compres. BTU/HR (HP)	1289(1/6)	993(1/5)	1709(1/6)	1468(1/3)
Voltage Range	115-127	115 - 127	115-127	115 - 127
Ambient Temp. Range	45° to 100°F	45° to 100°F	45° to 100°F	45° to 100°F
Control Set Point Range	33° to 39°F	-5 to 5°F	33° to 39°F	-5 to 5°F
Refrigerant	R290	R290	R290	R290

Refrigerators



VSR27A-8



VSR48A-12

Model Number	VSR27A-8	VSR48A-12
Interior Storage Capacity (AHAM)	6.33 ft³	12.09 ft³
Overall Dimensions (W x D x H including 4" casters)	26.75" x 30.13" x 40.69"	47.75" x 30.13" x 40.69"
Depth with Doors Open at 90°	54.76"	51.76"
Interior Door Opening Width	22.75"	19.75"
Interior Door Opening Height	22.88"	22.88"
Adjustable Shelves	1	2
Shelf Dimensions (W x D)	22" x 16"	21.25" x 16"
Crated Shipping Weight	200 lbs.	290 lbs.
Crated Shipping Dimensions (L x W x H)	34.5" x 29.13" x 45.5"	52.13" x 34.5" x 45.5"
Voltage	115V/60/1	115V/60/1
Amperage (AMP)	2.1	3.3
HACR Breaker (AMP)	15	15
Energy Consumption (kWh / day) ASHRAE	1.89	2.16
Approx. Nominal Compres. BTU/HR (HP)	1461(1/6)	2130(1/6)
Voltage Range	103 - 127	103 - 127
Ambient Temp. Range	45° to 100°F	45° to 100°F
Control Set Point Range	32.5° to 36.5°F	32.5° to 36.5°F
Refrigerant	R290	R290



GRAB & GO MADE EASY

MERCHANDISERS FOR DRINKS ON DEMAND

Hoshizaki's energy-efficient glass door merchandiser refrigerators and freezers showcase your products with maximum visibility and reliable cooling. They keep beverages, snacks, and perishable items at ideal temperatures. Available in silver, black, or white to complement any space, these merchandisers are perfect for retail, food service, offices, and more.



GLASS DOOR MERCHANDISER

FREEZER

- ▶ Silver painted galvanized steel exterior and interior with NSF approved white steel interior and stainless steel floor
- ▶ Forced air evaporator for quick temperature pull down
- ▶ Energy saving hot gas loop and an electric glass door heater

Model Number	FM-23-HC
Overall Dimensions (W x D x H) Including Levelling Feet	30" x 29.75" x 78"
Adjustable Shelves	5
Shelf Dimensions (W x D)	24.56" x 23.25"
Crated Shipping Weight	385 lbs.
Crated Shipping Dimensions (L x W x H)	33" x 32.5" x 85.25"
Voltage	115V/60/1
Amperage (AMP)	4.8
HACR Breaker (AMP)	15
Voltage Range	104 - 127
Ambient Temp. Range	60° - 86°F
Control Set Point Range	-10° to -0°F
Refrigerant	R290



GLASS DOOR MERCHANDISERS

Refrigerators

Choose from Black, White or Silver models



RM-7-HC

RM-10-HC ★

RM-26-HC ★

RM-45-SD-HC ★
(Sliding doors)

RM-49-HC ★

RM-65-HC

- Environmentally friendly R290 hydrocarbon refrigerant
- Doors mounted on heavy duty hinges with self-closing mechanism
- Forced air evaporator for quick temperature pull down
- Three year parts and labor warranty & Five year compressor warranty
- Large glass door(s) is energy efficient low-E multi pane glass
- Locks on doors are standard (accept for RM-7-HC)

Model Number	RM-7-HC	RM-10-HC ★	RM-26-HC ★	RM-45-SD-HC ★	RM-49-HC ★	RM-65-HC ★
Color Options	grey (as shown), black, white	grey (as shown), black, white	grey (as shown), black, white	grey (as shown), black, white	grey (as shown), black, white	grey (as shown), black, white
Interior Storage Capacity (AHAM)	7 ft³	10 ft³	26 ft³	38.26 ft³	49 ft³	56.04 ft³
Capacity	20 oz. bottles: 102 12 oz. cans: 217	20 oz. bottles: 168 12 oz. cans: 384	20 oz. bottles: 360 12 oz. cans: 900	20 oz. bottles: 560 12 oz. cans: 1260	20 oz. bottles: 630 12 oz. cans: 1440	20 oz. bottles: 830 12 oz. cans: 1926
Overall Dimensions (W x D x H Including Leveling Feet)	21" x 25.25" x 39"	25" x 22.5" x 54.75"	29.75" x 29.75" x 79.75"	51" x 29" x 79.5"	60" x 29.75" x 78"	78" x 29.75" x 78"
Adjustable Shelves	2 adjustable, 1 floor shelf	3	5	5 per section	5 per section	5 per section
Shelf Dimensions (W x D)	17.75" x 20.75" 18" x 9.25" (Floor)	21" x 17.5"	25.75" x 24"	23" x 20.5"	27" x 21.75"	(C) 27.3" x 21.7" (L/R) 22.4" x 21.7"
Crated Shipping Weight	180 lbs.	230 lbs.	331 lbs.	520 lbs.	610 lbs.	800 lbs.
Crated Shipping Dimensions (L x W x H)	28" x 24.5" x 44"	30" x 28" x 60"	34" x 34" x 82"	54" x 32.25" x 84"	63" x 32.25" x 86"	81" x 32.25" x 84"
Voltage	115V/60/1	115V/60/1	115V/60/1	115V/60/1	115V/60/1	115V/60/1
Amperage (AMP)	3.2	1.8	3.5	6.5	7.6	8.2
HACR Breaker (AMP)	15	15	15	15	15	15
Energy Consumption (kWh / day) ENERGY STAR / DOE	1.38	1.1	1.81	4.55	4.37	5.67
Approx. Nominal Compress BTU/HR (HP)	1/8HP	1/5HP	1/3HP	1/2HP	1/2HP	(L) 1/3HP (R) 1/3HP
Voltage Range	104 - 126	104 - 126	104 - 126	104 - 126	104 - 126	104 - 126
Ambient Temp. Range	60° - 86°F	60° - 86°F	60° - 86°F	60° - 86°F	60° - 86°F	60° - 86°F
Factory Set Point Range	35° - 44°F	35° - 43°F	35° - 44°F	38° - 47°F	35° - 44°F	35° - 43.5°F
Refrigerant	R290	R290	R290	R290	R290	R290



UNDERCOUNTER | COMPACT REFRIGERATORS

Solid or Glass Doors



HR15A ★



HR15A-G



HR24C ★



HR24C-G

- Stainless steel interior and exterior
- UL approval for outdoor use
- ADA Compliant 
- Lockable stainless steel door is field reversible

- Ducted air flow for even air distribution throughout cabinet
- Interior LED lighting
- Optional wine shelves

Model Number	HR15A ★	HR15A-G	HR24C ★	HR24C-G
Interior Storage Capacity (AHAM)	2.54 ft³	2.54 ft³	3.87 ft³	3.87 ft³
Overall Dimensions (W x D x H including legs)	14.8" x 25.75" x 31.5"	14.8" x 25.75" x 31.5"	23.4" x 26.5" x 31.5"	23.4" x 26.5" x 31.5"
Depth with Doors Open at 90°	37.25"	37.25"	46.7"	46.7"
Adjustable Shelves	2	2	3	3
Shelves (#) / Dimensions(W x D)	(2) / 10" x 20" adjustable slide out shelf	(2) 10" x 20"	(1) / 18.5" x 17" (2) / 18.5" x 12"	(1) / 18.5" x 17" (2) / 18.5" x 12"
Crated Shipping Weight	115 lbs	115 lbs	115 lbs	115 lbs
Crated Shipping Dimensions (L x W x H)	30.6" x 18.75" x 37"	30.6" x 18.75" x 37"	26.8" x 24" x 36.6"	26.8" x 24" x 36.6"
Voltage	115V/60/1	115V/60/1	115V/60/1	115V/60/1
Amperage (AMP)	0.9	0.9	1.1	1.1
HACR Breaker (AMP)	15	15	15	15
Energy Consumption (kWh / day) ASHRAE	0.54	0.54	0.64	0.64
Heat Rejection (BTU / hr)*	145	145	648	648
Voltage Range	104 - 127	104-127	115 - 127	115 - 127
Ambient Temp. Range	45° - 90°F	45° - 90°F	45° - 100°F	45° - 100°F
Control Set Point Range	28° - 40°F	28° - 40°F	34° - 52°F	34° - 52°F
Refrigerant	R600a	R600a	R600a	R600a

*Based on 100°F ambient cycling at set point

SUSHI CASES | UPRIGHTS

FEATURES & BENEFITS OF HOSHIZAKI SUSHI CASES

- Energy efficient LED lights with on/off switch
- Elegant curved front glass design enhances product on display
- Condenser airflow comes in the back and out the side
- Large diameter 1" drain at front, vinyl hose included
- NSF approved thermometer
- Easy to clean ceiling
- Plate space on top of unit, 5.6 inches
- Larger front to back interior, 11 inches
- Interior floor has a radius at all four sides
- Self-contained refrigeration unit - easy to install
- Large diameter upper evaporator with tin plating
- Slightly taller doors with plastic seal at end, opposite of the handle
- Solid food plates with radius groove to fit sushi foods
- Energy-efficient and environmentally friendly R600a refrigerant



Model Number	Condenser	Refrigeration Unit Location (Front View)	Dimensions W x D x H	Shipping Dimensions W x D x H	Electrical	Shipping Weight
HNC-120BA-R-SLH	Air-Cooled	Right Side	47.2" x 13.6" x 11"	51.5" x 16.25" x 20.25"	115V/60/1	94 Lbs.
HNC-120BA-L-SLH	Air-Cooled	Left Side	47.2" x 13.6" x 11"	51.5" x 16.25" x 20.25"	115V/60/1	94 Lbs.
HNC-150BA-R-SLH	Air-Cooled	Right Side	59.1" x 13.6" x 11"	62.25" x 16.25" x 20.25"	115V/60/1	115 Lbs.
HNC-150BA-L-SLH	Air-Cooled	Left Side	59.1" x 13.6" x 11"	62.25" x 16.25" x 20.25"	115V/60/1	115 Lbs.
HNC-180BA-R-SLH	Air-Cooled	Right Side	70.9" x 13.6" x 11"	74" x 16.25" x 20.25"	115V/60/1	130 Lbs.
HNC-180BA-L-SLH	Air-Cooled	Left Side	70.9" x 13.6" x 11"	74" x 16.25" x 20.25"	115V/60/1	130 Lbs.
HNC-210BA-R-SLH	Air-Cooled	Right Side	82.7" x 13.6" x 11"	85.75" x 16.25" x 20.25"	115V/60/1	145 Lbs.
HNC-210BA-L-SLH	Air-Cooled	Left Side	82.7" x 13.6" x 11"	85.75" x 16.25" x 20.25"	115V/60/1	145 Lbs.


"R" - Condensing Unit is on RIGHT from front view

"L" - Condensing Unit is on LEFT from front view


Not intended for overnight storage. NSF Standard 7




HNC-120BA-L-SLH



HNC-210BA-L-SLH



HNC-150BA-L-SLH



HNC-180BA-L-SLH



READY AND ON TAP WHEN YOU ARE

Hoshizaki's **BACK BAR** REFRIGERATORS, BOTTLE COOLERS, and **DIRECT DRAW** REFRIGERATORS are built to keep beverages cold and service efficient. Zero clearance installation is ideal for tight spaces.



BACK BAR | REFRIGERATORS

Glass Doors



BB59-G



BB69-G



BB80-G-S



BB95-G

- Stainless steel interior with LED lights
- Heavy duty 18-gauge stainless steel top
- Maximum product storage capacity with the ability to store tall boys three high per section
- Black vinyl coated or stainless steel exterior front, sides, and rear
- Energy efficient Low-E Multi pane glass self-closing doors come standard with barrel locks
- Engineered to maintain NSF-7 temperatures in 100°F ambient

Model Number	BB59-G(-S*)	BB69-G(-S*)	BB80-G(-S*)	BB95-G(S*)
Cabinet Dimensions W x D x H	59.5" x 29" x 36.88"	69.5" x 29" x 36.88"	80" x 29" x 36.88"	95.5" x 29" x 36.88"
Door(s)	2	2	3	3
Shelves	4	4	6	6
Capacity (AHAM) cu ft	18.45 ft ³	21.80 ft ³	26.74 ft ³	32.53 ft ³
Capacity 12oz. cans	852	1014	1092	1302
Capacity 1/2 Barrels	3	3	4	5
HP	1/3	1/3	1/3	1/3
Voltage	115V/60/1	115V/60/1	115V/60/1	115V/60/1
Amperage (AMP)	2.5	2.5	2.5	2.5
NEMA Plug	8 ft. 5-15P	8 ft. 5-15P	8 ft. 5-15P	8 ft. 5-15P
Shipping Dimensions W x D x H	62.5" x 31.25" x 42.75"	72.5" x 31.25" x 42.75"	82.5" x 31.25" x 42.75"	98.5" x 31.25" x 42.75"
Shipping Weight	310 lbs. 330(-S*) lbs.	345 lbs. 395(-S*) lbs.	370 lbs. 430(-S*) lbs.	435 lbs. 490(-S*) lbs.
Refrigerant	R290	R290	R290	R290

*(-S) Stainless Steel Exterior option available - Made to order.

BACK BAR | REFRIGERATORS

Solid Doors



BB59



BB69



BB80-S



BB95

- Stainless steel interior with LED lights
- Heavy duty 18-gauge stainless steel top
- Maximum product storage capacity with the ability to store tall boys three high per section
- Black vinyl coated or stainless steel exterior front, sides, and rear
- Doors come with a stainless steel interior liner are self-closing and include locks
- Engineered to maintain NSF-7 temperatures in 100°F ambient

Model Number	BB59(-S*)	BB69(-S*)	BB80(-S*)	BB95(-S*)
Cabinet Dimensions W x D x H	59.5" x 29" x 36.88"	69.5" x 29" x 36.88"	80" x 29" x 36.88"	95.5" x 29" x 36.88"
Door(s)	2	2	3	3
Shelves	4	4	6	6
Capacity (AHAM) cu ft	18.16 ft ³	21.8 ft ³	28.74 ft ³	32.53 ft ³
Capacity 12oz. cans	852	1014	1092	1302
Capacity 1/2 Barrels	3	3	4	5
HP	1/3	1/3	1/3	1/3
Voltage	115V/60/1	115V/60/1	115V/60/1	115V/60/1
Amperage (AMP)	2.5	2.5	2.5	2.5
NEMA Plug	8 ft. 5-15P	8 ft. 5-15P	8 ft. 5-15P	8 ft. 5-15P
Shipping Dimensions W x D x H	62.5" x 31.25" x 42.75"	72.5" x 31.25" x 42.75"	82.5" x 31.25" x 42.75"	98.5" x 31.25" x 42.75"
Shipping Weight	315 lbs. 320(-S*) lbs.	350 lbs. 390(-S*) lbs.	375 lbs. 420(-S*) lbs.	450 lbs. 480(-S*) lbs.
Refrigerant	R290	R290	R290	R290

*(-S) Stainless Steel Exterior option available - Made to order.

SLIDE TOP | BOTTLE COOLERS

Slide Top



CC50



CC65



CC80-S



CC95







- Stainless steel interior
- Heavy duty 18-gauge stainless steel top
- Front breathing, side mount refrigeration is easily accessible for cleaning and service
- Black vinyl coated or stainless steel exterior front, sides, and rear
- Durable stainless steel slide top lids including locks
- Engineered to maintain NSF-7 temperatures in 100°F ambient

Model Number	CC50(-S*)	CC65(-S*)	CC80(-S*)	CC95(-S*)
Cabinet Dimensions† W x D x H	50.5" x 31.25" x 39"	65.5" x 26.5" x 33.38"	80" x 26.5" x 33.38"	95" x 26.5" x 33.38"
Lids	2	2	3	3
Bin Dividers	3	4	6	7
Capacity (AHAM) cu ft	14.4 ft³	19.6 ft³	24.67 ft³	27.98 ft³
Capacity 12oz. / 20oz. Cans	704 / 286	890 / 360	1150 / 547	1408 / 672
HP	1/4	1/3	1/3	1/2
Voltage	115V/60/1	115V/60/1	115V/60/1	115V/60/1
Amperage (AMP)	2.0	2.0	2.0	2.0
NEMA Plug	8 ft. 5-15P	8 ft. 5-15P	8 ft. 5-15P	8 ft. 5-15P
Shipping Dimensions W x D x H	53.5" x 31.25" x 39"	68.5" x 31.25" x 39"	82.5" x 31.25" x 39"	98.5" x 31.25" x 39"
Shipping Weight	235 lbs.	275 lbs.	315 lbs.	355 lbs.
Refrigerant	R290	R290	R290	R290

*(-S) Stainless Steel Exterior option available - Made to order.

† Does not include 1" rear cabinet bumper or bottle cap catcher depth

BACK BAR REFRIGERATION KEG FOOTPRINTS



DIRECT DRAW | REFRIGERATORS



- Included: Polished stainless-steel insulated towers with plated brass faucet
- Black vinyl coated or stainless steel exterior front, sides, and rear
- Heavy duty 18-gauge stainless steel top
- Stainless steel threshold protects door frame from damage when loading and unloading
- Stainless steel interior

Model Number	DD24(-S*)	DD59(-S*)	DD69(-S*)	DD80(-S*)	DD95(-S*)
Cabinet Dimensions W x D x H	24.88" x 30" x 39.38"	59.5" x 29" x 36.88"	69.5" x 29" x 36.88"	80" x 29" x 36.88"	95.5" x 29" x 36.88"
Door(s)	1	2	2	3	3
Included Tower(s)	1	2	2	2	2
Tap(s)	1	3	3	4	4
Capacity (AHAM) cu ft	7.46 ft ³	18.45 ft ³	21.8 ft ³	28.74 ft ³	32.53 ft ³
Capacity 1/2 Barrels	1	2**	3	4	5
HP	1/6	1/3	1/3	1/3	1/3
Voltage	115V/60/1	115V/60/1	115V/60/1	115V/60/1	115V/60/1
Amperage (AMP)	1.5	2.5	2.5	2.5	2.5
NEMA Plug	5-15P	5-15P	5-15P	5-15P	5-15P
Shipping Dimensions W x D x H	34.5" x 29" x 45.5"	62.5" x 31.25" x 42.5"	72.5" x 31.25" x 42.5"	82.5" x 31.25" x 42.5"	98.5" x 31.25" x 42.5"
Shipping Weight	175 lbs.	345 lbs. 310(-S*) lbs.	360 lbs. 350(-S*) lbs.	385 lbs. 375(-S*) lbs.	430 lbs. 420(-S*) lbs.
Refrigerant	R290	R290	R290	R290	R290

*(-S) Stainless Steel Exterior option available - Made to order.

** DD59 will also accommodate (1)1/4 slim keg.



ICE ACCESSORIES

Model Number	Description	For Use With
HS-5061	Drain Pump (Beckett Brand) 1 Year Warranty - Parts & labor (order as accessory)	AM-50BAJ, C-80BAJ, KM-81BAJ, KM-116BAJ
HS-0182	Side Trim Kit	AM-50BAK, C-80BAK
H9320-51 	Recommended Water Filtration - Single Configuration	AM-50BAJ, C-80BAJ, KM-81BAJ, KM-116BAJ, KM-161B_J, KM-231BAJ, KM-301B_J, KM-350M_J, KM-520M_J, KM-660M_J, KMD-410M_J, KMD-505M_J, KMD-530M_J, KMD-705M_J KML-325M_J, KML-500M_J, KML-700M_J, IM-500SAB, IM-200BAC, IM-50BAA-LM, F-300BAJ, F-330BAJ, F-500BAJ, F-450MAJ, F-801M_J, F-1002M_J, F-1501M_J, F-2001M_J, F-330BAJ-C, F-450MAJ-C, F-801M_J-C, F-1002M_J-C, F-1501M_J-C, F-2001MRJ-C, FD-650M_J-C, FD-1002M_J-C, FS-1001MLJ-C, FS-1022MLJ-C, FS-1501MLJ-C
H9320-52 	Recommended Water Filtration - Double Configuration	KM-901M_J, KM-1100M_J, KMD-860M_J, IM-50BAA-Q, KMS-822MLJ, KMS-1122MLJ, KMS-1402MLJ
H9320-53 	Recommended Water Filtration - Triple Configuration	KM-1301S_J, KM-1340M_J, KM-1601MRJ, KM-1601S_J, KM-1900S_J, KM-2200S_J3, KM-2600S_J3, KMH-2100S_J, KMS-2000MLJ
HS-5426	Tamper Proof Kit - Air-Cooled Units	KM-350M_J, KM-520M_J, KM-660M_J
HS-5427	Tamper Proof Kit - Water/Remote Units	KM-520M_J, KM-660M_J
HS-5245	Tamper Proof Kit - Air-Cooled Units	KM-901M_J, KM-1100M_J
HS-5246	Tamper Proof Kit - Water/Remote Units	KM-901M_J, KM-1100M_J
HS-5252	Tamper Proof Kit - Air-Cooled Units	KM-1301S_J, KM-1601S_J
HS-5253	Tamper Proof Kit - Water/Remote Units	KM-1301S_J, KM-1601S_J
HS-5030	Transformer Kit - 4 wire to 3 wire (eliminates need for dedicated neutral)	KM-1340M_J, KM-1601MRJ, KM-1601S_J, KM-1900S_J, KMH-2100S_J
HS-5062	Extension bracket for Freestyle application	KMS-822MLJ
HS-5255	Tamper Proof Kit	KM-2200S_J3, KM-1900S_J
HS-5348	Soft Cubelet Ice Kit	F-1002M_J-C
HS-5396	Soft Cubelet Ice Kit	F-1501M_J-C / F-2001M_J-C
LP-6 LEG	Four 6" Stainless Steel Legs Package available (optional)	F-300BAJ, F-330BAJ, F-500BAJ, F-330BAJ-C, B-250SF, B-500SF, BD-500SF, B-700SF, B-800SF, B-900SF
HS-2120	Cutter head for finer flaked ice	F-801M_J, F-1002M_J
HS-2036	Top Kit for KM-350M, KM-520M or KM-660M	DM-200B
DM Legs	Four 4" Black Die Cast Legs Kit	DM-200B
HS-5329	Top Kit for for FS-1022MLJ-C	DM-4420N
HS-5330	Top Kit for for FD-650M_J-C & FD-1002M_J-C	DM-4420N, IM-500SAB
HS-2033	Order 8" Top Kit to accommodate 22"W ice machines	B-250SF, B-900SF, B-500SF
HS-5429	Bin Door Catch	B-250SF
HS-2035	Order 22" Top Kit to accommodate 30"W ice machines	B-800SF, B-900SF, B-700SF
HS-2032	4" Top Kit to accommodate (2) 22"W ice machines	B-800SF, B-900SF
HS-2132	Top Kit: KMD application	B-900SF
HS-2129	Top Kit: KMD application	B-500SF
HS-2034	Order 14" Top Kit to accommodate 30"W ice machines	B-700SF, B-800SF
HS-2130	Top Kit: KMD application	B-700SF
HS-2066	Seismic Kit for SD 500 Stands	SD Stands
HS-2071	Leg Seismic Kit SD 500 Stands	SD Stands
HS-2150	Quick-Connect Kit (not required if line set is ordered)	URC-5FZ
HS-5604	25' Brazing Required R-404A	URC-9FZ
HS-5505	35' Brazing Required R-404A	URC-9FZ, URC-14FZ
HS-5606	55' Brazing Required R-404A	URC-9FZ, URC-14FZ
HS-5299	25' Brazing Required R-404A	SRC-10J
HS-5300	35' Brazing Required R-404A	SRC-10J
HS-5301	55' Brazing Required R-404A	SRC-10J
HS-5102	Hail Guard Kit	URC-14FZ

HS-0243	25' Brazing Required R-404A	SRK-20J, SRK-20J3
HS-0244	35' Brazing Required R-404A	SRK-20J, SRK-20J3
HS-0245	55' Brazing Required R-404A	SRK-20J, SRK-20J3
HS-5600	Booster Antenna	Remote Monitoring System
HS-5607	Optional Bin Scoop Holder	All SF Bins
HS-5323	25' Brazing Required R-404A	URC-22FZ
HS-5324	35' Brazing Required R-404A	URC-22FZ
HS-5325	55' Brazing Required R-404A	URC-22FZ
HS-5095	Hail Guard Kit	URC-22FZ
HS-0250	25' Brazing Required R-404A	SRK-10J, SRK-12J, SRK-12J3, SRK-15J, SRK-15J3
HS-0251	35' Brazing Required R-404A	SRK-10J, SRK-12J, SRK-12J3, SRK-15J, SRK-15J3
HS-0252	55' Brazing Required R-404A	SRK-10J, SRK-12J, SRK-12J3, SRK-15J, SRK-15J3
HS-5587	Brazed Line Set 25 Ft for URC-5FZ	URC-5FZ
HS-5588	Brazed Line Set 35 Ft for URC-5FZ	URC-5FZ
H9320-54	Single - Medical System	Single Manifold System - Medical

DCM(-OS) & DB DISPENSER ACCESSORIES

Model Number	Description	For Use With
LP-4 LEG	Four 4" Stainless Steel Legs Package available (optional)	DCM-271BAH(-OS)
LP-6 LEG	Four 6" Stainless Steel Legs Package available	DCM-300BAH(-OS), DCM-500BAH(-OS), DCM-75_B_H(-OS), DB-200H
LP-6P LEG	Four 6" Painted Legs Package available	DCM-300BAH(-OS), DCM-500BAH(-OS), DCM-75_B_H(-OS)
LP-6 FLANGE LEG	Four 6" Stainless Steel Legs Package available	DB-130H, B-300SF, BD-300SF, SD Stands
SD-271	Equipment Stand	DCM-271BAH(-OS)
SD-500	Equipment Stand	DCM-300BAH(-OS), DCM-500BAH(-OS)
SD-750	Equipment Stand	DCM-75_B_H(-OS)
HS-2036	Top Kit for KM-350M, KM-520M or KM-660M	DB-200H
HS-2066	Seismic Wall Mount Kit	DCM-300BAH(-OS), DCM-500BAH(-OS)
HS-2067	Seismic Wall Mount Kit	DCM-75_B_H(-OS)
HS-2070	Seismic Wall Mount Kit	DCM-271 BAH(-OS)
HS-2071	Leg Seismic Kit	DCM-300BAH(-OS), DCM-500BAH(-OS)
HS-2072	Leg Seismic Kit	DCM-75_B_H(-OS)
HS-2104	Wall Mount Kit	DCM-271BAH(-OS)
HS-2109	Chute & grill replacement kit	DB-130H, DB-200H
HS-5749	Water Dispense Kit	DB-130H & DB-200H
HS-5559	Round Anti-Microbial Cover (25 mm diameter)	DCM-300BAH, DCM-500BAH, DCM-75_B_H
H9320-54	4H-SI Water Filter Hoshizaki Healthcare Filtration System - Single Configuration	DCM-271BAH, DCM-300BAH, DCM-500BAH, DCM-75_B_H
H9655-08	4H-SI Water Filter Hoshizaki Healthcare Filtration System - Cartridge (1 pk)	DCM-271BAH, DCM-300BAH, DCM-500BAH, DCM-75_B_H



REFRIGERATION ACCESSORIES

CASTERS & LEGS

Model Number	Description	For Use With
HS-3546	4" Casters - Set of four, two with brakes	1/2 Section Uprights
HS-3547	4" Casters - Set of six, three with brakes	3 Section Uprights
HS-5035	4" Casters - Set of four, two with brakes	1, 2 & 3 Section Horizontal Units
HS-5036	6" Casters - Set of four, two with brakes	1, 2 & 3 Section Horizontal Units
HS-5037	2 1/4" Casters - Set of four, two with brakes for ADA Compliant dimensions	1 & 2 Section Undercounters
HS-5320	3 3/8" Casters - Set of four, two with brakes for ADA Compliant dimensions	for pizza preps
HS-5321	3 3/8" Casters - Set of six, three with brakes for ADA Compliant dimensions	for pizza preps
HS-5662	4" Casters with Shims (6pk)	BB80, BB95, BB80-G, BB95-G, CC80, CC95, DD80, DD95
HS-5663	4" Casters with Shims (4pk)	BB59, BB69, BB59-G, BB69-G, CC50, CC65, DD59, DD69
LP-6 LEG	6" Stainless Steel Legs, set of 4	1, 2 & 3 Section Upright Models [3 section needs 2 sets] & pizza preps
LP-6P LEG	6" Painted Leg (grey), set of 4	1, 2 & 3 Section Upright Models [3 section needs 2 sets]& pizza preps

FOOT PEDALS

Model Number	Description	For Use With Steelheart® Models
HS-5378	One Door Foot Pedal (right foot pedal)	Left Hinge - upright, solid door Steelheart® models
HS-5379	One Door Foot Pedal (left foot pedal)	Right Hinge - upright, solid door Steelheart® models
HS-5380	Two Door Foot Pedal	2 & 3 Section Uprights
HS-5555	Left-Hinged Door Foot Pedal (right foot pedal)	Solid door undercounter, worktop and sandwich preps
HS-5556	Right-Hinged Door Foot Pedal (left foot pedal)	Solid door undercounter, worktop and sandwich preps

DOOR REVERSAL KIT

Model Number	Description
HS-5258	Door Reversal Kit - Undercounter Glass Door Models (Right Hinge to Left Hinge)
HS-5259	Door Reversal Kit - Undercounter Glass Door Models (Left Hinge to Right Hinge)

SHELVES

Model Number	Description	For Use With Steelheart® Models
HS-5052	Industrial Strength Epoxy Coated Shelf, Includes 4 Pilaster Clips	1,2,3 Section Uprights
HS-5053	Industrial Strength Epoxy Coated Shelf, 3 each, Includes 12 Pilaster Clips	1,2,3 Section Uprights
HS-5054	Industrial Strength Stainless Steel Shelf, Includes 4 Pilaster Clips	1,2,3 Section Uprights
HS-3504	Industrial Strength Stainless Steel Center Shelf	2 Section Uprights
HS-3505	Industrial Strength Stainless Steel Center Shelf, 3 each	2 Section Uprights
HS-3509	Industrial Strength Epoxy Coated Shelf Center Shelf	2 Section Uprights
HS-3510	Industrial Strength Epoxy Coated Shelf Center Shelf, 3 each	2 Section Uprights
HS-3550	Pass-Thru Epoxy Shelf, 3 pack	1 & 2 Section Pass-Thrus
HS-3551	Pass-Thru Epoxy Shelf, 1 pack	1 & 2 Section Pass-Thrus
HS-3552	Pass-Thru Stainless Steel Shelf, 3 Pack	1 & 2 Section Pass-Thrus
HS-3553	Pass-Thru Stainless Steel Shelf, 1 Pack	1 & 2 Section Pass-Thrus
HS-5388	Industrial Strength Epoxy Coated Shelf Center Shelf, 1 each	3 Section Uprights
HS-5389	Industrial Strength Epoxy Coated Shelf Center Shelf, 3 each	3 Section Uprights
HS-5057	Tempered Glass Shelves, 3 each	For use with HR24C-G
HS-5058	Epoxy Coated Wire Shelf, Includes 4 Pilaster Clips	All 27" and 72" Undercounters, Worktops and Preps
HS-5235	Epoxy Coated Wire Shelf, Includes 4 Pilaster Clips	All 36" Undercounters, Worktops and Preps
HS-5059	Epoxy Coated Wire Shelf, Includes 4 Pilaster Clips	All 48" Undercounters, Worktops and Preps
HS-5108	Epoxy Coated Wire Shelf, Includes 4 Pilaster Clips	All 60" Undercounters, Worktops and Preps
HS-5116	Stainless Steel Shelf, Includes 4 Pilaster Clips	All 27" and 72" Undercounters, Worktops and Preps
HS-5117	Stainless Steel Shelf, Includes 4 Pilaster Clips	All 48" Undercounters, Worktops and Preps
HS-5118	Stainless Steel Shelf, Includes 4 Pilaster Clips	All 60" Undercounters, Worktops and Preps
HS-5151	Epoxy Coated Wire Shelf, Includes 4 Pilaster Clips	PR67/93B
HS-5152	Epoxy Coated Wire Shelf, Includes 4 Pilaster Clips	PR46B
HS-5153	Stainless Steel Shelf, Includes 4 Pilaster Clips	PR67/93B
HS-5154	Stainless Steel Shelf, Includes 4 Pilaster Clips	PR46B
HS-5169	Lower Stainless Steel Shelf, 4 Pilaster Clips	All 27" Undercounters, Worktops, and Preps
HS-5580	Stainless shelves - 1 pk	PR60B

SHELVES - CONTINUED

HS-5579	Additional epoxy shelf - 1 pk	PR60B
HS-5592	Standard wooden wine rack shelves	HR-15
HS-5593	Small wooden wine rack shelves	HR-24
HS-5594	Large wooden wine rack shelves	HR-24
HS-5595	Complete wine shelf set for HR-15 (set of 4 wood shelves with 4 slidina rails)	HR-15
HS-5596	Complete wine shelf set for HR-24 (set of 5 wood)	HR-24
HS-5614	Narrow Unit Shelves (Epoxy, 1 pack)	FSN models
HS-5658	Narrow Unit Shelves (Epoxy, 1 pack)	FSN models
HS-5679	Narrow Unit Shelves (SS, 1 pack)	FSN models
HS-5680	Narrow Unit Shelves (SS, 3 pack)	FSN models

OVERSHELVES

Model Number	Description	For Use With
HS-5172	Single Overshelf for 27" Cabinet	27" Undercounters, Worktops, Sandwich Preps & Mega Top
HS-5237	Single Overshelf for 36" Cabinet	36" Undercounters, Worktops, Sandwich Preps & Mega Top
HS-5229[†]	Single Overshelf for 46" / 93" Pizza Cabinet	46" / 93" Pizza Preps - cabinets can accommodate (2) HS-5229 Single Overshelves or (2) HS-5228 Double Overshelves.
HS-5173	Single Overshelf for 48" Cabinet	48" Undercounters, Worktops, Sandwich Preps & Mega Top
HS-5174	Single Overshelf for 60" Cabinet	60" Undercounters, Worktops, Sandwich Preps & Mega Top
HS-5639	Single Overshelf for 60" Pizza Cabinet	60" Pizza Cabinet
HS-5231[†]	Single Overshelf for 67" Pizza Cabinet	67" Pizza Cabinet
HS-5175	Single Overshelf for 72" Cabinet	72" Undercounters, Worktops, Sandwich Preps & Mega Top
HS-5163	Double Overshelf for 27" Cabinet	27" Undercounters, Worktops, Sandwich Preps & Mega Top
HS-5236	Double Overshelf for 36" Cabinet	36" Undercounters, Worktops, Sandwich Preps & Mega Top
HS-5228[†]	Double Overshelf for 46" / 93" Cabinet	46" / 93" Pizza Prep Preps 93" cabinets can accommodate (2) HS-5229 Single Overshelves
HS-5164	Double Overshelf for 48" Cabinet	48" Undercounters, Worktops, Sandwich Preps & Mega Top
HS-5165[†]	Double Overshelf for 60" Cabinet	60" Undercounters, Worktops, Sandwich Preps & Mega Top
HS-5640	Double Overshelf for 60" Cabinet	60" Pizza Preps
HS-5230[†]	Double Overshelf for 67" Cabinet	67" Pizza Prepss
HS-5166[†]	Double Overshelf for 72" Cabinet	72" Undercounters, Worktops, Sandwich Preps & Mega Top

[†]Compatible with models manufactured since March 2016. (Serial # FXXXXXC and after) / [†]Compatible with models manufactured since January 2017. (Serial # GXXXXXA and after) / * 93" cabinets can accommodate (2) HS-5229 Single Overshelves or (2) HS-5228 Double Overshelves.

TRAY / PAN SLIDES

(16) Sets on 3" Centers per section is the recommended maximum capacity for Uprights. Units can hold as many as (24) sets on 2" Centers per section.

Model Number	Description	For Use With
HS-3557	Stainless Steel Bottom Support Universal Pan Slides (1 Set), Includes 4 Pilaster Clips	Steelheart models
HS-3558	Stainless Steel Bottom Support Universal Pan Slides (4 Sets), Includes 16 Pilaster Clips	Steelheart models
HS-5092	Stainless Steel Bottom Support Wire Tray Slides (1 Set) for 18x26 Baker Pan Only, Includes 4 Pilaster Clips	Steelheart models
HS-5093	Stainless Steel Bottom Support Wire Tray Slides (4 Sets) for 18x26 Baker Pan Only, Includes 16 Pilaster Clips	Steelheart models

PIZZA PREP TABLES - PAN SLIDES

Model Number	Description
HS-5514	Removable Tray Pan Rack For Pizza Preps- Accommodates (6) 18" x 26" Sheet Pans With 3" Spacing

FLAT LIFT OFF COVERS

Model Number	Description	For Use With
HS-5070	Flat Lift-Off Stainless Steel Cover - 12 pan Mega Top opening	SR27B-12M, SR48B-12MD4 SR48B-12M, SR60B-12M, *SR60B-24M, *SR72B-24M, SR27B-12MD, *SR60B-24MD4 (*2 of each cover required per model)
HS-5279	Flat Lift-Off Stainless Steel Cover - 15 pan Mega Top opening	SR36B-15M
HS-5071	Flat Lift-Off Stainless Steel Cover - 18 pan Mega Top opening	SR48B-18M, SR60B-18M, SR72B-18M, SR48B-18MD4
HS-5072	Flat Lift-Off Stainless Steel Cover	SR27B-8, SR27B-8D
HS-5073	Flat Lift-Off Stainless Steel Cover	SR48B-8, SR60B-8
HS-5278	Flat Lift-Off Stainless Steel Cover - 10 pan Sandwich Top opening	SR36B-10
HS-5074	Flat Lift-Off Stainless Steel Cover - 12 pan Sandwich Top opening	SR48B-12, SR60B-12, SR72B-12
HS-5106	Flat Lift-Off Stainless Steel Cover	SR60B-16, SR72B-16
HS-5107	Flat Lift-Off Stainless Steel Cover	SR72B-18
HS-5070 + HS-5071	Flat Lift-Off Stainless Steel Cover - 12 pan Mega Top opening Flat Lift-Off Stainless Steel Cover - 18 pan Mega Top opening	SR72B-30M, SR72B-30MD6 (1 of each cover required per model)

COMPOSITE CUTTING BOARDS

Model Number	Description	For Use With
HS-5202	Dual Rear Cutting Board	
HS-5265	10" x 27" x 1/2" Composite Cutting Board	27" Sandwich Preps & Mega Top
HS-5266	10" x 36" x 1/2" Composite Cutting Board	36" Sandwich Preps & Mega Top
HS-5267	10" x 48" x 1/2" Composite Cutting Board	48" Sandwich Preps & Mega Top
HS-5268	10" x 60" x 1/2" Composite Cutting Board	60" Sandwich Preps & Mega Top
HS-5269	10" x 72" x 1/2" Composite Cutting Board	72" Sandwich Preps & Mega Top
HS-5270	19" x 46" x 1/2" Composite Cutting Board	46" Pizza Preps
HS-5271	19" x 67" x 1/2" Composite Cutting Board	67" Pizza Preps
HS-5272	19" x 93" x 1/2" Composite Cutting Board	93" Pizza Preps

GLASS DOOR MERCHANDISER ACCESSORIES

Model Number	Description	For Use With
HS-5446	Organizer Shelf With Tracks, Includes 4 Pilaster Clips	RM-10-HC
HS-5291	Organizer Shelf With Tracks, Includes 4 Pilaster Clips	RM-26-HC
HS-5293	Organizer Shelf With Tracks, Includes 4 Pilaster Clips	RM-45-SD-HC
HS-5295	Organizer Shelf With Tracks, Includes 4 Pilaster Clips	RM-49-HC
HS-5290	Price Tag Holder	RM-10-HC
HS-5292	Price Tag Holder	RM-26-HC
HS-5294	Price Tag Holder	RM-45-SD-HC
HS-5296	Price Tag Holder	RM-49-HC
HS-5447	Epoxy Shelf, Includes 4 Pilaster Clips	RM-10-HC
HS-5317	Epoxy Shelf, Includes 4 Pilaster Clips	RM-26-HC
HS-5318	Epoxy Shelf, Includes 4 Pilaster Clips	RM-45-SD-HC
HS-5319	Epoxy Shelf, Includes 4 Pilaster Clips	RM-49-HC
HS-5343	Epoxy Shelf, Includes 4 Pilaster Clips	RM-7-HC
HS-5344	Epoxy Floor Shelf	RM-7-HC
HS-5288	4" Casters-Set Of Four, Two With Brakes	RM-10-HC, RM-26-HC, RM-45-SD-HC, RM-49-HC
HS-5460	Flat Epoxy coated shelf, RM-65-HC Middle Section	RM-65-HC
HS-5461	Flat Epoxy coated shelf, RM-65-HC Right & Left Section	RM-65-HC
HS-5465	Organizer Shelf with Tracks, Middle Section	RM-65-HC
HS-5466	Organizer Shelf with Tracks, Right & Left Section	RM-65-HC

BACK BAR ACCESSORIES

Model Number	Description	For Use With
HS-5410	Complete Door Assembly-Solid, Right Hinge	All Back Bar and Direct Draw Models except DD24
HS-5411	Complete Door Assembly-Solid, Left Hinge	All Back Bar and Direct Draw Models except DD24, BB80, BB80-G, DD80
HS-5412	Complete Door Left Section Assembly-Solid, Left Hinge 80"	BB80, BB80-G, DD80
HS-5413	Complete Door Assembly-Glass, Right Hinge	All Back Bar and Direct Draw Models except DD24
HS-5414	Complete Door Assembly-Glass, Left Hinge	BB59, BB69, BB95, BB59-G, BB69-G, DD59, DD69, DD95
HS-5415	Complete Door Left Section Assembly-Glass, Left Hinge 80"	BB80, BB80-G, DD80
HS-5417	Flat Shelf, 59" & Right 80" Cabinets, 21.25" x 21.4", Includes 4 SS pilaster clips	BB59, BB59-G, DD59, (Right Section) BB80, BB80-G, DD80
HS-5418	Flat Shelf, 69" & 95" Cabinets, 26" x 21.4", Includes 4 SS pilaster clips	BB69, BB69-G, BB95, DD69, DD95, BB95-G
HS-5419	Flat Shelf Center, 80" Cabinets, 23.1" x 21.4", Includes 4 SS pilaster clips	(Center) BB80, BB80-G, DD80
HS-5420	Flat Shelf Left, 80" Cabinets, 18" x 21.4", Includes 4 SS pilaster clips	(Left Section) BB80, BB80-G, DD80
HS-5421	Set of 4 Pilasters 20.2"	All Back Bar and Direct Draw Models
HS-5515	Bottle Dividers for Back Bar Shelves, 6 Pack with 12 clips	BB59, BB69, BB80, BB95, BB59-G, BB69-G, BB80-G, BB95-G
HS-5662	4" Casters with Shims (6pk)	BB80, BB95, BB80-G, BB95-G, CC80, CC95, DD80, DD95
HS-5663	4" Casters with Shims (4pk)	BB59, BB69, BB59-G, BB69-G, CC50, CC65, DD59, DD69

ECONOMY SERIES

Model Number	Description	For Use With
HS-5511	Flat Shelf Economy Series 1 Section Uprights with clips	Refrigerator, Freezer
HS-5512	Flat Shelf Economy Series 2 Section Uprights with clips	Refrigerator, Freezer

MISCELLANEOUS ACCESSORIES

Model Number	Description	For Use With
HS-4007	Narrow drawer Assembly Divider Bar (Accommodates 1/2, 1/3 and 1/6 Size Pans)	Undercounters, Worktops, Prep Tables, Equipment Stands
HS-5534	12" Rail Divider Bar - Standard Pan Divider Bar for Pizza Prep Tables	Prep Tables

MISCELLANEOUS ACCESSORIES - CONTINUED

HS-5069	Sandwich Top Rail Adapter Bar - 12.6" x 1.0" (front to back)	Sandwich Preps & Mega Top Prep Tables
HS-5280	Full Size Pan Adapter Bar for UR27B-8 Rail	Sandwich Preps
HS-5281	Full Size Pan Adapter Bar for SR36B-10 Rail	Sandwich Preps
HS-5476	Black kickplate for HR15A, HR15A-G	HR15A, HR15A-G
HS-5112	Stacking Kit - UR27B & UF27B	Undercounters
HS-5170	Stainless Steel Back Panel	Worktops, Sandwich Preps & Pizza Preps
HS-5184	All Mega Top divider front to back	Mega Top Prep Tables
HS-5185	All Mega Top & Sandwich Prep 27-8 divider side to side (outer)	Sandwich Preps & Mega Top Prep Tables
HS-5186	Mega Top 18M & 30M divider side to side (center)	Mega Top Prep Tables
HS-5187	Sandwich Prep 27-8 divider front to back	Sandwich Preps Preps
HS-5188	Sandwich Prep 48-8 and 12, 16, 18 pan openings divider front to back	Sandwich Preps Preps
HS-5189	Sandwich Prep 48-8 and 12, 16, 18 pan openings side to side (outer)	Sandwich Preps Preps
HS-5190	Sandwich Prep 12 & 16 pan openings side to side (center)	Sandwich Preps Preps
HS-5191	Sandwich Prep 18 pan openings side to side (outer)	Sandwich Preps Preps
HS-5192	Sandwich Prep 18 pan openings side to side (center)	Sandwich Preps Preps
HS-5453	Heated Condensate Pan Kit	≥46" Undercounter, Worktop and Preps
HS-5462	Heated Condensate Pan	Steelheart® Uprights
HS-5525	Stainless Steel Rear Panel for 2 Section Upright, (factory installed only)	Steelheart® Uprights
HS-5526	Stainless Steel Rear Panel for 1 Section Upright, (factory installed only)	Steelheart® Uprights
HS-5496	Stainless Steel Rear Panel for DT1A (factory installed only)	Steelheart® Uprights
HS-5497	Stainless Steel Rear Panel for DT2A (factory installed only)	Steelheart® Uprights
HS-5449	14" cutting board brackets	SR48, 60 A-Series
HS-5530	Stacking Kit (Need 2 for stacked 3 high)	IM-500
HS-5585	14" cutting boards Brackets	SR48B & SR60B Models
HS-5601	Dual Rear Cutting board	SR60B-18M
HS-5626	Stainless Steel Panel Overlay Kit	48" B Series Refrigerator and Freezers, Undercounter, Worktop, Sandwich Preps, Mega Top Prep Models - FACTORY INSTALLED
HS-5620	Stainless Steel Panel Overlay Kit	27" B Series Refrigerator Undercounter, Worktop, Sandwich Preps, Mega Top Prep Models - FACTORY INSTALLED
HS-5621	Stainless Steel Panel Overlay Kit	UR27B-GLP01 Refrigerator Undercounter - FACTORY INSTALLED
HS-5622	Stainless Steel Panel Overlay Kit	27" B Series Freezer Undercounter and Worktop Models - FACTORY INSTALLED
HS-5624	Stainless Steel Panel Overlay Kit	UF27B-GLP01 Freezer Undercounter - FACTORY INSTALLED
HS-5625	Stainless Steel Panel Overlay Kit	36" B Series Undercounter and Worktop Refrigerator Models - FACTORY INSTALLED
HS-5627	Stainless Steel Panel Overlay Kit	UR48B-GLP01 Refrigerator Undercounter - FACTORY INSTALLED
HS-5628	Stainless Steel Panel Overlay Kit	72" B Series Refrigerator Undercounter, Worktop, Sandwich Preps, Mega Top Prep Models - FACTORY INSTALLED
HS-5630	Stainless Steel Panel Overlay Kit	60" B Series Refrigerator and Freezer Undercounter, Worktop, Sandwich Preps, Mega Top Prep Models - FACTORY INSTALLED
HS-5611	Stainless Steel Panel Overlay Kit	60" B Series Undercounter, Worktop, Sandwich Preps, Mega Top Prep Models - FACTORY INSTALLED
HS-5651	Rail Dividers for 1/6 size pans	PR46B
HS-5652	Rail Dividers for 1/6 size pans	PR60B
HS-5653	Rail Dividers for 1/6 size pans	PR67B
HS-5654	Rail Dividers for 1/6 size pans	PR93B
HS-5692	Drawer Dividers	PR60B
HS-5693	Drawer Dividers	PR46B, PR67B, PR93B
HS-5518	Narrow Dividers for Rubbermaid Pans	SR27B-8, SR27B-D2, SR48B-8, SR60B-8 models
HS-5519	Narrow Dividers for Rubbermaid Pans	SR27B-12M, SR27B-12MD2, SR48B-12, SR48B-12M, SR48B-12D2, SR48B-12D4, SR60B-12, SR60B-12M, SR72B-12, SR72B-12M models
HS-5521	Narrow Dividers for Rubbermaid Pans	SR60B-16, SR72B-16 models
HS-5522	Narrow Dividers for Rubermaid Pans	SR72B-18, SR60B-18M, SR72B-18M, SR48B-18MD4
HS-5655	Epoxy-Coated Wine Shelf	Steelheart® Single Section (1 pk)
HS-5656	Stainless Steel Wine Shelf	Steelheart® Single Section (1 pk)
HS-5691	Pizza Prep Table: Horizontal drawer divider bar	Pizza Prep 46", 67", & 93" models

MODEL NUMBER IDENTIFICATION | ICE



F - 450 M A J - (C)

Series Identification

KM/D/H/L/S	crescent® Ice Machine
DKM	crescent® Ice Machine/Dispenser
AM	“Top Hat” Ice Machine
F	Flaker Ice Machine
C/FS/FD	Cubelet Ice Machine
DCM	Cubelet Ice Machine/Dispenser
DWM	Water Dispenser
IM	Specialty Cube Ice Machine

Ice Production per 24 hours

Configuration

B	Icemaker with Built-In Storage
M	Modular Icemaker
S	Stackable Icemaker

Condenser Style

A	Air-Cooled Condenser
W	Water-Cooled Condenser
R	Remote Air-Cooled Condenser
L	Low Side / Serenity Series

Series Modification

Changes and improvements noted by next letter of the alphabet

Electrical Phase

3

denotes
Cubelet Ice
Machine

F-450MAJ-C

Flaker

450 lbs./24-hrs.

Modular

Air-Cooled

Series Modification (J)

Single Phase

Cubelet Ice

MODEL NUMBER IDENTIFICATION | REACH-INS

HORIZONTAL REFRIGERATION | MODEL NUMBER IDENTIFICATION CODE

S R 48 A - 18MD2

Series Identification

- U** Undercounter
- W** Worktop
- S** Sandwich Prep/Mega Top
- P** Pizza Prep
- C** Chef Base

Model Identification

- R** Refrigerator
- F** Freezer

Unit Width

- ##** In Inches

Series Modification

- A** Alphabetically increases per model revisions

Options Configuration

- LP / -D** Low Profile / Drawers
- # / -#D#** Number of 1/6 Sized Pan Capacity / Number of 1/6 Sized Pan Capacity with Number of Drawers in Sandwich Prep
- #M/ -#MD#** Number of 1/6 Sized Pan Capacity / Number of 1/6 Sized Pan Capacity with Number of Drawers in Mega Top
- 01** Unit with Cylinder Lock

SR48A-18MD2

Mega Top Prep Table,
Refrigerator,
48" Wide,
Revision A*,

(18) 1/6 Sized Pan Capacity in Rail,
Door and 2 Drawers*

*The series modification letter can be generally ignored when talking about the unit, this letter is important if you are getting Tech Support or ordering service parts.



UPRIGHT REFRIGERATION | MODEL NUMBER IDENTIFICATION CODE

R 1 A - FS - FS
PT & RT ONLY

Model Identification

- R** Refrigerator
- F** Freezer
- DT** Dual Temp
- PT** Pass Thru
- RN** Roll In
- RT** Roll Thru

Number of Sections

- 1 / 2 / 3** One, Two, or Three Sections

Series Modification

- A** Alphabetically increases per model revisions

Door Configuration

- FS / -HS** Full Height or Half Height Stainless Door
- FG / -HG** Full Height or Half Height Glass Door
- FSL / -HSL** Full Height or Half Height Stainless Door, Left-Hand Hinge

R1A-FS

Upright Refrigerator,
One Section
Revision A*,

Full Stainless Door

*The series modification letter can be generally ignored when talking about the unit, this letter is important if you are getting Tech Support or ordering service parts.





HOSHIZAKI

SERVICE & SUPPORT

Whether you need product resources, technical support, or service assistance, Hoshizaki's support team is ready to help.

Explore our tools and resources to keep your equipment running at peak performance.

Registration & Warranty



Register your equipment to activate your warranty and access product information.



Manuals & Guides



Access product manuals, spec sheets, and warranty statements for current and previous models.



Parts Manual Lookup



Browse interactive parts diagrams to identify the right parts for your products.



Training & FAQs



Explore our in-person and virtual training classes, or browse FAQs.



Find a Service Rep



Need maintenance or repairs? Locate an authorized Hoshizaki service representative near you.



KCL CAD / Revit Files



Access CAD and Revit files for Hoshizaki equipment to streamline your design and planning process.



Technical Support Videos



View essential technical training focused on operations and diagnostics of Hoshizaki equipment.



WARRANTY

Below are general warranty terms for currently produced units and do not represent the full scope or terms of the manufacturer's warranty. Product lines listed below are for reference and list is not intended to be fully-inclusive of all models warrantied.

For specific terms and warranty [Lookup by Model](#) or [Serial Number](#) please visit: www.hoshizakiamerica.com/support/warranty



Scan for Warranty
information

TERMS and CONDITIONS

TERMS: Terms are such as the company may extend to the purchaser.

LOST OR DAMAGED SHIPMENTS: Whenever seller shall deliver or cause to be delivered to a common carrier any goods ordered by consignee, whether the particular common carrier shall have been designated in the shipping instructions of the consignee or not, seller shall not be responsible for any delays or damage in shipment and the common carrier to which seller shall deliver goods shipped to the consignee is hereby declared to the agent of the consignee. Therefore, it is the responsibility of the consignee to file claim with the carrier for lost or damaged shipments.

ICE MACHINE WARRANTIES

All units to be free from manufacturing defects, covered by:

KMEdge™ Series Cubers, Ice Machine & Dispenser and DB/DM Hotel/Motel Dispensers

- 3-Year - Parts & Labor on Entire Machine
- 5-Year - Parts & Labor on Evaporator,
- 5-Year - Parts on Compressor, Air-Cooled Condenser Coil

AM-50 Series Cubers & C-80 Flakers

- 2-Year - Parts & Labor on Entire Machine

IM Series Cubers (Specialty Ice)

- 3-Year - Parts & Labor on Entire Machine
- 5-Year - Parts on Compressor and Air-Cooled Condenser Coil

Flakers and Cubelet Ice Machines, DCM Ice & Water Dispensers

- 3-Year - Parts & Labor on Entire Machine
- 5-Year - Parts on Compressor and Air-Cooled Condenser Coil

Bins

- 3-Year - Parts & Labor on Bins <1,000lbs. storage
- 5-Year - Parts & Labor on iBns >1,000lbs. storage

Accessories

- 90 Day - Parts only
- 1-Year - HS-5061 Drain Pump (Beckett Brand) - Parts & Labor
- 1-Year - Water Filter System & Replaceable Elements

REACH-IN WARRANTIES

All units to be free from manufacturing defects, covered by:

Steelheart® Series Refrigerators & Freezers

- 7-Year - Labor on Entire Machine
- 7-Year - Parts on Entire Machine
- 7-year - Parts on Compressor

Compact Undercounter Refrigerators, HR-Series & Back Bar Refrigerators & Glass Door Merchandisers

- 3-Year - Parts & Labor on Entire Machine
- 5-Year - Parts on Compressor

Valiance® Refrigeration Series

- 3-Year - Labor on entire machine
- 4-Year - Parts on entire machine
- 5-year - Parts on Compressor

Countertop Refrigerated Display Cases (Sushi)

- 1-Year - Parts & Labor on Entire Machine
- 2-Year - Parts & Labor on Compressor, Evaporator, Air-Cooled Condenser
- 5-Year - Parts on Compressor, Air-Cooled Condenser

Warranty valid in United States, Canada, Puerto Rico, & U.S. Territories only. Contact factory for warranty in other countries. Refer to manufacturer's full warranty for complete details.



HOSHIZAKI

HOSHIZAKI AMERICA, INC.



HOSHIZAKI ALLIANCE

EXCELLENCE
ACROSS THE
AMERICAS



LANCER **MACOM** **FOGEL**

HOSHIZAKI AMERICA INC., is a proud member of The Hoshizaki Alliance, a group of sister-companies Equipping People with Total Foodservice Solutions Through Trust, Quality, and Connection Across the Americas

HOSHIZAKI AMERICA, INC.
618 Highway 74 South, Peachtree City, GA 30269
Toll Free: (800) 438-6087 | Fax: (800) 345-1325
www.hoshizakiamerica.com